



BeyondTrust

Privilege Management Cloud 22.8 API Guide - Version 1

Table of Contents

Privilege Management Cloud API - Version 1	11
Authenticate to the PM Cloud API	11
Methods	13
AcceptedDomains	15
ActivityAudits	21
AuthorizationRequestAudits	28
Computers	33
Events	48
File	92
Groups	92
Policies	107
Roles	117
ScimResourceTypes	119
ScimSchemas	121
ScimServiceProviderConfig	125
ScimUsers	126
Tasks	134
Users	135
Models	148
AcceptedDomainDetailModel	154
AcceptedDomainListItemModel	154
ActivityAuditDetailModel	155
ActivityAuditDetailModelPagedResponse	156
ActivityAuditListItemModel	156
ActivityAuditListItemModelPagedResponse	157
ActivityAuditRoleNameModel	157
ActivityAuditRoleResourceModel	157
Agent	158
AgentBuild	158
AgentHostType	158
ApiClientDataAuditingDetailModel	159

Application	159
Applicationgroup	159
As	160
AsOrganization	160
AssignComputersToGroupRequest	160
AssignPolicyRevisionToGroupRequest	160
AssignUserToRoleRequest	161
Attribute	161
Authorization	162
AuthorizationRequestAuditDetailModel	162
AuthorizationRequestAuditDetailModelPagedResponse	163
AuthorizationRequestAuditListItemModel	163
AuthorizationRequestAuditListItemModelPagedResponse	164
Authorizationrequest	164
Authorizinguser	164
Base	165
Bundle	165
CertificateInformationModel	165
ChangedBy	166
Client	166
ClientNat	167
Cloud	167
CloudAccount	167
CloudInstance	168
CloudMachine	168
CloudOrigin	168
CloudProject	169
CloudService	169
CloudTarget	169
CodeSignature	170
Com	170
ComputerDataAuditingDetailModel	170
ComputerDetailModel	171

ComputerFilterModel	172
ComputerListItemModel	173
ComputerListItemModelPagedResponse	175
ComputerLogModel	175
ComputerRenewCertificateRequest	175
ComputerRetrieveLogsRequest	175
ComputerRetrieveStatusInfoRequest	176
ComputersAuthoriseRequest	176
ComputersDeactivateRequest	176
ComputersRejectRequest	176
ComputersRemoveRequest	177
Configuration	177
Container	178
ContainerCpu	179
ContainerDisk	179
ContainerDiskRead	179
ContainerDiskWrite	179
ContainerImage	179
ContainerImageHash	180
ContainerMemory	180
ContainerNetwork	180
ContainerNetworkEgress	180
ContainerNetworkIngress	180
Content	181
Contentgroup	181
CountRange	181
CreateAcceptedDomainRequest	181
CreateGroupRequest	182
CreateUserRequest	182
DataStream	182
DateFilterModel	183
DateSelectionMode	183
Destination	183

DestinationNat	184
Dll	184
Dns	185
DnsQuestion	185
Ecs	186
Elf	186
ElfHeader	186
ElfSections	187
ElfSegments	188
Email	188
EmailAttachments	189
EmailAttachmentsFile	189
EmailBcc	189
EmailCc	189
EmailFrom	190
EmailReplyTo	190
EmailSender	190
EmailTo	190
EndpointInformationModel	190
EpmEcsEvent	192
EpmEcsEventResponseModel	194
Epmwinmac	194
Error	195
Event	195
FaaS	195
FaaSTrigger	196
File	196
Geo	198
GeoPoint	198
Gpo	199
Group	199
GroupDataAuditingDetailModel	199
GroupListItemModel	200

GroupListItemModelPagedResponse	201
Hash	201
Host	202
HostBoot	203
HostCpu	203
HostDisk	203
HostDiskRead	203
HostDiskWrite	203
HostNetwork	204
HostNetworkEgress	204
HostNetworkIngress	204
Http	204
HttpRequest	205
HttpRequestBody	205
HttpResponse	205
HttpResponseBody	206
InstallationKeyDataAuditingDetailModel	206
ListItemErrorInfoModel	206
Log	207
LogFile	207
LogOrigin	207
LogOriginFile	207
Message	208
ModifyAcceptedDomainRequest	208
ModifyGroupRequest	208
ModifyPolicyRequest	208
ModifyUserPreferencesRequest	209
ModifyUserRequest	209
Network	209
OS	210
Observer	210
OperationValue	211
Operator	212

Orchestrator	212
OrchestratorCluster	212
OrchestratorResource	213
OrchestratorResourceParent	213
Organization	213
Os	213
Owner	214
Package	214
Pe	215
PolicyDataAuditingDetailModel	216
PolicyGroupsListItemModel	216
PolicyListItemModel	216
PolicyListItemModelPagedResponse	218
PolicyRevisionDataAuditingDetailModel	218
PolicyRevisionModel	218
PolicyRevisionState	219
Privilegedgroup	219
ProblemDetails	219
Process	220
ProcessEntryLeader	222
ProcessEntryMeta	223
ProcessGroupLeader	224
ProcessParent	225
ProcessPrevious	227
ProcessSessionLeader	229
ProcessThread	231
Registry	231
RegistryData	231
Related	231
RoleElement	232
RoleItemModel	232
RoleListItemModel	232
RoleModel	233

RolePermissionModel	233
Rule	233
Rulescript	234
RulescriptOutcome	234
SCIMEmail	234
SCIMUserName	235
ScimAuthenticationSchemes	235
ScimBulk	235
ScimOperation	236
ScimResourceMeta	236
ScimResourceResponse	236
ScimResourceResponseScimListResponse	237
ScimSchemaResponse	237
ScimSchemaResponseScimListResponse	237
ScimServiceProviderConfigResponse	238
ScimSupported	238
ScimUserMetaModel	239
ScimUserModel	239
ScimUserModelScimListResponse	240
ScimUserPatchRequest	240
Server	240
ServerNat	241
Service	241
ServiceNode	242
ServiceOrigin	242
ServiceTarget	243
Session	243
SettingDataAuditingDetailModel	244
SortDirection	244
SortModel	244
Source	245
SourceNat	245
SubAttribute	246

TaskDetailModel	246
Threat	247
ThreatEnrichments	247
ThreatEnrichmentsMatched	248
ThreatFeed	248
ThreatGroup	248
ThreatIndicator	249
ThreatIndicatorEmail	250
ThreatIndicatorMarking	250
ThreatSoftware	250
ThreatTactic	251
ThreatTechnique	251
ThreatTechniqueSubtechnique	251
Tls	251
TlsClient	252
TlsClientHash	253
TlsServer	253
TlsServerHash	254
Token	254
Tracing	254
TracingSpan	254
TracingTrace	255
TracingTransaction	255
UnassignComputersToGroupRequest	255
Url	255
User	256
UserAgent	257
UserAgentDevice	257
UserChanges	257
UserDataAuditing	258
UserDetailModel	259
UserEffective	259
UserListItemModel	260


UserListItemModelPagedResponse	261
UserRoleResourceItemModel	261
UserTarget	262
Vlan	262
Vulnerability	262
VulnerabilityScanner	263
VulnerabilityScore	263
Workstyle	264
X509	264
X509Issuer	265
X509Subject	265
_event	266
_rule	267
id_AssignComputersByCsv_body	268

Privilege Management Cloud API - Version 1

Authenticate to the PM Cloud API

API requests are executed by sending an HTTP request to PM Cloud. Send the request using any HTTPS-capable socket library or scripting language module, URL fetcher such as cURL, or an OAuth library specific to your platform. BeyondTrust's web APIs use OAuth as the authentication method.

To authenticate to the API, you must create an API account on the **Configuration > Settings > API Settings** page. The account must have permission to access the necessary APIs. API requests require a token to be first created and then submitted with each API request.

 For more information about creating an API account, please see [Configure Access to the Management API](#) in the *Privilege Management Cloud Administration Guide*.

Create a Token

Create a token by POSTing to the URL of your BeyondTrust site followed by `/oauth/connect/token`:

```
https://example-services.pm.beyondtrustcloud.com/oauth/connect/token
```

Replace "example" with your production sub-domain name, as shown:


```
https://[yourProductionSub-domainName]-services.pm.beyondtrustcloud.com/oauth/connect/token
```

The OAuth client ID and client secret associated with the API account should be included in the POST body:

```
grant_type=client_credentials&client_id=[yourClientId]&client_secret=[yourGeneratedClientSecret]
```

If the request is processed without error, you will get an access token JSON response:

```
{
  "access_token": "<token>",
  "token_type": "Bearer",
  "expires_in": 3600,
  "scope": "urn:management:api"
}
```

 **Note:** The client secret cannot be modified, but it can be regenerated on the **Configuration > Settings > API Settings** page. Regenerating a client secret and then saving the account immediately invalidates any OAuth tokens associated with the account. Any API calls using those tokens will be unable to access the API. A new token must be generated using the new client secret.

Request an API Resource

Now that you have an access token, you can make GET/POST requests via HTTPS to the web API:

```
https://example-services.pm.beyondtrustcloud.com/management-api/v1/Groups
```

The obtained token is used for HTTP authentication and must be included in an HTTP authorization header with each request:

```
Authorization: Bearer <token>
```

If the token is valid, you gain access to the requested URL.

Authentication Errors

Requests made to the web API with expired or invalid tokens result in a "HTTP 401 Unauthorized" response.

Methods

[[Jump to Models](#)]

Table of Contents

AcceptedDomains

- [get /v1/AcceptedDomains](#)
- [delete /v1/AcceptedDomains/{id}](#)
- [get /v1/AcceptedDomains/{id}](#)
- [put /v1/AcceptedDomains/{id}](#)
- [post /v1/AcceptedDomains](#)

ActivityAudits

- [get /v1/ActivityAudits](#)
- [get /v1/ActivityAudits/{id}](#)

AuthorizationRequestAudits

- [get /v1/AuthorizationRequestAudits](#)
- [get /v1/AuthorizationRequestAudits/{id}](#)

Computers

- [post /v1/Computers/Authorise](#)
- [post /v1/Computers/Certificate/Renew](#)
- [post /v1/Computers/Deactivate](#)
- [delete /v1/Computers](#)
- [post /v1/Computers/Details/Request](#)
- [get /v1/Computers](#)
- [get /v1/Computers/{id}/CommandLog](#)
- [get /v1/Computers/{id}](#)
- [get /v1/Computers/{id}/Logs](#)
- [get /v1/Computers/Logs/{id}/Content](#)
- [post /v1/Computers/Logs/Request](#)
- [post /v1/Computers/Reject](#)

Events

- [get /v1/Events/FromStartDate](#)

File

- [get /v1/File/download/GetYamlApiDefinitionFile](#)

Groups

- [post /v1/Groups/AutoAssignPolicyRevision](#)
- [get /v1/Groups](#)
- [post /v1/Groups/{id}/AssignComputersByCsv](#)
- [post /v1/Groups/{id}/AssignComputers](#)
- [post /v1/Groups/{id}/AssignPolicyRevision](#)
- [patch /v1/Groups/{id}/ClearPolicy](#)
- [delete /v1/Groups/{id}](#)
- [get /v1/Groups/{id}](#)
- [patch /v1/Groups/{id}/MarkAsDefault](#)
- [post /v1/Groups](#)
- [put /v1/Groups](#)
- [post /v1/Groups/UnassignComputers](#)

Policies

- [get /v1/Policies](#)
- [get /v1/Policies/{id}/AssignedGroups](#)
- [get /v1/Policies/{id}/Content](#)
- [delete /v1/Policies/{id}](#)
- [patch /v1/Policies/{id}/DiscardDraft](#)
- [get /v1/Policies/{id}](#)
- [put /v1/Policies/{id}](#)
- [get /v1/Policies/{id}/Revisions](#)
- [get /v1/Policies/PolicyRevision/{policyRevisionId}/Content](#)

Roles

- [get /v1/Roles](#)
- [get /v1/Roles/{id}](#)

ScimResourceTypes

- [get /scim/v2/ResourceTypes](#)
- [get /scim/v2/ResourceTypes/User](#)

ScimSchemas

- [get /scim/v2/Schemas](#)

ScimServiceProviderConfig

- [get /scim/v2/ServiceProviderConfig](#)

ScimUsers

- [get /scim/v2/Users](#)
- [post /scim/v2/Users](#)
- [get /scim/v2/Users/{userID}](#)
- [patch /scim/v2/Users/{userID}](#)
- [put /scim/v2/Users/{userID}](#)

Tasks

- [get /v1/Tasks/{id}](#)

Users

- [get /v1/Users](#)
- [post /v1/Users/{id}/AssignRole](#)
- [patch /v1/Users/{id}/Disable](#)
- [patch /v1/Users/{id}/Enable](#)
- [get /v1/Users/{id}](#)
- [put /v1/Users/{id}/ModifyUserPreferences](#)
- [put /v1/Users/{id}](#)
- [patch /v1/Users/{id}/ResendInvite](#)
- [post /v1/Users](#)

AcceptedDomains

 **get /v1/AcceptedDomains**

Retrieves list of Accepted Domains (v1AcceptedDomainsGet)

Return type

array[[AcceptedDomainListItemModel](#)]

Example data

Content-Type: application/json

```
[ {
  "created" : "2000-01-23T04:56:07.000+00:00",
  "domain" : "domain",
  "errorInfo" : {
    "userAccountName" : "userAccountName",
    "parentTaskName" : "parentTaskName",
    "initiated" : "2000-01-23T04:56:07.000+00:00",
    "errorCode" : 0,
    "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
  },
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "locked" : true
}, {
  "created" : "2000-01-23T04:56:07.000+00:00",
  "domain" : "domain",
  "errorInfo" : {
    "userAccountName" : "userAccountName",
    "parentTaskName" : "parentTaskName",
    "initiated" : "2000-01-23T04:56:07.000+00:00",
    "errorCode" : 0,
    "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
  },
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "locked" : true
} ]
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

500

Server Error



```
delete /v1/AcceptedDomains/{id}
```

Deletes Accepted Domain (v1AcceptedDomainsIdDelete)

Path parameters

id (required)

Path Parameter — format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

204

No Content

404

Not Found **ProblemDetails**

409Conflict **ProblemDetails****423**Client Error **ProblemDetails**`get /v1/AcceptedDomains/{id}`

Retrieves Record of Accepted Domain (v1AcceptedDomainsIdGet)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

[AcceptedDomainDetailModel](#)

Example data

Content-Type: application/json

```
{
  "created" : "2000-01-23T04:56:07.000+00:00",
  "domain" : "domain",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200Success **AcceptedDomainDetailModel**

401Unauthorized **ProblemDetails****404**Not Found **ProblemDetails**`put /v1/AcceptedDomains/{id}`

Modifies Accepted Domain (v1AcceptedDomainsIdPut)

Path parameters

id (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ModifyAcceptedDomainRequest](#) (optional)**Body Parameter** —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

204

No Content

400Bad Request **ProblemDetails****401**Unauthorized **ProblemDetails****404**Not Found **ProblemDetails****409**Conflict **ProblemDetails****423**Client Error **ProblemDetails****post /v1/AcceptedDomains**

Creates Accepted Domain (v1AcceptedDomainsPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request bodybody [CreateAcceptedDomainRequest](#) (optional)**Body Parameter** —**Return type**

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

201

Created `UUID`

409

Conflict `ProblemDetails`

ActivityAudits



```
get /v1/ActivityAudits
```

Retrieves list of Activity Audits with pagination (sorting and filtering) (`v1ActivityAuditsGet`)

Query parameters

Sorts (optional)

Query Parameter —

`Pagination.PageSize` (optional)

Query Parameter — The number of records per page, for example 1. Shouldn't exceed 200. format: int32

`Pagination.PageNumber` (optional)

Query Parameter — The page number to retrieve from results, for example 1 format: int32

`Filter.User` (optional)

Query Parameter — Initiated User email or API Client identifier

`Filter.Details` (optional)

Query Parameter — Details of activity

`Filter.Created.Dates` (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

`Filter.Created.SelectionMode` (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.Entity (optional)

Query Parameter — Name of Activity Audit entity

Filter.AuditType (optional)

Query Parameter — Audit Type Name

Filter.ChangedBy (optional)

Query Parameter — Audit ChangedBy

Return type

[ActivityAuditListItemModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "created" : "2000-01-23T04:56:07.000+00:00",
    "changedBy" : "API",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "details" : "details",
    "id" : 5,
    "auditType" : "auditType",
    "locked" : true,
    "user" : "user",
    "entity" : "entity"
  }, {
    "created" : "2000-01-23T04:56:07.000+00:00",
    "changedBy" : "API",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "details" : "details",
    "id" : 5,
    "auditType" : "auditType",
    "locked" : true,
    "user" : "user",
    "entity" : "entity"
  }
]
```

```
} ],  
  "pageSize" : 6,  
  "totalRecordCount" : 1  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **ActivityAuditListItemModelPagedResponse**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

500

Server Error



```
get /v1/ActivityAudits/{id}
```

Retrieves Record of Activity Audit (`v1ActivityAuditsIdGet`)

Path parameters

id (required)

Path Parameter — format: int64

Return type

[ActivityAuditDetailModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "computerDataAuditing" : {
      "deactivatedAgents" : {
        "key" : "deactivatedAgents"
      },
      "newDeletedAgents" : [ "newDeletedAgents", "newDeletedAgents" ],
      "updatedPoliciesOn" : {
        "key" : "updatedPoliciesOn"
      }
    },
    "groupDataAuditing" : {
      "oldDescription" : "oldDescription",
      "addPolicyRevisions" : {
        "key" : "addPolicyRevisions"
      },
      "newName" : "newName",
      "removePolicyRevisions" : {
        "key" : "removePolicyRevisions"
      },
      "oldName" : "oldName",
      "newAgents" : {
        "key" : "newAgents"
      },
      "oldIsDefault" : true,
      "newDescription" : "newDescription",
      "newIsDefault" : true,
      "removeAgents" : {
        "key" : "removeAgents"
      }
    },
    "created" : "2000-01-23T04:56:07.000+00:00",
    "policyDataAuditing" : {
      "oldDescription" : "oldDescription",
      "newName" : "newName",
      "oldName" : "oldName",
      "newDescription" : "newDescription"
    },
    "policyRevisionDataAuditing" : {
      "newGroups" : {
        "key" : "newGroups"
      }
    },
    "auditType" : "auditType",
    "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "settingsDataAuditing" : {
      "modifyDomainOldValue" : "modifyDomainOldValue",
```



```
"modifyDomainNewValue" : "modifyDomainNewValue",
"removeDomain" : "removeDomain",
"addDomain" : "addDomain"
},
"apiClientDataAuditing" : {
  "oldDescription" : "oldDescription",
  "newName" : "newName",
  "deleted" : true,
  "secretUpdated" : true,
  "oldName" : "oldName",
  "newDescription" : "newDescription"
},
"installationKeyDataAuditing" : {
  "newDisabled" : true,
  "oldDisabled" : true,
  "deleted" : true,
  "newLabel" : "newLabel",
  "oldLabel" : "oldLabel"
},
"userDataAuditing" : {
  "oldDisabled" : true,
  "newUserType" : "newUserType",
  "oldEmailAddress" : "oldEmailAddress",
  "roles" : [ {
    "resourceId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "newRoles" : [ {
      "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "roleName" : "roleName"
    } ], {
      "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "roleName" : "roleName"
    } ],
    "oldRoles" : [ null, null ],
    "resourceName" : "resourceName",
    "resourceType" : "resourceType"
  }, {
    "resourceId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "newRoles" : [ {
      "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "roleName" : "roleName"
    } ], {
      "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "roleName" : "roleName"
    } ],
    "oldRoles" : [ null, null ],
    "resourceName" : "resourceName",
    "resourceType" : "resourceType"
  } ],
  "newPreferredLanguage" : "newPreferredLanguage",
  "oldDateTimeDisplayFormat" : "oldDateTimeDisplayFormat",
  "newDisabled" : true,
  "newDateTimeDisplayFormat" : "newDateTimeDisplayFormat",
  "oldOlsonTimeZoneId" : "oldOlsonTimeZoneId",
```

```
    "oldUserType" : "oldUserType",
    "oldPreferredLanguage" : "oldPreferredLanguage",
    "newOlsonTimeZoneId" : "newOlsonTimeZoneId",
    "newEmailAddress" : "newEmailAddress"
  },
  "changedBy" : "API",
  "details" : "details",
  "id" : 5,
  "user" : "user",
  "entity" : "entity"
}, {
  "computerDataAuditing" : {
    "deactivatedAgents" : {
      "key" : "deactivatedAgents"
    },
    "newDeletedAgents" : [ "newDeletedAgents", "newDeletedAgents" ],
    "updatedPoliciesOn" : {
      "key" : "updatedPoliciesOn"
    }
  },
  "groupDataAuditing" : {
    "oldDescription" : "oldDescription",
    "addPolicyRevisions" : {
      "key" : "addPolicyRevisions"
    },
    "newName" : "newName",
    "removePolicyRevisions" : {
      "key" : "removePolicyRevisions"
    },
    "oldName" : "oldName",
    "newAgents" : {
      "key" : "newAgents"
    },
    "oldIsDefault" : true,
    "newDescription" : "newDescription",
    "newIsDefault" : true,
    "removeAgents" : {
      "key" : "removeAgents"
    }
  },
  "created" : "2000-01-23T04:56:07.000+00:00",
  "policyDataAuditing" : {
    "oldDescription" : "oldDescription",
    "newName" : "newName",
    "oldName" : "oldName",
    "newDescription" : "newDescription"
  },
  "policyRevisionDataAuditing" : {
    "newGroups" : {
      "key" : "newGroups"
    }
  }
},
"auditType" : "auditType",
```

```
"userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"settingsDataAuditing" : {
  "modifyDomainOldValue" : "modifyDomainOldValue",
  "modifyDomainNewValue" : "modifyDomainNewValue",
  "removeDomain" : "removeDomain",
  "addDomain" : "addDomain"
},
"apiClientDataAuditing" : {
  "oldDescription" : "oldDescription",
  "newName" : "newName",
  "deleted" : true,
  "secretUpdated" : true,
  "oldName" : "oldName",
  "newDescription" : "newDescription"
},
"installationKeyDataAuditing" : {
  "newDisabled" : true,
  "oldDisabled" : true,
  "deleted" : true,
  "newLabel" : "newLabel",
  "oldLabel" : "oldLabel"
},
"userDataAuditing" : {
  "oldDisabled" : true,
  "newUserType" : "newUserType",
  "oldEmailAddress" : "oldEmailAddress",
  "roles" : [ {
    "resourceId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "newRoles" : [ {
      "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "roleName" : "roleName"
    }, {
      "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "roleName" : "roleName"
    } ],
    "oldRoles" : [ null, null ],
    "resourceName" : "resourceName",
    "resourceType" : "resourceType"
  }, {
    "resourceId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "newRoles" : [ {
      "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "roleName" : "roleName"
    }, {
      "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "roleName" : "roleName"
    } ],
    "oldRoles" : [ null, null ],
    "resourceName" : "resourceName",
    "resourceType" : "resourceType"
  } ],
  "newPreferredLanguage" : "newPreferredLanguage",
  "oldDateTimeDisplayFormat" : "oldDateTimeDisplayFormat",
```

```
    "newDisabled" : true,
    "newDateTimeDisplayFormat" : "newDateTimeDisplayFormat",
    "oldOlsonTimeZoneId" : "oldOlsonTimeZoneId",
    "oldUserType" : "oldUserType",
    "oldPreferredLanguage" : "oldPreferredLanguage",
    "newOlsonTimeZoneId" : "newOlsonTimeZoneId",
    "newEmailAddress" : "newEmailAddress"
  },
  "changedBy" : "API",
  "details" : "details",
  "id" : 5,
  "user" : "user",
  "entity" : "entity"
} ],
"pageSize" : 6,
"totalRecordCount" : 1
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **ActivityAuditDetailModelPagedResponse**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

AuthorizationRequestAudits



```
get /v1/AuthorizationRequestAudits
```

Retrieves the list of Authorization Request Audit with pagination (sorting and filtering) (v1AuthorizationRequestAuditsGet)

Query parameters

Sorts (optional)

Query Parameter —

Pagination.PageSize (optional)

Query Parameter — The number of records per page, for example 1. Shouldn't exceed 200. format: int32

Pagination.PageNumber (optional)

Query Parameter — The page number to retrieve from results, for example 1 format: int32

Filter.TicketId (optional)

Query Parameter —

Filter.User (optional)

Query Parameter —

Filter.ComputerName (optional)

Query Parameter —

Filter.ProductName (optional)

Query Parameter —

Filter.Reason (optional)

Query Parameter —

Filter.DecisionPerformedByUser (optional)

Query Parameter —

Filter.Decision (optional)

Query Parameter —

Filter.TimeOfRequest.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24

19:09:47.6816562 +00:00 format: date-time

Filter.TimeOfRequest.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.DecisionTime.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24

19:09:47.6816562 +00:00 format: date-time

Filter.DecisionTime.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.StartTime.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24

19:09:47.6816562 +00:00 format: date-time

Filter.StartTime.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.Duration (optional)

Query Parameter —

Return type

[AuthorizationRequestAuditListItemModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "duration" : "duration",
    "reason" : "reason",
    "decision" : "decision",
    "computerName" : "computerName",
    "decisionTime" : "2000-01-23T04:56:07.000+00:00",
    "timeOfRequest" : "2000-01-23T04:56:07.000+00:00",
    "startTime" : "2000-01-23T04:56:07.000+00:00",
    "id" : 5,
    "user" : "user",
    "ticketId" : "ticketId",
    "productName" : "productName",
    "decisionPerformedByUser" : "decisionPerformedByUser"
  }, {
    "duration" : "duration",
    "reason" : "reason",
    "decision" : "decision",
    "computerName" : "computerName",
    "decisionTime" : "2000-01-23T04:56:07.000+00:00",
    "timeOfRequest" : "2000-01-23T04:56:07.000+00:00",
    "startTime" : "2000-01-23T04:56:07.000+00:00",
    "id" : 5,
    "user" : "user",
    "ticketId" : "ticketId",
    "productName" : "productName",
    "decisionPerformedByUser" : "decisionPerformedByUser"
  } ],
  "pageSize" : 6,
  "totalRecordCount" : 1
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **AuthorizationRequestAuditListItemModelPagedResponse**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

403

Forbidden **ProblemDetails**



`get /v1/AuthorizationRequestAudits/{id}`

Retrieves Record of Authorization Request Audit (v1AuthorizationRequestAuditsIdGet)

Path parameters

id (required)

Path Parameter — format: int64

Return type

[AuthorizationRequestAuditDetailModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "duration" : "duration",
    "reason" : "reason",
    "decision" : "decision",
    "computerName" : "computerName",
    "decisionTime" : "2000-01-23T04:56:07.000+00:00",
    "timeOfRequest" : "2000-01-23T04:56:07.000+00:00",
```

```
    "startTime" : "2000-01-23T04:56:07.000+00:00",
    "id" : 5,
    "user" : "user",
    "ticketId" : "ticketId",
    "productName" : "productName",
    "decisionPerformedByUser" : "decisionPerformedByUser"
  }, {
    "duration" : "duration",
    "reason" : "reason",
    "decision" : "decision",
    "computerName" : "computerName",
    "decisionTime" : "2000-01-23T04:56:07.000+00:00",
    "timeOfRequest" : "2000-01-23T04:56:07.000+00:00",
    "startTime" : "2000-01-23T04:56:07.000+00:00",
    "id" : 5,
    "user" : "user",
    "ticketId" : "ticketId",
    "productName" : "productName",
    "decisionPerformedByUser" : "decisionPerformedByUser"
  } ],
  "pageSize" : 6,
  "totalRecordCount" : 1
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **AuthorizationRequestAuditDetailModelPagedResponse**

401

Unauthorized **ProblemDetails**

403

Forbidden **ProblemDetails**

404

Not Found **ProblemDetails**

Computers

 `post /v1/Computers/Authorise`

Authorises Computers (v1ComputersAuthorisePost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ComputersAuthoriseRequest](#) (optional)

Body Parameter —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success

201

Created **UUID**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

409Conflict **ProblemDetails****423**Client Error **ProblemDetails****post /v1/Computers/Certificate/Renew**

Request to Renew Computer Certificate (v1ComputersCertificateRenewPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request bodybody [ComputerRenewCertificateRequest](#) (optional)**Body Parameter** —**Produces**

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses**202**

Accepted

400Bad Request **ProblemDetails****404**Not Found **ProblemDetails**

409Conflict **ProblemDetails** `post /v1/Computers/Deactivate`

Deactivates Computers (v1ComputersDeactivatePost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ComputersDeactivateRequest](#) (optional)**Body Parameter** —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success

201Created **UUID****400**Bad Request **ProblemDetails****401**Unauthorized **ProblemDetails**

404Not Found **ProblemDetails****409**Conflict **ProblemDetails****423**Client Error **ProblemDetails****delete /v1/Computers**

Deletes Computers (v1ComputersDelete)

Consumes

This API call consumes the following media types via the Content-Type request header:

- **application/json**
- **text/json**
- **application/*+json**

Request bodybody [ComputersRemoveRequest](#) (optional)**Body Parameter** — Request containing data to filter Computers to be removed**Produces**

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses**200**

Success

201Created **UUID**

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



post /v1/Computers/Details/Request

Retrieves Computer Status Info (v1ComputersDetailsRequestPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request body

body [ComputerRetrieveStatusInfoRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json

- text/json

Responses

201

Created **UUID**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



`get /v1/Computers`

Retrieves the list of Computers with pagination (sorting and filtering) (v1ComputersGet)

Query parameters

Sorts (optional)

Query Parameter —

Pagination.PageSize (optional)

Query Parameter — The number of records per page, for example 1. Shouldn't exceed 200. format: int32

Pagination.PageNumber (optional)

Query Parameter — The page number to retrieve from results, for example 1 format: int32

Filter.ComputerId (optional)

Query Parameter — The Id of the Computer(Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

Filter.Host (optional)

Query Parameter — The host name of the Computer, for example - Computer1

Filter.HostType (optional)

Query Parameter — The host type of the Computer, for example - MicrosoftWindows, Linux

Filter.AgentVersion (optional)

Query Parameter — The agent version of the Computer, example - 5.6.126.0

Filter.AdapterVersion (optional)

Query Parameter — The adapter version of the Computer, example - 20.5.195.0

Filter.AuthorisationState (optional)

Query Parameter — The state of the Computer, example - Authorised, Pending

Filter.LastConnected.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

Filter.LastConnected.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.PolicyRevisionStatus (optional)

Query Parameter — Policy Revision Status, example - AwaitingLatestPolicy

Filter.PolicyId (optional)

Query Parameter — Policy Id, example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

Filter.PolicyName (optional)

Query Parameter — Policy Name, example - Policy1

Filter.GroupId (optional)

Query Parameter — Group Id, example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

Filter.GroupName (optional)

Query Parameter — Group Name, example - Group1

Filter.OS (optional)

Query Parameter — OS Name, example - Windows

Filter.Domain (optional)

Query Parameter — Domain Name, example - BeyondTrust

Filter.Created.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

Filter.Created.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.DuplicateCount.Min (optional)

Query Parameter — Min Value of CountRange, example - 1,2,3 format: int32

Filter.DuplicateCount.Max (optional)

Query Parameter — Max Value of CountRange, example - 1,2,3 format: int32

Return type

[ComputerListItemModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "rejected" : true,
    "deactivatedOn" : "2000-01-23T04:56:07.000+00:00",
    "groupId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "deactivated" : true,
    "authorisationState" : "authorisationState",
    "lastConnected" : "2000-01-23T04:56:07.000+00:00",
    "hostType" : "Undefined",
    "host" : "host",
    "adapterVersion" : "adapterVersion",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "locked" : true,
    "os" : "os",
    "policyName" : "policyName",
    "created" : "2000-01-23T04:56:07.000+00:00",
    "pendingDeactivation" : true,
    "duplicate" : true,
    "policyRevisionId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "credentialType" : "credentialType",
    "groupName" : "groupName",
    "policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "duplicateCount" : 5,
    "domain" : "domain",
    "agentVersion" : "agentVersion",
    "policyRevisionStatus" : "policyRevisionStatus"
  }, {
    "rejected" : true,
    "deactivatedOn" : "2000-01-23T04:56:07.000+00:00",
    "groupId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "deactivated" : true,
    "authorisationState" : "authorisationState",
    "lastConnected" : "2000-01-23T04:56:07.000+00:00",
```



```

        "hostType" : "Undefined",
        "host" : "host",
        "adapterVersion" : "adapterVersion",
        "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
        "locked" : true,
        "os" : "os",
        "policyName" : "policyName",
        "created" : "2000-01-23T04:56:07.000+00:00",
        "pendingDeactivation" : true,
        "duplicate" : true,
        "policyRevisionId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
        "credentialType" : "credentialType",
        "groupName" : "groupName",
        "policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
        "duplicateCount" : 5,
        "domain" : "domain",
        "agentVersion" : "agentVersion",
        "policyRevisionStatus" : "policyRevisionStatus"
    } ],
    "pageSize" : 6,
    "totalRecordCount" : 1
}
    
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **ComputerListItemModelPagedResponse**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**



get /v1/Computers/{id}/CommandLog

Gets Computer Command Logs List (v1ComputersIdCommandLogGet)

Path parameters

id (required)

Path Parameter — format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success

404

Not Found **ProblemDetails**



```
get /v1/Computers/{id}
```

Retrieves a detail of the Computer (v1ComputersIdGet)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

[ComputerDetailModel](#)

Example data

Content-Type: application/json

```
{  
  "deactivatedOn" : "2000-01-23T04:56:07.000+00:00",
```

```
"groupId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"hostPolicyName" : "hostPolicyName",
"policyRevision" : 0,
"autoDeactivated" : true,
"agentLogs" : [ {
  "created" : "2000-01-23T04:56:07.000+00:00",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "returned" : "2000-01-23T04:56:07.000+00:00"
}, {
  "created" : "2000-01-23T04:56:07.000+00:00",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "returned" : "2000-01-23T04:56:07.000+00:00"
} ],
"deactivated" : true,
"authorisationState" : "authorisationState",
"certificateInformation" : {
  "lastIssued" : "2000-01-23T04:56:07.000+00:00",
  "validFrom" : "2000-01-23T04:56:07.000+00:00",
  "validTo" : "2000-01-23T04:56:07.000+00:00"
},
"lastConnected" : "2000-01-23T04:56:07.000+00:00",
"hostType" : "hostType",
"authorised" : "2000-01-23T04:56:07.000+00:00",
"adapterVersion" : "adapterVersion",
"hostLastUpdated" : "2000-01-23T04:56:07.000+00:00",
"id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"policyName" : "policyName",
"created" : "2000-01-23T04:56:07.000+00:00",
"pendingDeactivation" : true,
"endpointInformation" : {
  "systemModel" : "systemModel",
  "systemPrimaryOwnerName" : "systemPrimaryOwnerName",
  "osArchitecture" : "osArchitecture",
  "systemSystemType" : "systemSystemType",
  "systemDomain" : "systemDomain",
  "processorManufacturer" : "processorManufacturer",
  "osVersion" : "osVersion",
  "systemName" : "systemName",
  "osVersionString" : "osVersionString",
  "osCaption" : "osCaption",
  "systemManufacturer" : "systemManufacturer",
  "processorName" : "processorName",
  "osCodeSet" : "osCodeSet",
  "osSystemDrive" : "osSystemDrive",
  "osOrganization" : "osOrganization",
  "processorDescription" : "processorDescription",
  "osCountryCode" : "osCountryCode",
  "osInstallDate" : "2000-01-23T04:56:07.000+00:00",
  "osSystemDirectory" : "osSystemDirectory",
  "osComputerDescription" : "osComputerDescription",
  "osSerialNumber" : "osSerialNumber",
  "macAddress" : "macAddress",
  "processorCaption" : "processorCaption",
```

```

        "systemDnsHostName" : "systemDnsHostName",
        "osManufacturer" : "osManufacturer",
        "systemWorkgroup" : "systemWorkgroup"
    },
    "connected" : true,
    "credentialType" : "credentialType",
    "groupName" : "groupName",
    "policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "duplicateCount" : 1,
    "agentVersion" : "agentVersion",
    "hostPolicyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "policyRevisionStatus" : "policyRevisionStatus",
    "hostPolicyRevision" : 6
}
    
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **ComputerDetailModel**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**



`get /v1/Computers/{id}/Logs`

Gets Computer Logs (`v1ComputersIdLogsGet`)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

array[[ComputerLogModel](#)]

Example data

Content-Type: application/json

```
[ {
  "created" : "2000-01-23T04:56:07.000+00:00",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "returned" : "2000-01-23T04:56:07.000+00:00"
}, {
  "created" : "2000-01-23T04:56:07.000+00:00",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "returned" : "2000-01-23T04:56:07.000+00:00"
} ]
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**



`get /v1/Computers/Logs/{id}/Content`

Downloads Computer Log (v1ComputersLogsIdContentGet)

Path parameters

id (required)

Path Parameter — format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**



`post /v1/Computers/Logs/Request`

Retrieves Computer Logs (v1ComputersLogsRequestPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request body

body [ComputerRetrieveLogsRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

201

Created **UUID**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



```
post /v1/Computers/Reject
```

Rejects Computers (v1ComputersRejectPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request body

body [ComputersRejectRequest](#) (optional)

Body Parameter — Request containing data to filter Computers to be rejected

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success

201

Created **UUID**

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**

Events



```
get /v1/Events/FromStartDate
```

Gets the list of events by start date (v1EventsFromStartDateGet)

Query parameters

StartDate (required)

Query Parameter — Start Date(UTC) to search events from (Elastic Ingestion Timestamp in UTC). Example: 2022-08-12T17:34:28.694Z

RecordSize (optional)

Query Parameter — Maximum records that can be returned. Min size: 1, Max size: 1000, Example: 100 default: 1000 format: int32

Return type

[EpmEcsEventResponseModel](#)

Example data

Content-Type: application/json

```
{
  "totalRecordsReturned" : 0,
  "events" : [ {
    "container" : {
      "image" : {
        "name" : "name",
        "tag" : [ "tag", "tag" ],
        "hash" : {
          "all" : [ "all", "all" ]
        }
      },
      "disk" : {
        "read" : {
          "bytes" : 2
        },
        "write" : {
          "bytes" : 4
        }
      },
      "memory" : {
        "usage" : 7.386281948385884
      },
      "name" : "name",
      "cpu" : {
        "usage" : 3.616076749251911
      },
      "runtime" : "runtime",
      "id" : "id",
      "labels" : "labels",
      "network" : {
        "ingress" : {
          "bytes" : 1
        }
      }
    }
  }
]
```

```
    },
    "egress" : {
      "bytes" : 1
    }
  },
  "server" : {
    "nat" : {
      "port" : 7,
      "ip" : "ip"
    },
    "address" : "address",
    "top_level_domain" : "top_level_domain",
    "ip" : "ip",
    "mac" : "mac",
    "packets" : 5,
    "registered_domain" : "registered_domain",
    "port" : 3,
    "bytes" : 9,
    "domain" : "domain",
    "subdomain" : "subdomain"
  },
  "agent" : {
    "build" : {
      "original" : "original"
    },
    "name" : "name",
    "id" : "id",
    "type" : "type",
    "ephemeral_id" : "ephemeral_id",
    "version" : "version"
  },
  "faas" : {
    "execution" : "execution",
    "coldstart" : true,
    "name" : "name",
    "id" : "id",
    "trigger" : {
      "type" : "type",
      "request_id" : "request_id"
    },
    "version" : "version"
  },
  "log" : {
    "file" : {
      "path" : "path"
    },
    "level" : "level",
    "logger" : "logger",
    "origin" : {
      "file" : {
        "line" : 7,
        "name" : "name"
      }
    }
  }
}
```

```
    },
    "function" : "function"
  },
  "syslog" : "syslog"
},
"destination" : {
  "nat" : {
    "port" : 1,
    "ip" : "ip"
  },
  "address" : "address",
  "top_level_domain" : "top_level_domain",
  "ip" : "ip",
  "mac" : "mac",
  "packets" : 7,
  "registered_domain" : "registered_domain",
  "port" : 1,
  "bytes" : 6,
  "domain" : "domain",
  "subdomain" : "subdomain"
},
"rule" : {
  "reference" : "reference",
  "license" : "license",
  "author" : [ "author", "author" ],
  "name" : "name",
  "ruleset" : "ruleset",
  "description" : "description",
  "id" : "id",
  "category" : "category",
  "uuid" : "uuid",
  "version" : "version"
},
"error" : {
  "code" : "code",
  "id" : "id",
  "stack_trace" : "stack_trace",
  "message" : "message",
  "type" : "type"
},
"network" : {
  "transport" : "transport",
  "type" : "type",
  "inner" : "inner",
  "packets" : 3,
  "protocol" : "protocol",
  "forwarded_ip" : "forwarded_ip",
  "community_id" : "community_id",
  "application" : "application",
  "vlan" : {
    "name" : "name",
    "id" : "id"
  }
},
```

```
"bytes" : 5,
"name" : "name",
"iana_number" : "iana_number",
"direction" : "direction"
},
"cloud" : {
  "availability_zone" : "availability_zone",
  "instance" : {
    "name" : "name",
    "id" : "id"
  },
  "provider" : "provider",
  "machine" : {
    "type" : "type"
  },
  "service" : {
    "name" : "name"
  },
  "origin" : {
    "availability_zone" : "availability_zone",
    "provider" : "provider",
    "region" : "region"
  },
  "project" : {
    "name" : "name",
    "id" : "id"
  },
  "region" : "region",
  "account" : {
    "name" : "name",
    "id" : "id"
  },
  "target" : {
    "availability_zone" : "availability_zone",
    "provider" : "provider",
    "region" : "region"
  }
},
"observer" : {
  "product" : "product",
  "ip" : [ "ip", "ip" ],
  "serial_number" : "serial_number",
  "type" : "type",
  "version" : "version",
  "mac" : "mac",
  "egress" : "egress",
  "ingress" : "ingress",
  "hostname" : "hostname",
  "vendor" : "vendor",
  "name" : "name"
},
"file" : {
  "extension" : "extension",
```

```
"SourceUrl" : "SourceUrl",
"Owner" : {
  "Identifier" : "Identifier",
  "DomainName" : "DomainName",
  "Name" : "Name",
  "DomainIdentifier" : "DomainIdentifier"
},
"gid" : "gid",
"drive_letter" : "drive_letter",
"type" : "type",
"mtime" : "2000-01-23T04:56:07.000+00:00",
"accessed" : "2000-01-23T04:56:07.000+00:00",
"directory" : "directory",
"inode" : "inode",
"mode" : "mode",
"path" : "path",
"uid" : "uid",
"ctime" : "2000-01-23T04:56:07.000+00:00",
"fork_name" : "fork_name",
"elf" : {
  "imports" : {
    "key" : "imports"
  },
  "shared_libraries" : [ "shared_libraries", "shared_libraries" ],
  "byte_order" : "byte_order",
  "exports" : {
    "key" : "exports"
  },
  "cpu_type" : "cpu_type",
  "header" : {
    "object_version" : "object_version",
    "data" : "data",
    "os_abi" : "os_abi",
    "entrypoint" : 6,
    "abi_version" : "abi_version",
    "type" : "type",
    "class" : "class",
    "version" : "version"
  },
  "creation_date" : "2000-01-23T04:56:07.000+00:00",
  "sections" : [ {
    "chi2" : 5,
    "virtual_address" : 2,
    "entropy" : 6,
    "physical_offset" : "physical_offset",
    "flags" : "flags",
    "name" : "name",
    "physical_size" : 1,
    "type" : "type",
    "virtual_size" : 6
  }, {
    "chi2" : 5,
    "virtual_address" : 2,
```

```
    "entropy" : 6,
    "physical_offset" : "physical_offset",
    "flags" : "flags",
    "name" : "name",
    "physical_size" : 1,
    "type" : "type",
    "virtual_size" : 6
  } ],
  "telfhash" : "telfhash",
  "architecture" : "architecture",
  "segments" : [ {
    "type" : "type",
    "sections" : "sections"
  }, {
    "type" : "type",
    "sections" : "sections"
  } ]
},
"group" : "group",
"owner" : "owner",
"created" : "2000-01-23T04:56:07.000+00:00",
"Bundle" : {
  "Type" : "Type",
  "DownloadSource" : "DownloadSource",
  "Version" : "Version",
  "InfoDescription" : "InfoDescription",
  "Creator" : "Creator",
  "Name" : "Name"
},
"target_path" : "target_path",
"DriveType" : "DriveType",
"x509" : {
  "not_after" : "2000-01-23T04:56:07.000+00:00",
  "public_key_exponent" : 3,
  "not_before" : "2000-01-23T04:56:07.000+00:00",
  "subject" : {
    "state_or_province" : [ "state_or_province", "state_or_province" ],
    "country" : [ "country", "country" ],
    "organization" : [ "organization", "organization" ],
    "distinguished_name" : "distinguished_name",
    "locality" : [ "locality", "locality" ],
    "common_name" : [ "common_name", "common_name" ],
    "organizational_unit" : [ "organizational_unit", "organizational_unit" ]
  },
  "public_key_algorithm" : "public_key_algorithm",
  "public_key_curve" : "public_key_curve",
  "signature_algorithm" : "signature_algorithm",
  "version_number" : "version_number",
  "serial_number" : "serial_number",
  "public_key_size" : 6,
  "alternative_names" : [ "alternative_names", "alternative_names" ],
  "issuer" : {
    "state_or_province" : [ "state_or_province", "state_or_province" ],
```

```
    "country" : [ "country", "country" ],
    "organization" : [ "organization", "organization" ],
    "distinguished_name" : "distinguished_name",
    "locality" : [ "locality", "locality" ],
    "common_name" : [ "common_name", "common_name" ],
    "organizational_unit" : [ "organizational_unit", "organizational_unit" ]
  }
},
"size" : 9,
"mime_type" : "mime_type",
"ZoneTag" : "ZoneTag",
"name" : "name",
"attributes" : [ "attributes", "attributes" ],
"device" : "device"
},
"ecs" : {
  "version" : "version"
},
"related" : {
  "hosts" : [ "hosts", "hosts" ],
  "ip" : [ "ip", "ip" ],
  "user" : [ "user", "user" ],
  "hash" : [ "hash", "hash" ]
},
"host" : {
  "os" : {
    "kernel" : "kernel",
    "name" : "name",
    "type" : "type",
    "family" : "family",
    "version" : "version",
    "platform" : "platform",
    "full" : "full"
  },
  "ip" : [ "ip", "ip" ],
  "cpu" : {
    "usage" : 3.353193347011243
  },
  "pid_ns_ino" : "pid_ns_ino",
  "type" : "type",
  "mac" : "mac",
  "uptime" : 6,
  "network" : {
    "ingress" : {
      "bytes" : 0,
      "packets" : 7
    },
    "egress" : {
      "bytes" : 6,
      "packets" : 0
    }
  }
},
"hostname" : "hostname",
```

```
"disk" : {
  "read" : {
    "bytes" : 3
  },
  "write" : {
    "bytes" : 7
  }
},
"domain" : "domain",
"name" : "name",
"id" : "id",
"boot" : {
  "id" : "id"
},
"architecture" : "architecture",
"DomainIdentifier" : "DomainIdentifier"
},
"client" : {
  "nat" : {
    "port" : 5,
    "ip" : "ip"
  },
  "address" : "address",
  "top_level_domain" : "top_level_domain",
  "ip" : "ip",
  "mac" : "mac",
  "packets" : 5,
  "geo" : {
    "continent_name" : "continent_name",
    "region_iso_code" : "region_iso_code",
    "city_name" : "city_name",
    "country_iso_code" : "country_iso_code",
    "timezone" : "timezone",
    "country_name" : "country_name",
    "name" : "name",
    "continent_code" : "continent_code",
    "location" : {
      "lon" : 7.061401241503109,
      "lat" : 9.301444243932576
    },
    "region_name" : "region_name",
    "postal_code" : "postal_code"
  },
  "registered_domain" : "registered_domain",
  "as" : {
    "number" : 2,
    "organization" : {
      "name" : "name"
    }
  }
},
"port" : 6,
"bytes" : 1,
"domain" : "domain",
```



```
"subdomain" : "subdomain",
"user" : {
  "effective" : {
    "full_name" : "full_name",
    "domain" : "domain",
    "roles" : [ "roles", "roles" ],
    "name" : "name",
    "id" : "id",
    "email" : "email",
    "hash" : "hash",
    "DomainIdentifier" : "DomainIdentifier"
  },
  "full_name" : "full_name",
  "domain" : "domain",
  "roles" : [ "roles", "roles" ],
  "name" : "name",
  "changes" : {
    "full_name" : "full_name",
    "domain" : "domain",
    "roles" : [ "roles", "roles" ],
    "name" : "name",
    "id" : "id",
    "email" : "email",
    "hash" : "hash",
    "DomainIdentifier" : "DomainIdentifier"
  },
  "id" : "id",
  "email" : "email",
  "hash" : "hash",
  "DomainIdentifier" : "DomainIdentifier",
  "group" : {
    "domain" : "domain",
    "name" : "name",
    "id" : "id"
  },
  "target" : {
    "full_name" : "full_name",
    "domain" : "domain",
    "roles" : [ "roles", "roles" ],
    "name" : "name",
    "id" : "id",
    "email" : "email",
    "hash" : "hash",
    "DomainIdentifier" : "DomainIdentifier"
  }
}
},
"event" : {
  "reason" : "reason",
  "code" : "code",
  "timezone" : "timezone",
  "type" : [ "type", "type" ],
  "duration" : 9,
```

```
"reference" : "reference",
"agent_id_status" : "agent_id_status",
"ingested" : "2000-01-23T04:56:07.000+00:00",
"provider" : "provider",
"action" : "action",
"end" : "2000-01-23T04:56:07.000+00:00",
"id" : "id",
"outcome" : "outcome",
"severity" : 5,
"original" : "original",
"risk_score" : 6.683562403749608,
"kind" : "kind",
"created" : "2000-01-23T04:56:07.000+00:00",
"module" : "module",
"start" : "2000-01-23T04:56:07.000+00:00",
"url" : "url",
"sequence" : 9,
"risk_score_norm" : 8.762042012749001,
"category" : [ "category", "category" ],
"dataset" : "dataset",
"hash" : "hash"
},
"email" : {
  "cc" : {
    "address" : [ "address", "address" ]
  },
  "origination_timestamp" : "2000-01-23T04:56:07.000+00:00",
  "attachments" : [ {
    "file" : {
      "extension" : "extension",
      "size" : 4,
      "mime_type" : "mime_type",
      "name" : "name"
    }
  }, {
    "file" : {
      "extension" : "extension",
      "size" : 4,
      "mime_type" : "mime_type",
      "name" : "name"
    }
  } ],
  "bcc" : {
    "address" : [ "address", "address" ]
  },
  "local_id" : "local_id",
  "subject" : "subject",
  "message_id" : "message_id",
  "x_mailer" : "x_mailer",
  "content_type" : "content_type",
  "reply_to" : {
    "address" : [ "address", "address" ]
  }
},
```

```
"sender" : {
  "address" : "address"
},
"delivery_timestamp" : "2000-01-23T04:56:07.000+00:00",
"from" : {
  "address" : [ "address", "address" ]
},
"to" : {
  "address" : [ "address", "address" ]
},
"direction" : "direction"
},
"user_agent" : {
  "original" : "original",
  "name" : "name",
  "version" : "version",
  "device" : {
    "name" : "name"
  }
},
"registry" : {
  "hive" : "hive",
  "path" : "path",
  "data" : {
    "strings" : [ "strings", "strings" ],
    "bytes" : "bytes",
    "type" : "type"
  },
  "value" : "value",
  "key" : "key"
},
"process" : {
  "parent" : {
    "interactive" : true,
    "pid" : 7,
    "working_directory" : "working_directory",
    "title" : "title",
    "end" : "2000-01-23T04:56:07.000+00:00",
    "same_as_process" : true,
    "group_leader" : {
      "interactive" : true,
      "pid" : 4,
      "working_directory" : "working_directory",
      "title" : "title",
      "end" : "2000-01-23T04:56:07.000+00:00",
      "same_as_process" : true,
      "pgid" : 3,
      "start" : "2000-01-23T04:56:07.000+00:00",
      "entity_id" : "entity_id",
      "executable" : "executable",
      "uptime" : 2,
      "env_vars" : "env_vars",
      "args" : [ "args", "args" ],
```

```
    "name" : "name",
    "exit_code" : 1,
    "tty" : "tty",
    "args_count" : 0,
    "command_line" : "command_line"
  },
  "pgid" : 5,
  "start" : "2000-01-23T04:56:07.000+00:00",
  "entity_id" : "entity_id",
  "executable" : "executable",
  "uptime" : 6,
  "env_vars" : "env_vars",
  "args" : [ "args", "args" ],
  "name" : "name",
  "exit_code" : 8,
  "tty" : "tty",
  "args_count" : 4,
  "command_line" : "command_line"
},
"interactive" : true,
"pid" : 0,
"working_directory" : "working_directory",
"title" : "title",
"end" : "2000-01-23T04:56:07.000+00:00",
"same_as_process" : true,
"previous" : {
  "interactive" : true,
  "pid" : 5,
  "working_directory" : "working_directory",
  "title" : "title",
  "end" : "2000-01-23T04:56:07.000+00:00",
  "same_as_process" : true,
  "pgid" : 5,
  "start" : "2000-01-23T04:56:07.000+00:00",
  "entity_id" : "entity_id",
  "executable" : "executable",
  "uptime" : 7,
  "env_vars" : "env_vars",
  "args" : [ "args", "args" ],
  "name" : "name",
  "exit_code" : 3,
  "tty" : "tty",
  "args_count" : 8,
  "command_line" : "command_line"
},
"pgid" : 6,
"start" : "2000-01-23T04:56:07.000+00:00",
"entry_meta" : {
  "source" : {
    "nat" : {
      "port" : 0,
      "ip" : "ip"
    }
  }
},
```

```
    "address" : "address",
    "top_level_domain" : "top_level_domain",
    "ip" : "ip",
    "mac" : "mac",
    "packets" : 9,
    "registered_domain" : "registered_domain",
    "port" : 9,
    "bytes" : 0,
    "domain" : "domain",
    "subdomain" : "subdomain"
  },
  "type" : "type"
},
"thread" : {
  "name" : "name",
  "id" : 1
},
"entity_id" : "entity_id",
"executable" : "executable",
"uptime" : 4,
"env_vars" : "env_vars",
"args" : [ "args", "args" ],
"session_leader" : {
  "interactive" : true,
  "pid" : 1,
  "working_directory" : "working_directory",
  "title" : "title",
  "end" : "2000-01-23T04:56:07.000+00:00",
  "same_as_process" : true,
  "pgid" : 3,
  "start" : "2000-01-23T04:56:07.000+00:00",
  "entity_id" : "entity_id",
  "executable" : "executable",
  "uptime" : 8,
  "env_vars" : "env_vars",
  "args" : [ "args", "args" ],
  "name" : "name",
  "exit_code" : 0,
  "tty" : "tty",
  "args_count" : 9,
  "command_line" : "command_line"
},
"entry_leader" : {
  "interactive" : true,
  "pid" : 8,
  "working_directory" : "working_directory",
  "title" : "title",
  "end" : "2000-01-23T04:56:07.000+00:00",
  "same_as_process" : true,
  "pgid" : 6,
  "start" : "2000-01-23T04:56:07.000+00:00",
  "entity_id" : "entity_id",
  "executable" : "executable",
```

```
    "uptime" : 8,
    "env_vars" : "env_vars",
    "args" : [ "args", "args" ],
    "name" : "name",
    "exit_code" : 9,
    "tty" : "tty",
    "args_count" : 4,
    "command_line" : "command_line"
  },
  "name" : "name",
  "exit_code" : 7,
  "tty" : "tty",
  "args_count" : 4,
  "command_line" : "command_line"
},
"tracing" : {
  "trace" : {
    "id" : "id"
  },
  "transaction" : {
    "id" : "id"
  },
  "span" : {
    "id" : "id"
  }
},
"package" : {
  "installed" : "2000-01-23T04:56:07.000+00:00",
  "build_version" : "build_version",
  "description" : "description",
  "type" : "type",
  "version" : "version",
  "reference" : "reference",
  "path" : "path",
  "license" : "license",
  "install_scope" : "install_scope",
  "size" : 4,
  "name" : "name",
  "checksum" : "checksum",
  "architecture" : "architecture"
},
"dll" : {
  "path" : "path",
  "code_signature" : {
    "valid" : true,
    "digest_algorithm" : "digest_algorithm",
    "signing_id" : "signing_id",
    "trusted" : true,
    "subject_name" : "subject_name",
    "exists" : true,
    "team_id" : "team_id",
    "status" : "status",
    "timestamp" : "2000-01-23T04:56:07.000+00:00"
```

```
    },
    "pe" : {
      "file_version" : "file_version",
      "product" : "product",
      "imphash" : "imphash",
      "description" : "description",
      "original_file_name" : "original_file_name",
      "company" : "company",
      "pehash" : "pehash",
      "architecture" : "architecture"
    },
    "name" : "name",
    "hash" : {
      "sha1" : "sha1",
      "sha384" : "sha384",
      "sha256" : "sha256",
      "sha512" : "sha512",
      "tlsh" : "tlsh",
      "ssdeep" : "ssdeep",
      "md5" : "md5"
    }
  },
  "dns" : {
    "op_code" : "op_code",
    "response_code" : "response_code",
    "resolved_ip" : [ "resolved_ip", "resolved_ip" ],
    "question" : {
      "registered_domain" : "registered_domain",
      "top_level_domain" : "top_level_domain",
      "name" : "name",
      "subdomain" : "subdomain",
      "type" : "type",
      "class" : "class"
    },
    "answers" : "answers",
    "id" : "id",
    "header_flags" : [ "header_flags", "header_flags" ],
    "type" : "type"
  },
  "vulnerability" : {
    "reference" : "reference",
    "severity" : "severity",
    "score" : {
      "environmental" : 0.4833312865174044,
      "version" : "version",
      "temporal" : 4.518309517874243,
      "base" : 8.675064425986758
    },
    "report_id" : "report_id",
    "scanner" : {
      "vendor" : "vendor"
    },
    "description" : "description",
```

```
"id" : "id",
"classification" : "classification",
"enumeration" : "enumeration",
"category" : [ "category", "category" ]
},
"orchestrator" : {
  "cluster" : {
    "name" : "name",
    "id" : "id",
    "version" : "version",
    "url" : "url"
  },
  "resource" : {
    "parent" : {
      "type" : "type"
    },
    "ip" : [ "ip", "ip" ],
    "name" : "name",
    "id" : "id",
    "type" : "type"
  },
  "organization" : "organization",
  "namespace" : "namespace",
  "type" : "type",
  "api_version" : "api_version"
},
"EPMWinMac" : {
  "COM" : {
    "AppID" : "AppID",
    "CLSID" : "CLSID",
    "DisplayName" : "DisplayName"
  },
  "TenantId" : "TenantId",
  "AuthorizingUser" : {
    "Identifier" : "Identifier",
    "DomainName" : "DomainName",
    "Name" : "Name",
    "DomainIdentifier" : "DomainIdentifier"
  },
  "PrivilegedGroup" : {
    "Access" : "Access",
    "RID" : "RID",
    "Name" : "Name"
  },
  "AuthorizationRequest" : {
    "AuthRequestURI" : "AuthRequestURI",
    "ControlAuthorization" : true
  },
  "SchemaVersion" : "SchemaVersion",
  "Configuration" : {
    "Path" : "Path",
    "Message" : {
      "Authorization" : {
```



```
    "ResponseStatus" : "ResponseStatus",
    "ChallengeCode" : "ChallengeCode"
  },
  "Type" : "Type",
  "Description" : "Description",
  "Identifier" : "Identifier",
  "UserReason" : "UserReason",
  "Name" : "Name"
},
"GPO" : {
  "Version" : "Version",
  "DisplayName" : "DisplayName",
  "LinkInformation" : "LinkInformation",
  "ActiveDirectoryPath" : "ActiveDirectoryPath"
},
"Token" : {
  "Description" : "Description",
  "Identifier" : "Identifier",
  "Name" : "Name"
},
"ContentGroup" : {
  "Description" : "Description",
  "Identifier" : "Identifier",
  "Name" : "Name"
},
"RuleScript" : {
  "Outcome" : {
    "Version" : "Version",
    "Output" : "Output",
    "RuleAffected" : true,
    "Name" : "Name",
    "Result" : "Result"
  },
  "FileName" : "FileName",
  "Publisher" : "Publisher"
},
"RevisionNumber" : "RevisionNumber",
"Workstyle" : {
  "Description" : "Description",
  "Identifier" : "Identifier",
  "Name" : "Name"
},
"Source" : "Source",
"Name" : "Name",
"ApplicationGroup" : {
  "Description" : "Description",
  "Identifier" : "Identifier",
  "Name" : "Name"
},
"Identifier" : "Identifier",
"Content" : {
  "Type" : "Type",
  "Description" : "Description",
```

```
    "Identifier" : "Identifier"
  },
  "Rule" : {
    "Action" : "Action",
    "Identifier" : "Identifier",
    "OnDemand" : true
  },
  "Application" : {
    "Type" : "Type",
    "Description" : "Description",
    "Identifier" : "Identifier"
  }
},
"Event" : {
  "Type" : "Type",
  "Action" : "Action"
},
"GroupId" : "GroupId",
"Session" : {
  "Locale" : "Locale",
  "PowerUser" : true,
  "WindowsSessionId" : "WindowsSessionId",
  "Administrator" : true,
  "Identifier" : "Identifier",
  "UILanguage" : "UILanguage"
}
},
"data_stream" : {
  "namespace" : "namespace",
  "type" : "type",
  "dataset" : "dataset"
},
"service" : {
  "node" : {
    "role" : "role",
    "name" : "name"
  },
  "environment" : "environment",
  "address" : "address",
  "origin" : {
    "environment" : "environment",
    "address" : "address",
    "name" : "name",
    "id" : "id",
    "state" : "state",
    "type" : "type",
    "ephemeral_id" : "ephemeral_id",
    "version" : "version"
  },
  "name" : "name",
  "id" : "id",
  "state" : "state",
  "type" : "type",
```

```
"ephemeral_id" : "ephemeral_id",
"version" : "version",
"target" : {
  "environment" : "environment",
  "address" : "address",
  "name" : "name",
  "id" : "id",
  "state" : "state",
  "type" : "type",
  "ephemeral_id" : "ephemeral_id",
  "version" : "version"
}
},
"organization" : {
  "name" : "name",
  "id" : "id"
},
"http" : {
  "request" : {
    "referrer" : "referrer",
    "method" : "method",
    "mime_type" : "mime_type",
    "bytes" : 8,
    "id" : "id",
    "body" : {
      "bytes" : 4,
      "content" : "content"
    }
  },
  "response" : {
    "status_code" : 7,
    "mime_type" : "mime_type",
    "bytes" : 3,
    "body" : {
      "bytes" : 3,
      "content" : "content"
    }
  },
  "version" : "version"
},
"tls" : {
  "cipher" : "cipher",
  "established" : true,
  "server" : {
    "not_after" : "2000-01-23T04:56:07.000+00:00",
    "ja3s" : "ja3s",
    "subject" : "subject",
    "not_before" : "2000-01-23T04:56:07.000+00:00",
    "certificate" : "certificate",
    "issuer" : "issuer",
    "certificate_chain" : [ "certificate_chain", "certificate_chain" ],
    "hash" : {
      "sha1" : "sha1",
```

```
    "sha256" : "sha256",
    "md5" : "md5"
  }
},
"curve" : "curve",
"next_protocol" : "next_protocol",
"client" : {
  "not_after" : "2000-01-23T04:56:07.000+00:00",
  "server_name" : "server_name",
  "supported_ciphers" : [ "supported_ciphers", "supported_ciphers" ],
  "subject" : "subject",
  "not_before" : "2000-01-23T04:56:07.000+00:00",
  "certificate" : "certificate",
  "ja3" : "ja3",
  "issuer" : "issuer",
  "certificate_chain" : [ "certificate_chain", "certificate_chain" ],
  "hash" : {
    "sha1" : "sha1",
    "sha256" : "sha256",
    "md5" : "md5"
  }
},
"resumed" : true,
"version" : "version",
"version_protocol" : "version_protocol"
},
"threat" : {
  "indicator" : {
    "first_seen" : "2000-01-23T04:56:07.000+00:00",
    "last_seen" : "2000-01-23T04:56:07.000+00:00",
    "confidence" : "confidence",
    "ip" : "ip",
    "sightings" : 0,
    "description" : "description",
    "type" : "type",
    "url" : {
      "extension" : "extension",
      "original" : "original",
      "scheme" : "scheme",
      "top_level_domain" : "top_level_domain",
      "query" : "query",
      "path" : "path",
      "registered_domain" : "registered_domain",
      "fragment" : "fragment",
      "password" : "password",
      "port" : 3,
      "domain" : "domain",
      "subdomain" : "subdomain",
      "full" : "full",
      "username" : "username"
    },
    "scanner_stats" : 3,
    "reference" : "reference",
```

```
"marking" : {
  "tlp" : "tlp"
},
"port" : 2,
"provider" : "provider",
"modified_at" : "2000-01-23T04:56:07.000+00:00",
"email" : {
  "address" : "address"
}
},
"feed" : {
  "reference" : "reference",
  "name" : "name",
  "description" : "description",
  "dashboard_id" : "dashboard_id"
},
"framework" : "framework",
"software" : {
  "reference" : "reference",
  "name" : "name",
  "alias" : [ "alias", "alias" ],
  "id" : "id",
  "type" : "type",
  "platforms" : [ "platforms", "platforms" ]
},
"technique" : {
  "reference" : [ "reference", "reference" ],
  "name" : [ "name", "name" ],
  "subtechnique" : {
    "reference" : [ "reference", "reference" ],
    "name" : [ "name", "name" ],
    "id" : [ "id", "id" ]
  },
  "id" : [ "id", "id" ]
},
"enrichments" : [ {
  "indicator" : "indicator",
  "matched" : {
    "field" : "field",
    "occurred" : "2000-01-23T04:56:07.000+00:00",
    "atomic" : "atomic",
    "index" : "index",
    "id" : "id",
    "type" : "type"
  }
}, {
  "indicator" : "indicator",
  "matched" : {
    "field" : "field",
    "occurred" : "2000-01-23T04:56:07.000+00:00",
    "atomic" : "atomic",
    "index" : "index",
    "id" : "id",
```

```
    "type" : "type"
  }
} ],
"group" : {
  "reference" : "reference",
  "name" : "name",
  "alias" : [ "alias", "alias" ],
  "id" : "id"
},
"tactic" : {
  "reference" : [ "reference", "reference" ],
  "name" : [ "name", "name" ],
  "id" : [ "id", "id" ]
}
},
"base" : {
  "@timestamp" : "2000-01-23T04:56:07.000+00:00",
  "message" : "message",
  "tags" : [ "tags", "tags" ],
  "labels" : "labels"
}
}, {
  "container" : {
    "image" : {
      "name" : "name",
      "tag" : [ "tag", "tag" ],
      "hash" : {
        "all" : [ "all", "all" ]
      }
    },
    "disk" : {
      "read" : {
        "bytes" : 2
      },
      "write" : {
        "bytes" : 4
      }
    },
    "memory" : {
      "usage" : 7.386281948385884
    },
    "name" : "name",
    "cpu" : {
      "usage" : 3.616076749251911
    },
    "runtime" : "runtime",
    "id" : "id",
    "labels" : "labels",
    "network" : {
      "ingress" : {
        "bytes" : 1
      },
      "egress" : {
```

```
        "bytes" : 1
      }
    },
    "server" : {
      "nat" : {
        "port" : 7,
        "ip" : "ip"
      },
      "address" : "address",
      "top_level_domain" : "top_level_domain",
      "ip" : "ip",
      "mac" : "mac",
      "packets" : 5,
      "registered_domain" : "registered_domain",
      "port" : 3,
      "bytes" : 9,
      "domain" : "domain",
      "subdomain" : "subdomain"
    },
    "agent" : {
      "build" : {
        "original" : "original"
      },
      "name" : "name",
      "id" : "id",
      "type" : "type",
      "ephemeral_id" : "ephemeral_id",
      "version" : "version"
    },
    "faas" : {
      "execution" : "execution",
      "coldstart" : true,
      "name" : "name",
      "id" : "id",
      "trigger" : {
        "type" : "type",
        "request_id" : "request_id"
      },
      "version" : "version"
    },
    "log" : {
      "file" : {
        "path" : "path"
      },
      "level" : "level",
      "logger" : "logger",
      "origin" : {
        "file" : {
          "line" : 7,
          "name" : "name"
        },
        "function" : "function"
      }
    }
  }
}
```

```
    },
    "syslog" : "syslog"
  },
  "destination" : {
    "nat" : {
      "port" : 1,
      "ip" : "ip"
    },
    "address" : "address",
    "top_level_domain" : "top_level_domain",
    "ip" : "ip",
    "mac" : "mac",
    "packets" : 7,
    "registered_domain" : "registered_domain",
    "port" : 1,
    "bytes" : 6,
    "domain" : "domain",
    "subdomain" : "subdomain"
  },
  "rule" : {
    "reference" : "reference",
    "license" : "license",
    "author" : [ "author", "author" ],
    "name" : "name",
    "ruleset" : "ruleset",
    "description" : "description",
    "id" : "id",
    "category" : "category",
    "uuid" : "uuid",
    "version" : "version"
  },
  "error" : {
    "code" : "code",
    "id" : "id",
    "stack_trace" : "stack_trace",
    "message" : "message",
    "type" : "type"
  },
  "network" : {
    "transport" : "transport",
    "type" : "type",
    "inner" : "inner",
    "packets" : 3,
    "protocol" : "protocol",
    "forwarded_ip" : "forwarded_ip",
    "community_id" : "community_id",
    "application" : "application",
    "vlan" : {
      "name" : "name",
      "id" : "id"
    },
    "bytes" : 5,
    "name" : "name",
```



```
    "iana_number" : "iana_number",
    "direction" : "direction"
  },
  "cloud" : {
    "availability_zone" : "availability_zone",
    "instance" : {
      "name" : "name",
      "id" : "id"
    },
    "provider" : "provider",
    "machine" : {
      "type" : "type"
    },
    "service" : {
      "name" : "name"
    },
    "origin" : {
      "availability_zone" : "availability_zone",
      "provider" : "provider",
      "region" : "region"
    },
    "project" : {
      "name" : "name",
      "id" : "id"
    },
    "region" : "region",
    "account" : {
      "name" : "name",
      "id" : "id"
    },
    "target" : {
      "availability_zone" : "availability_zone",
      "provider" : "provider",
      "region" : "region"
    }
  },
  "observer" : {
    "product" : "product",
    "ip" : [ "ip", "ip" ],
    "serial_number" : "serial_number",
    "type" : "type",
    "version" : "version",
    "mac" : "mac",
    "egress" : "egress",
    "ingress" : "ingress",
    "hostname" : "hostname",
    "vendor" : "vendor",
    "name" : "name"
  },
  "file" : {
    "extension" : "extension",
    "SourceUrl" : "SourceUrl",
    "Owner" : {
```

```
    "Identifier" : "Identifier",
    "DomainName" : "DomainName",
    "Name" : "Name",
    "DomainIdentifier" : "DomainIdentifier"
  },
  "gid" : "gid",
  "drive_letter" : "drive_letter",
  "type" : "type",
  "mtime" : "2000-01-23T04:56:07.000+00:00",
  "accessed" : "2000-01-23T04:56:07.000+00:00",
  "directory" : "directory",
  "inode" : "inode",
  "mode" : "mode",
  "path" : "path",
  "uid" : "uid",
  "ctime" : "2000-01-23T04:56:07.000+00:00",
  "fork_name" : "fork_name",
  "elf" : {
    "imports" : {
      "key" : "imports"
    },
    "shared_libraries" : [ "shared_libraries", "shared_libraries" ],
    "byte_order" : "byte_order",
    "exports" : {
      "key" : "exports"
    },
    "cpu_type" : "cpu_type",
    "header" : {
      "object_version" : "object_version",
      "data" : "data",
      "os_abi" : "os_abi",
      "entrypoint" : 6,
      "abi_version" : "abi_version",
      "type" : "type",
      "class" : "class",
      "version" : "version"
    },
    "creation_date" : "2000-01-23T04:56:07.000+00:00",
    "sections" : [ {
      "chi2" : 5,
      "virtual_address" : 2,
      "entropy" : 6,
      "physical_offset" : "physical_offset",
      "flags" : "flags",
      "name" : "name",
      "physical_size" : 1,
      "type" : "type",
      "virtual_size" : 6
    }, {
      "chi2" : 5,
      "virtual_address" : 2,
      "entropy" : 6,
      "physical_offset" : "physical_offset",
```

```
    "flags" : "flags",
    "name" : "name",
    "physical_size" : 1,
    "type" : "type",
    "virtual_size" : 6
  } ],
  "telfhash" : "telfhash",
  "architecture" : "architecture",
  "segments" : [ {
    "type" : "type",
    "sections" : "sections"
  }, {
    "type" : "type",
    "sections" : "sections"
  } ]
},
"group" : "group",
"owner" : "owner",
"created" : "2000-01-23T04:56:07.000+00:00",
"Bundle" : {
  "Type" : "Type",
  "DownloadSource" : "DownloadSource",
  "Version" : "Version",
  "InfoDescription" : "InfoDescription",
  "Creator" : "Creator",
  "Name" : "Name"
},
"target_path" : "target_path",
"DriveType" : "DriveType",
"x509" : {
  "not_after" : "2000-01-23T04:56:07.000+00:00",
  "public_key_exponent" : 3,
  "not_before" : "2000-01-23T04:56:07.000+00:00",
  "subject" : {
    "state_or_province" : [ "state_or_province", "state_or_province" ],
    "country" : [ "country", "country" ],
    "organization" : [ "organization", "organization" ],
    "distinguished_name" : "distinguished_name",
    "locality" : [ "locality", "locality" ],
    "common_name" : [ "common_name", "common_name" ],
    "organizational_unit" : [ "organizational_unit", "organizational_unit" ]
  },
  "public_key_algorithm" : "public_key_algorithm",
  "public_key_curve" : "public_key_curve",
  "signature_algorithm" : "signature_algorithm",
  "version_number" : "version_number",
  "serial_number" : "serial_number",
  "public_key_size" : 6,
  "alternative_names" : [ "alternative_names", "alternative_names" ],
  "issuer" : {
    "state_or_province" : [ "state_or_province", "state_or_province" ],
    "country" : [ "country", "country" ],
    "organization" : [ "organization", "organization" ],
```

```
    "distinguished_name" : "distinguished_name",
    "locality" : [ "locality", "locality" ],
    "common_name" : [ "common_name", "common_name" ],
    "organizational_unit" : [ "organizational_unit", "organizational_unit" ]
  }
},
"size" : 9,
"mime_type" : "mime_type",
"ZoneTag" : "ZoneTag",
"name" : "name",
"attributes" : [ "attributes", "attributes" ],
"device" : "device"
},
"ecs" : {
  "version" : "version"
},
"related" : {
  "hosts" : [ "hosts", "hosts" ],
  "ip" : [ "ip", "ip" ],
  "user" : [ "user", "user" ],
  "hash" : [ "hash", "hash" ]
},
"host" : {
  "os" : {
    "kernel" : "kernel",
    "name" : "name",
    "type" : "type",
    "family" : "family",
    "version" : "version",
    "platform" : "platform",
    "full" : "full"
  },
  "ip" : [ "ip", "ip" ],
  "cpu" : {
    "usage" : 3.353193347011243
  },
  "pid_ns_ino" : "pid_ns_ino",
  "type" : "type",
  "mac" : "mac",
  "uptime" : 6,
  "network" : {
    "ingress" : {
      "bytes" : 0,
      "packets" : 7
    },
    "egress" : {
      "bytes" : 6,
      "packets" : 0
    }
  }
},
"hostname" : "hostname",
"disk" : {
  "read" : {
```

```
        "bytes" : 3
      },
      "write" : {
        "bytes" : 7
      }
    },
    "domain" : "domain",
    "name" : "name",
    "id" : "id",
    "boot" : {
      "id" : "id"
    },
    "architecture" : "architecture",
    "DomainIdentifier" : "DomainIdentifier"
  },
  "client" : {
    "nat" : {
      "port" : 5,
      "ip" : "ip"
    },
    "address" : "address",
    "top_level_domain" : "top_level_domain",
    "ip" : "ip",
    "mac" : "mac",
    "packets" : 5,
    "geo" : {
      "continent_name" : "continent_name",
      "region_iso_code" : "region_iso_code",
      "city_name" : "city_name",
      "country_iso_code" : "country_iso_code",
      "timezone" : "timezone",
      "country_name" : "country_name",
      "name" : "name",
      "continent_code" : "continent_code",
      "location" : {
        "lon" : 7.061401241503109,
        "lat" : 9.301444243932576
      },
      "region_name" : "region_name",
      "postal_code" : "postal_code"
    },
    "registered_domain" : "registered_domain",
    "as" : {
      "number" : 2,
      "organization" : {
        "name" : "name"
      }
    },
    "port" : 6,
    "bytes" : 1,
    "domain" : "domain",
    "subdomain" : "subdomain",
    "user" : {
```

```
"effective" : {
  "full_name" : "full_name",
  "domain" : "domain",
  "roles" : [ "roles", "roles" ],
  "name" : "name",
  "id" : "id",
  "email" : "email",
  "hash" : "hash",
  "DomainIdentifier" : "DomainIdentifier"
},
"full_name" : "full_name",
"domain" : "domain",
"roles" : [ "roles", "roles" ],
"name" : "name",
"changes" : {
  "full_name" : "full_name",
  "domain" : "domain",
  "roles" : [ "roles", "roles" ],
  "name" : "name",
  "id" : "id",
  "email" : "email",
  "hash" : "hash",
  "DomainIdentifier" : "DomainIdentifier"
},
"id" : "id",
"email" : "email",
"hash" : "hash",
"DomainIdentifier" : "DomainIdentifier",
"group" : {
  "domain" : "domain",
  "name" : "name",
  "id" : "id"
},
"target" : {
  "full_name" : "full_name",
  "domain" : "domain",
  "roles" : [ "roles", "roles" ],
  "name" : "name",
  "id" : "id",
  "email" : "email",
  "hash" : "hash",
  "DomainIdentifier" : "DomainIdentifier"
}
},
"event" : {
  "reason" : "reason",
  "code" : "code",
  "timezone" : "timezone",
  "type" : [ "type", "type" ],
  "duration" : 9,
  "reference" : "reference",
  "agent_id_status" : "agent_id_status",
```

```
"ingested" : "2000-01-23T04:56:07.000+00:00",
"provider" : "provider",
"action" : "action",
"end" : "2000-01-23T04:56:07.000+00:00",
"id" : "id",
"outcome" : "outcome",
"severity" : 5,
"original" : "original",
"risk_score" : 6.683562403749608,
"kind" : "kind",
"created" : "2000-01-23T04:56:07.000+00:00",
"module" : "module",
"start" : "2000-01-23T04:56:07.000+00:00",
"url" : "url",
"sequence" : 9,
"risk_score_norm" : 8.762042012749001,
"category" : [ "category", "category" ],
"dataset" : "dataset",
"hash" : "hash"
},
"email" : {
  "cc" : {
    "address" : [ "address", "address" ]
  },
  "origination_timestamp" : "2000-01-23T04:56:07.000+00:00",
  "attachments" : [ {
    "file" : {
      "extension" : "extension",
      "size" : 4,
      "mime_type" : "mime_type",
      "name" : "name"
    }
  }, {
    "file" : {
      "extension" : "extension",
      "size" : 4,
      "mime_type" : "mime_type",
      "name" : "name"
    }
  } ],
  "bcc" : {
    "address" : [ "address", "address" ]
  },
  "local_id" : "local_id",
  "subject" : "subject",
  "message_id" : "message_id",
  "x_mailer" : "x_mailer",
  "content_type" : "content_type",
  "reply_to" : {
    "address" : [ "address", "address" ]
  },
  "sender" : {
    "address" : "address"
  }
}
```

```
    },
    "delivery_timestamp" : "2000-01-23T04:56:07.000+00:00",
    "from" : {
      "address" : [ "address", "address" ]
    },
    "to" : {
      "address" : [ "address", "address" ]
    },
    "direction" : "direction"
  },
  "user_agent" : {
    "original" : "original",
    "name" : "name",
    "version" : "version",
    "device" : {
      "name" : "name"
    }
  },
  "registry" : {
    "hive" : "hive",
    "path" : "path",
    "data" : {
      "strings" : [ "strings", "strings" ],
      "bytes" : "bytes",
      "type" : "type"
    },
    "value" : "value",
    "key" : "key"
  },
  "process" : {
    "parent" : {
      "interactive" : true,
      "pid" : 7,
      "working_directory" : "working_directory",
      "title" : "title",
      "end" : "2000-01-23T04:56:07.000+00:00",
      "same_as_process" : true,
      "group_leader" : {
        "interactive" : true,
        "pid" : 4,
        "working_directory" : "working_directory",
        "title" : "title",
        "end" : "2000-01-23T04:56:07.000+00:00",
        "same_as_process" : true,
        "pgid" : 3,
        "start" : "2000-01-23T04:56:07.000+00:00",
        "entity_id" : "entity_id",
        "executable" : "executable",
        "uptime" : 2,
        "env_vars" : "env_vars",
        "args" : [ "args", "args" ],
        "name" : "name",
        "exit_code" : 1,

```



```
    "tty" : "tty",
    "args_count" : 0,
    "command_line" : "command_line"
  },
  "pgid" : 5,
  "start" : "2000-01-23T04:56:07.000+00:00",
  "entity_id" : "entity_id",
  "executable" : "executable",
  "uptime" : 6,
  "env_vars" : "env_vars",
  "args" : [ "args", "args" ],
  "name" : "name",
  "exit_code" : 8,
  "tty" : "tty",
  "args_count" : 4,
  "command_line" : "command_line"
},
"interactive" : true,
"pid" : 0,
"working_directory" : "working_directory",
"title" : "title",
"end" : "2000-01-23T04:56:07.000+00:00",
"same_as_process" : true,
"previous" : {
  "interactive" : true,
  "pid" : 5,
  "working_directory" : "working_directory",
  "title" : "title",
  "end" : "2000-01-23T04:56:07.000+00:00",
  "same_as_process" : true,
  "pgid" : 5,
  "start" : "2000-01-23T04:56:07.000+00:00",
  "entity_id" : "entity_id",
  "executable" : "executable",
  "uptime" : 7,
  "env_vars" : "env_vars",
  "args" : [ "args", "args" ],
  "name" : "name",
  "exit_code" : 3,
  "tty" : "tty",
  "args_count" : 8,
  "command_line" : "command_line"
},
"pgid" : 6,
"start" : "2000-01-23T04:56:07.000+00:00",
"entry_meta" : {
  "source" : {
    "nat" : {
      "port" : 0,
      "ip" : "ip"
    },
    "address" : "address",
    "top_level_domain" : "top_level_domain",
```

```
    "ip" : "ip",
    "mac" : "mac",
    "packets" : 9,
    "registered_domain" : "registered_domain",
    "port" : 9,
    "bytes" : 0,
    "domain" : "domain",
    "subdomain" : "subdomain"
  },
  "type" : "type"
},
"thread" : {
  "name" : "name",
  "id" : 1
},
"entity_id" : "entity_id",
"executable" : "executable",
"uptime" : 4,
"env_vars" : "env_vars",
"args" : [ "args", "args" ],
"session_leader" : {
  "interactive" : true,
  "pid" : 1,
  "working_directory" : "working_directory",
  "title" : "title",
  "end" : "2000-01-23T04:56:07.000+00:00",
  "same_as_process" : true,
  "pgid" : 3,
  "start" : "2000-01-23T04:56:07.000+00:00",
  "entity_id" : "entity_id",
  "executable" : "executable",
  "uptime" : 8,
  "env_vars" : "env_vars",
  "args" : [ "args", "args" ],
  "name" : "name",
  "exit_code" : 0,
  "tty" : "tty",
  "args_count" : 9,
  "command_line" : "command_line"
},
"entry_leader" : {
  "interactive" : true,
  "pid" : 8,
  "working_directory" : "working_directory",
  "title" : "title",
  "end" : "2000-01-23T04:56:07.000+00:00",
  "same_as_process" : true,
  "pgid" : 6,
  "start" : "2000-01-23T04:56:07.000+00:00",
  "entity_id" : "entity_id",
  "executable" : "executable",
  "uptime" : 8,
  "env_vars" : "env_vars",
```

```
    "args" : [ "args", "args" ],
    "name" : "name",
    "exit_code" : 9,
    "tty" : "tty",
    "args_count" : 4,
    "command_line" : "command_line"
  },
  "name" : "name",
  "exit_code" : 7,
  "tty" : "tty",
  "args_count" : 4,
  "command_line" : "command_line"
},
"tracing" : {
  "trace" : {
    "id" : "id"
  },
  "transaction" : {
    "id" : "id"
  },
  "span" : {
    "id" : "id"
  }
},
"package" : {
  "installed" : "2000-01-23T04:56:07.000+00:00",
  "build_version" : "build_version",
  "description" : "description",
  "type" : "type",
  "version" : "version",
  "reference" : "reference",
  "path" : "path",
  "license" : "license",
  "install_scope" : "install_scope",
  "size" : 4,
  "name" : "name",
  "checksum" : "checksum",
  "architecture" : "architecture"
},
"dll" : {
  "path" : "path",
  "code_signature" : {
    "valid" : true,
    "digest_algorithm" : "digest_algorithm",
    "signing_id" : "signing_id",
    "trusted" : true,
    "subject_name" : "subject_name",
    "exists" : true,
    "team_id" : "team_id",
    "status" : "status",
    "timestamp" : "2000-01-23T04:56:07.000+00:00"
  },
  "pe" : {
```

```
    "file_version" : "file_version",
    "product" : "product",
    "imphash" : "imphash",
    "description" : "description",
    "original_file_name" : "original_file_name",
    "company" : "company",
    "pehash" : "pehash",
    "architecture" : "architecture"
  },
  "name" : "name",
  "hash" : {
    "sha1" : "sha1",
    "sha384" : "sha384",
    "sha256" : "sha256",
    "sha512" : "sha512",
    "tlsh" : "tlsh",
    "ssdeep" : "ssdeep",
    "md5" : "md5"
  }
},
"dns" : {
  "op_code" : "op_code",
  "response_code" : "response_code",
  "resolved_ip" : [ "resolved_ip", "resolved_ip" ],
  "question" : {
    "registered_domain" : "registered_domain",
    "top_level_domain" : "top_level_domain",
    "name" : "name",
    "subdomain" : "subdomain",
    "type" : "type",
    "class" : "class"
  },
  "answers" : "answers",
  "id" : "id",
  "header_flags" : [ "header_flags", "header_flags" ],
  "type" : "type"
},
"vulnerability" : {
  "reference" : "reference",
  "severity" : "severity",
  "score" : {
    "environmental" : 0.4833312865174044,
    "version" : "version",
    "temporal" : 4.518309517874243,
    "base" : 8.675064425986758
  },
  "report_id" : "report_id",
  "scanner" : {
    "vendor" : "vendor"
  },
  "description" : "description",
  "id" : "id",
  "classification" : "classification",
```

```
    "enumeration" : "enumeration",
    "category" : [ "category", "category" ]
  },
  "orchestrator" : {
    "cluster" : {
      "name" : "name",
      "id" : "id",
      "version" : "version",
      "url" : "url"
    },
    "resource" : {
      "parent" : {
        "type" : "type"
      },
      "ip" : [ "ip", "ip" ],
      "name" : "name",
      "id" : "id",
      "type" : "type"
    },
    "organization" : "organization",
    "namespace" : "namespace",
    "type" : "type",
    "api_version" : "api_version"
  },
  "EPMWinMac" : {
    "COM" : {
      "AppID" : "AppID",
      "CLSID" : "CLSID",
      "DisplayName" : "DisplayName"
    },
    "TenantId" : "TenantId",
    "AuthorizingUser" : {
      "Identifier" : "Identifier",
      "DomainName" : "DomainName",
      "Name" : "Name",
      "DomainIdentifier" : "DomainIdentifier"
    },
    "PrivilegedGroup" : {
      "Access" : "Access",
      "RID" : "RID",
      "Name" : "Name"
    },
    "AuthorizationRequest" : {
      "AuthRequestURI" : "AuthRequestURI",
      "ControlAuthorization" : true
    },
    "SchemaVersion" : "SchemaVersion",
    "Configuration" : {
      "Path" : "Path",
      "Message" : {
        "Authorization" : {
          "ResponseStatus" : "ResponseStatus",
          "ChallengeCode" : "ChallengeCode"
        }
      }
    }
  }
}
```

```
    },
    "Type" : "Type",
    "Description" : "Description",
    "Identifier" : "Identifier",
    "UserReason" : "UserReason",
    "Name" : "Name"
  },
  "GPO" : {
    "Version" : "Version",
    "DisplayName" : "DisplayName",
    "LinkInformation" : "LinkInformation",
    "ActiveDirectoryPath" : "ActiveDirectoryPath"
  },
  "Token" : {
    "Description" : "Description",
    "Identifier" : "Identifier",
    "Name" : "Name"
  },
  "ContentGroup" : {
    "Description" : "Description",
    "Identifier" : "Identifier",
    "Name" : "Name"
  },
  "RuleScript" : {
    "Outcome" : {
      "Version" : "Version",
      "Output" : "Output",
      "RuleAffected" : true,
      "Name" : "Name",
      "Result" : "Result"
    },
    "FileName" : "FileName",
    "Publisher" : "Publisher"
  },
  "RevisionNumber" : "RevisionNumber",
  "Workstyle" : {
    "Description" : "Description",
    "Identifier" : "Identifier",
    "Name" : "Name"
  },
  "Source" : "Source",
  "Name" : "Name",
  "ApplicationGroup" : {
    "Description" : "Description",
    "Identifier" : "Identifier",
    "Name" : "Name"
  },
  "Identifier" : "Identifier",
  "Content" : {
    "Type" : "Type",
    "Description" : "Description",
    "Identifier" : "Identifier"
  },
  },
```

```
"Rule" : {
  "Action" : "Action",
  "Identifier" : "Identifier",
  "OnDemand" : true
},
"Application" : {
  "Type" : "Type",
  "Description" : "Description",
  "Identifier" : "Identifier"
}
},
"Event" : {
  "Type" : "Type",
  "Action" : "Action"
},
"GroupId" : "GroupId",
"Session" : {
  "Locale" : "Locale",
  "PowerUser" : true,
  "WindowsSessionId" : "WindowsSessionId",
  "Administrator" : true,
  "Identifier" : "Identifier",
  "UILanguage" : "UILanguage"
}
},
"data_stream" : {
  "namespace" : "namespace",
  "type" : "type",
  "dataset" : "dataset"
},
"service" : {
  "node" : {
    "role" : "role",
    "name" : "name"
  },
  "environment" : "environment",
  "address" : "address",
  "origin" : {
    "environment" : "environment",
    "address" : "address",
    "name" : "name",
    "id" : "id",
    "state" : "state",
    "type" : "type",
    "ephemeral_id" : "ephemeral_id",
    "version" : "version"
  },
  "name" : "name",
  "id" : "id",
  "state" : "state",
  "type" : "type",
  "ephemeral_id" : "ephemeral_id",
  "version" : "version",
```

```
"target" : {
  "environment" : "environment",
  "address" : "address",
  "name" : "name",
  "id" : "id",
  "state" : "state",
  "type" : "type",
  "ephemeral_id" : "ephemeral_id",
  "version" : "version"
},
"organization" : {
  "name" : "name",
  "id" : "id"
},
"http" : {
  "request" : {
    "referrer" : "referrer",
    "method" : "method",
    "mime_type" : "mime_type",
    "bytes" : 8,
    "id" : "id",
    "body" : {
      "bytes" : 4,
      "content" : "content"
    }
  },
  "response" : {
    "status_code" : 7,
    "mime_type" : "mime_type",
    "bytes" : 3,
    "body" : {
      "bytes" : 3,
      "content" : "content"
    }
  },
  "version" : "version"
},
"tls" : {
  "cipher" : "cipher",
  "established" : true,
  "server" : {
    "not_after" : "2000-01-23T04:56:07.000+00:00",
    "ja3s" : "ja3s",
    "subject" : "subject",
    "not_before" : "2000-01-23T04:56:07.000+00:00",
    "certificate" : "certificate",
    "issuer" : "issuer",
    "certificate_chain" : [ "certificate_chain", "certificate_chain" ],
    "hash" : {
      "sha1" : "sha1",
      "sha256" : "sha256",
      "md5" : "md5"
    }
  }
}
```



```
    }
  },
  "curve" : "curve",
  "next_protocol" : "next_protocol",
  "client" : {
    "not_after" : "2000-01-23T04:56:07.000+00:00",
    "server_name" : "server_name",
    "supported_ciphers" : [ "supported_ciphers", "supported_ciphers" ],
    "subject" : "subject",
    "not_before" : "2000-01-23T04:56:07.000+00:00",
    "certificate" : "certificate",
    "ja3" : "ja3",
    "issuer" : "issuer",
    "certificate_chain" : [ "certificate_chain", "certificate_chain" ],
    "hash" : {
      "sha1" : "sha1",
      "sha256" : "sha256",
      "md5" : "md5"
    }
  },
  "resumed" : true,
  "version" : "version",
  "version_protocol" : "version_protocol"
},
"threat" : {
  "indicator" : {
    "first_seen" : "2000-01-23T04:56:07.000+00:00",
    "last_seen" : "2000-01-23T04:56:07.000+00:00",
    "confidence" : "confidence",
    "ip" : "ip",
    "sightings" : 0,
    "description" : "description",
    "type" : "type",
    "url" : {
      "extension" : "extension",
      "original" : "original",
      "scheme" : "scheme",
      "top_level_domain" : "top_level_domain",
      "query" : "query",
      "path" : "path",
      "registered_domain" : "registered_domain",
      "fragment" : "fragment",
      "password" : "password",
      "port" : 3,
      "domain" : "domain",
      "subdomain" : "subdomain",
      "full" : "full",
      "username" : "username"
    },
    "scanner_stats" : 3,
    "reference" : "reference",
    "marking" : {
      "tlp" : "tlp"
    }
  }
}
```

```
    },
    "port" : 2,
    "provider" : "provider",
    "modified_at" : "2000-01-23T04:56:07.000+00:00",
    "email" : {
      "address" : "address"
    }
  },
  "feed" : {
    "reference" : "reference",
    "name" : "name",
    "description" : "description",
    "dashboard_id" : "dashboard_id"
  },
  "framework" : "framework",
  "software" : {
    "reference" : "reference",
    "name" : "name",
    "alias" : [ "alias", "alias" ],
    "id" : "id",
    "type" : "type",
    "platforms" : [ "platforms", "platforms" ]
  },
  "technique" : {
    "reference" : [ "reference", "reference" ],
    "name" : [ "name", "name" ],
    "subtechnique" : {
      "reference" : [ "reference", "reference" ],
      "name" : [ "name", "name" ],
      "id" : [ "id", "id" ]
    },
    "id" : [ "id", "id" ]
  },
  "enrichments" : [ {
    "indicator" : "indicator",
    "matched" : {
      "field" : "field",
      "occurred" : "2000-01-23T04:56:07.000+00:00",
      "atomic" : "atomic",
      "index" : "index",
      "id" : "id",
      "type" : "type"
    }
  }, {
    "indicator" : "indicator",
    "matched" : {
      "field" : "field",
      "occurred" : "2000-01-23T04:56:07.000+00:00",
      "atomic" : "atomic",
      "index" : "index",
      "id" : "id",
      "type" : "type"
    }
  }
]
```

```
    } ],  
    "group" : {  
      "reference" : "reference",  
      "name" : "name",  
      "alias" : [ "alias", "alias" ],  
      "id" : "id"  
    },  
    "tactic" : {  
      "reference" : [ "reference", "reference" ],  
      "name" : [ "name", "name" ],  
      "id" : [ "id", "id" ]  
    }  
  },  
  "base" : {  
    "@timestamp" : "2000-01-23T04:56:07.000+00:00",  
    "message" : "message",  
    "tags" : [ "tags", "tags" ],  
    "labels" : "labels"  
  }  
} ]  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **EpmEcsEventResponseModel**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

500

Server Error

File

 `get /v1/File/download/GetYamlApiDefinitionFile`

Get the API definition file in YAML format (v1FileDownloadGetYamlApiDefinitionFileGet)

Return type

String

Example data

Content-Type: application/json

```
""
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success **String**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

Groups

 `post /v1/Groups/AutoAssignPolicyRevision`

Auto assign policy revision to the group (v1GroupsAutoAssignPolicyRevisionPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request body

body [AssignPolicyRevisionToGroupRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success **UUID**

404

Not Found **ProblemDetails**

423

Client Error **ProblemDetails**

 `get /v1/Groups`

Retrieves the list of Groups with pagination (sorting and filtering) (v1GroupsGet)

Query parameters

Sorts (optional)

Query Parameter —

Pagination.PageSize (optional)

Query Parameter — The number of records per page, for example 1. Shouldn't exceed 200. format: int32

Pagination.PageNumber (optional)

Query Parameter — The page number to retrieve from results, for example 1 format: int32

Filter.Id (optional)

Query Parameter — The Id of the group(Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

Filter.Name (optional)

Query Parameter — The name of the group

Filter.Description (optional)

Query Parameter — The description of the group

Filter.PolicyName (optional)

Query Parameter — The policy name of the group

Filter.PolicyRevisionStatus (optional)

Query Parameter — The policy revision status of the group

Filter.ComputerCount (optional)

Query Parameter — Number of computers in a group format: int32

Filter.ActiveComputers.Value (optional)

Query Parameter — Integer value for the filter, e.g. 100 format: int32

Filter.ActiveComputers.Operator (optional)

Query Parameter —

Filter.Created.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

Filter.Created.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Return type

[GroupListItemModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "policyName" : "policyName",
    "created" : "2000-01-23T04:56:07.000+00:00",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "description" : "description",
    "policyRevisionId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "revision" : 7,
    "computerCount" : 5,
    "activeComputers" : 2,
    "default" : true,
    "policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "name" : "name",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "locked" : true,
    "policyRevisionStatus" : "OnLatestPolicy"
  }, {
    "policyName" : "policyName",
    "created" : "2000-01-23T04:56:07.000+00:00",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "description" : "description",
    "policyRevisionId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "revision" : 7,
    "computerCount" : 5,
    "activeComputers" : 2,
    "default" : true,
    "policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "name" : "name",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "locked" : true,
    "policyRevisionStatus" : "OnLatestPolicy"
  } ],
  "pageSize" : 6,
  "totalRecordCount" : 1
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success **GroupListItemModelPagedResponse**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

500

Server Error



`post /v1/Groups/{id}/AssignComputersByCsv`

assigns computers to the group by input of csv file (v1GroupsIdAssignComputersByCsvPost)

Path parameters

id (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- multipart/form-data

Form parameters

csvFile (optional)

Form Parameter — format: binary

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

201

Created **UUID**

404

Not Found **ProblemDetails**

423

Client Error **ProblemDetails**



```
post /v1/Groups/{id}/AssignComputers
```

assigns computers to the group (v1GroupsIdAssignComputersPost)

Path parameters

id (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request body

body [AssignComputersToGroupRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

201

Created **UUID**

404

Not Found **ProblemDetails**

423

Client Error **ProblemDetails**



```
post /v1/Groups/{id}/AssignPolicyRevision
```

Assigns policy revision to the group (v1GroupsIdAssignPolicyRevisionPost)

Path parameters

id (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [AssignPolicyRevisionToGroupRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **UUID**

404

Not Found **ProblemDetails**

423Client Error **ProblemDetails** `patch /v1/Groups/{id}/ClearPolicy`

Clears policy from group (v1GroupsIdClearPolicyPatch)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

204No Content **UUID****404**Not Found **ProblemDetails****423**Client Error **ProblemDetails**

 `delete /v1/Groups/{id}`

Deletes group (v1GroupsIdDelete)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

204

No Content **UUID**

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**

 `get /v1/Groups/{id}`

Retrieves a detail of the group (v1GroupsIdGet)

Path parameters

id (required)

Path Parameter — format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

 `patch /v1/Groups/{id}/MarkAsDefault`

Marks group as default (v1GroupsIdMarkAsDefaultPatch)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

204

No Content **UUID**

404

Not Found **ProblemDetails**

423

Client Error **ProblemDetails**



post /v1/Groups

Creates Group (v1GroupsPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request body

body [CreateGroupRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

201

Created **UUID**

409

Conflict **ProblemDetails**



```
put /v1/Groups
```

Modifies Group (v1GroupsPut)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request body

body [ModifyGroupRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

204

No Content **UUID**

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



`post /v1/Groups/UnassignComputers`

Unassigns computers from the groups (`v1GroupsUnassignComputersPost`)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request body

body [UnassignComputersToGroupRequest](#) (optional)

Body Parameter —

Return type

array[UUID]

Example data

Content-Type: application/json

```
[ "046b6c7f-0b8a-43b9-b35d-6489e6daee91", "046b6c7f-0b8a-43b9-b35d-6489e6daee91" ]
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

202

Accepted

204

No Content

404

Not Found **ProblemDetails**

423

Client Error **ProblemDetails**

Policies

 `get /v1/Policies`

Retrieve list of Policies with pagination (sorting and filtering) (v1PoliciesGet)

Query parameters

Sorts (optional)

Query Parameter —

Pagination.PageSize (optional)

Query Parameter — The number of records per page, for example 1. Shouldn't exceed 200. format: int32

Pagination.PageNumber (optional)

Query Parameter — The page number to retrieve from results, for example 1 format: int32

Filter.Name (optional)

Query Parameter — The Name of the Policy, e.g. - Policy1

Filter.Size (optional)

Query Parameter — The Size of the Policy in Kb, e.g. 225 format: int32

Filter.Revision (optional)

Query Parameter — The number of revisions for the Policy, e.g. 5 format: int32

Filter.TotalAssignedRevisions (optional)

Query Parameter — The total number of Groups with the Policy assigned (any Revision), e.g. 10 format: int32

Filter.Created.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

Filter.Created.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.DraftUser (optional)

Query Parameter — The 'Locked By' user, i.e. the user that created the last draft which has locked the Policy, e.g.

jbloggs@email.com

Return type

[PolicyListItemModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "latestAssignedRevisions" : 3,
    "created" : "2000-01-23T04:56:07.000+00:00",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "description" : "description",
    "hasOpenDraft" : true,
    "periodLocked" : "periodLocked",
    "revision" : 2,
    "totalAssignedRevisions" : 9,
    "totalRevisions" : 7,
    "openDraftId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "checkedOutDate" : "2000-01-23T04:56:07.000+00:00",
    "isAssignedToGroup" : true,
    "size" : 5,
    "draftUserId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "name" : "name",
    "lastModifiedUserId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "lastModifiedUser" : "lastModifiedUser",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "lastModified" : "2000-01-23T04:56:07.000+00:00",
    "draftUser" : "draftUser",
    "locked" : true,
    "lastPolicyToGroupAssignment" : "2000-01-23T04:56:07.000+00:00"
  }, {
    "latestAssignedRevisions" : 3,
    "created" : "2000-01-23T04:56:07.000+00:00",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "description" : "description",
    "hasOpenDraft" : true,
    "periodLocked" : "periodLocked",
    "revision" : 2,
    "totalAssignedRevisions" : 9,
    "totalRevisions" : 7,
    "openDraftId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "checkedOutDate" : "2000-01-23T04:56:07.000+00:00",
    "isAssignedToGroup" : true,
    "size" : 5,
    "draftUserId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
```

```
"name" : "name",
"lastModifiedUserId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"lastModifiedUser" : "lastModifiedUser",
"id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"lastModified" : "2000-01-23T04:56:07.000+00:00",
"draftUser" : "draftUser",
"locked" : true,
"lastPolicyToGroupAssignment" : "2000-01-23T04:56:07.000+00:00"
} ],
"pageSize" : 6,
"totalRecordCount" : 1
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success **PolicyListItemModelPagedResponse**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

500

Server Error



```
get /v1/Policies/{id}/AssignedGroups
```

Retrieves list of Groups that are assigned to Policy (v1PoliciesIdAssignedGroupsGet)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

array[[PolicyGroupsListItemModel](#)]

Example data

Content-Type: application/json

```
[ {
  "isDefault" : true,
  "policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "name" : "name",
  "description" : "description",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "policyRevisionId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
}, {
  "isDefault" : true,
  "policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "name" : "name",
  "description" : "description",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "policyRevisionId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
} ]
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

 `get /v1/Policies/{id}/Content`

Downloads Latest Policy Revision (v1PoliciesIdContentGet)

Path parameters

id (required)

Path Parameter — format: uuid

Produces


This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

404

Not Found **ProblemDetails**

 `delete /v1/Policies/{id}`

Deletes policy (v1PoliciesIdDelete)

Path parameters

id (required)

Path Parameter — format: uuid

Query parameters

forceDelete (optional)

Query Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

201

Created **UUID**

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



`patch /v1/Policies/{id}/DiscardDraft`

Reverts and discards policy changes (v1PoliciesIdDiscardDraftPatch)

Path parameters

id (required)

Path Parameter — Policy identifier format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

204

No Content

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



```
get /v1/Policies/{id}
```

Retrieves a detail of the policy (v1PoliciesIdGet)

Path parameters

id (required)

Path Parameter — format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success

401Unauthorized **ProblemDetails****404**Not Found **ProblemDetails** `put /v1/Policies/{id}`

Request to update policy properties (v1PoliciesIdPut)

Path parameters

id (required)

Path Parameter — PolicyId format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ModifyPolicyRequest](#) (optional)**Body Parameter** — policy properties

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

204

No Content

404Not Found **ProblemDetails****409**Conflict **ProblemDetails****423**Client Error **ProblemDetails****get /v1/Policies/{id}/Revisions**

Retrieves list of policy revisions (v1PoliciesIdRevisionsGet)

Path parameters

id (required)

Path Parameter — format: uuid**Return type**array[[PolicyRevisionModel](#)]**Example data**

Content-Type: application/json

```
[ {
  "size" : 6,
  "created" : "2000-01-23T04:56:07.000+00:00",
  "isAssignedGroup" : true,
  "comment" : "comment",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "user" : "user",
  "revision" : 0
}, {
  "size" : 6,
  "created" : "2000-01-23T04:56:07.000+00:00",
  "isAssignedGroup" : true,
  "comment" : "comment",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "user" : "user",
  "revision" : 0
} ]
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**



```
get /v1/Policies/PolicyRevision/{policyRevisionId}/Content
```

Downloads Policy Revision (`v1PoliciesPolicyRevisionPolicyRevisionIdContentGet`)

Path parameters

`policyRevisionId` (required)

Path Parameter — format: `uuid`

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

404

Not Found **ProblemDetails**

Roles

`get /v1/Roles`

Retrieve list of Roles (v1RolesGet)

Return type

array[[RoleListItemModel](#)]

Example data

Content-Type: application/json

```
[ {
  "name" : "name",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "allowPermissions" : [ {
    "resource" : "resource",
    "action" : "action"
  }, {
    "resource" : "resource",
    "action" : "action"
  } ],
  "denyPermissions" : [ null, null ]
}, {
  "name" : "name",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "allowPermissions" : [ {
    "resource" : "resource",
    "action" : "action"
  }, {
    "resource" : "resource",
    "action" : "action"
  } ],
  "denyPermissions" : [ null, null ]
} ]
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

500

Server Error



```
get /v1/Roles/{id}
```

Retrieve role details (v1RolesIdGet)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

[RoleModel](#)

Example data

Content-Type: application/json

```
{
  "name" : "name",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "allowPermissions" : [ {
    "resource" : "resource",
    "action" : "action"
  }, {
    "resource" : "resource",
    "action" : "action"
  }
]
```

```

    } ],
    "denyPermissions" : [ null, null ]
}
    
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **RoleModel**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

500

Server Error

ScimResourceTypes

 `get /scim/v2/ResourceTypes`

gets types of resources available (scimV2ResourceTypesGet)

Query parameters

api-version (optional)

Query Parameter —

Return type

[ScimResourceResponseScimListResponse](#)

Example data

Content-Type: application/json

```
{
  "totalResults" : 0,
  "startIndex" : 6,
  "itemsPerPage" : 1,
  "schemas" : [ "schemas", "schemas" ],
  "Resources" : [ {
    "schema" : "schema",
    "endpoint" : "endpoint",
    "meta" : {
      "resourceType" : "resourceType"
    },
    "schemas" : [ "schemas", "schemas" ],
    "name" : "name",
    "description" : "description"
  }, {
    "schema" : "schema",
    "endpoint" : "endpoint",
    "meta" : {
      "resourceType" : "resourceType"
    },
    "schemas" : [ "schemas", "schemas" ],
    "name" : "name",
    "description" : "description"
  } ]
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **ScimResourceResponseScimListResponse**



get /scim/v2/ResourceTypes/User

gets types of resources available (scimV2ResourceTypesUserGet)

Query parameters

api-version (optional)

Query Parameter —

Return type

[ScimResourceResponse](#)

Example data

Content-Type: application/json

```
{
  "schema" : "schema",
  "endpoint" : "endpoint",
  "meta" : {
    "resourceType" : "resourceType"
  },
  "schemas" : [ "schemas", "schemas" ],
  "name" : "name",
  "description" : "description"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success **ScimResourceResponse**

ScimSchemas



get /scim/v2/Schemas

Get the Schema supported by the SCIM Api (scimV2SchemasGet)

Query parameters

api-version (optional)

Query Parameter —

Return type

[ScimSchemaResponseScimListResponse](#)

Example data

Content-Type: application/json

```
{
  "totalResults" : 0,
  "startIndex" : 6,
  "itemsPerPage" : 1,
  "schemas" : [ "schemas", "schemas" ],
  "Resources" : [ {
    "meta" : {
      "resourceType" : "resourceType"
    },
    "schemas" : [ "schemas", "schemas" ],
    "name" : "name",
    "description" : "description",
    "attributes" : [ {
      "uniqueness" : "uniqueness",
      "name" : "name",
      "description" : "description",
      "mutability" : "mutability",
      "type" : "type",
      "caseExact" : true,
      "multiValued" : true,
      "returned" : "returned",
      "required" : true,
      "subAttributes" : [ {
        "uniqueness" : "uniqueness",
        "name" : "name",
        "description" : "description",
        "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
        "mutability" : "mutability",
        "type" : "type",
        "caseExact" : true,
        "multiValued" : true,
        "returned" : "returned",
        "required" : true
      }, {
        "uniqueness" : "uniqueness",
```

```
    "name" : "name",
    "description" : "description",
    "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
    "mutability" : "mutability",
    "type" : "type",
    "caseExact" : true,
    "multiValued" : true,
    "returned" : "returned",
    "required" : true
  } ]
}, {
  "uniqueness" : "uniqueness",
  "name" : "name",
  "description" : "description",
  "mutability" : "mutability",
  "type" : "type",
  "caseExact" : true,
  "multiValued" : true,
  "returned" : "returned",
  "required" : true,
  "subAttributes" : [ {
    "uniqueness" : "uniqueness",
    "name" : "name",
    "description" : "description",
    "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
    "mutability" : "mutability",
    "type" : "type",
    "caseExact" : true,
    "multiValued" : true,
    "returned" : "returned",
    "required" : true
  }, {
    "uniqueness" : "uniqueness",
    "name" : "name",
    "description" : "description",
    "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
    "mutability" : "mutability",
    "type" : "type",
    "caseExact" : true,
    "multiValued" : true,
    "returned" : "returned",
    "required" : true
  } ]
} ],
"id" : "id"
}, {
  "meta" : {
    "resourceType" : "resourceType"
  },
  "schemas" : [ "schemas", "schemas" ],
  "name" : "name",
  "description" : "description",
  "attributes" : [ {
```

```
"uniqueness" : "uniqueness",
"name" : "name",
"description" : "description",
"mutability" : "mutability",
"type" : "type",
"caseExact" : true,
"multiValued" : true,
"returned" : "returned",
"required" : true,
"subAttributes" : [ {
  "uniqueness" : "uniqueness",
  "name" : "name",
  "description" : "description",
  "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
  "mutability" : "mutability",
  "type" : "type",
  "caseExact" : true,
  "multiValued" : true,
  "returned" : "returned",
  "required" : true
}, {
  "uniqueness" : "uniqueness",
  "name" : "name",
  "description" : "description",
  "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
  "mutability" : "mutability",
  "type" : "type",
  "caseExact" : true,
  "multiValued" : true,
  "returned" : "returned",
  "required" : true
} ]
}, {
  "uniqueness" : "uniqueness",
  "name" : "name",
  "description" : "description",
  "mutability" : "mutability",
  "type" : "type",
  "caseExact" : true,
  "multiValued" : true,
  "returned" : "returned",
  "required" : true,
  "subAttributes" : [ {
    "uniqueness" : "uniqueness",
    "name" : "name",
    "description" : "description",
    "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
    "mutability" : "mutability",
    "type" : "type",
    "caseExact" : true,
    "multiValued" : true,
    "returned" : "returned",
    "required" : true
```

```

    }, {
      "uniqueness" : "uniqueness",
      "name" : "name",
      "description" : "description",
      "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
      "mutability" : "mutability",
      "type" : "type",
      "caseExact" : true,
      "multiValued" : true,
      "returned" : "returned",
      "required" : true
    } ]
  } ],
  "id" : "id"
} ]
}
    
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success **ScimSchemaResponseScimListResponse**

ScimServiceProviderConfig



`get /scim/v2/ServiceProviderConfig`

gets the Json structure available (scimV2ServiceProviderConfigGet)

Query parameters

api-version (optional)

Query Parameter —

Return type

[ScimServiceProviderConfigResponse](#)

Example data

Content-Type: application/json

```
{
  "patch" : {
    "supported" : true
  },
  "authenticationSchemes" : {
    "name" : "name",
    "description" : "description",
    "type" : "type",
    "primary" : true
  },
  "meta" : {
    "resourceType" : "resourceType"
  },
  "schemas" : [ "schemas", "schemas" ],
  "bulk" : {
    "maxPayloadSize" : 6,
    "maxOperations" : 0,
    "supported" : true
  }
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **ScimServiceProviderConfigResponse**

ScimUsers

 `get /scim/v2/Users`

(scimV2UsersGet)

Query parameters

filter (optional)

Query Parameter —

startIndex (optional)

Query Parameter — format: int32

count (optional)

Query Parameter — format: int32

api-version (optional)

Query Parameter —

Return type

[ScimUserModelScimListResponse](#)

Example data

Content-Type: application/json

```
{
  "totalResults" : 0,
  "startIndex" : 6,
  "itemsPerPage" : 1,
  "schemas" : [ "schemas", "schemas" ],
  "Resources" : [ {
    "displayName" : "displayName",
    "timezone" : "timezone",
    "roles" : [ {
      "value" : "value",
      "primary" : true
    }, {
      "value" : "value",
      "primary" : true
    } ],
    "externalId" : "externalId",
    "groups" : [ "", "" ],
    "active" : true,
    "userName" : "userName",
    "locale" : "locale",
    "emails" : [ {
      "type" : "type",
```

```
    "value" : "value",
    "primary" : true
  }, {
    "type" : "type",
    "value" : "value",
    "primary" : true
  } ],
  "password" : "password",
  "dateTimeFormat" : "dateTimeFormat",
  "meta" : {
    "created" : "2000-01-23T04:56:07.000+00:00",
    "resourceType" : "resourceType"
  },
  "schemas" : [ "schemas", "schemas" ],
  "name" : {
    "givenName" : "givenName",
    "familyName" : "familyName",
    "middleName" : "middleName"
  },
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
}, {
  "displayName" : "displayName",
  "timezone" : "timezone",
  "roles" : [ {
    "value" : "value",
    "primary" : true
  }, {
    "value" : "value",
    "primary" : true
  } ],
  "externalId" : "externalId",
  "groups" : [ "", "" ],
  "active" : true,
  "userName" : "userName",
  "locale" : "locale",
  "emails" : [ {
    "type" : "type",
    "value" : "value",
    "primary" : true
  }, {
    "type" : "type",
    "value" : "value",
    "primary" : true
  } ],
  "password" : "password",
  "dateTimeFormat" : "dateTimeFormat",
  "meta" : {
    "created" : "2000-01-23T04:56:07.000+00:00",
    "resourceType" : "resourceType"
  },
  "schemas" : [ "schemas", "schemas" ],
  "name" : {
    "givenName" : "givenName",
```



```
    "familyName" : "familyName",
    "middleName" : "middleName"
  },
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
} ]
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success **ScimUserModelScimListResponse**



post /scim/v2/Users

(scimV2UsersPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request body

body [ScimUserModel](#) (optional)

Body Parameter —

Query parameters

api-version (optional)

Query Parameter —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

201

Created

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**



```
get /scim/v2/Users/{userID}
```

(scimV2UsersUserIDGet)

Path parameters

userID (required)

Path Parameter — format: uuid

Query parameters

api-version (optional)

Query Parameter —

Return type

[ScimUserModel](#)

Example data

Content-Type: application/json

```
{
  "displayName" : "displayName",
  "timezone" : "timezone",
  "roles" : [ {
    "value" : "value",
    "primary" : true
  }, {
    "value" : "value",
    "primary" : true
  } ],
  "externalId" : "externalId",
  "groups" : [ "", "" ],
  "active" : true,
  "userName" : "userName",
  "locale" : "locale",
  "emails" : [ {
    "type" : "type",
    "value" : "value",
    "primary" : true
  }, {
    "type" : "type",
    "value" : "value",
    "primary" : true
  } ],
  "password" : "password",
  "dateTimeFormat" : "dateTimeFormat",
  "meta" : {
    "created" : "2000-01-23T04:56:07.000+00:00",
    "resourceType" : "resourceType"
  },
  "schemas" : [ "schemas", "schemas" ],
  "name" : {
    "givenName" : "givenName",
    "familyName" : "familyName",
    "middleName" : "middleName"
  },
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **ScimUserModel**

404

Not Found **ProblemDetails**

`patch /scim/v2/Users/{userID}`

Patch operation (scimV2UsersUserIDPatch)

Path parameters

userID (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ScimUserPatchRequest](#) (optional)

Body Parameter —

Query parameters

api-version (optional)

Query Parameter —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success

404Not Found **ProblemDetails****423**Client Error **ProblemDetails** `put /scim/v2/Users/{userID}`

Modify a user (scimV2UsersUserIDPut)

Path parameters

userID (required)

Path Parameter — format: uuid**Consumes**

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request bodybody [ScimUserModel](#) (optional)**Body Parameter** —**Query parameters**

api-version (optional)

Query Parameter —**Produces**

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**

Tasks



`get /v1/Tasks/{id}`

Retrieves a detail of the Task (v1TasksIdGet)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

[TaskDetailModel](#)

Example data

Content-Type: application/json

```
{
  "initiated" : "2000-01-23T04:56:07.000+00:00",
  "messageParameters" : [ {
    "key" : "messageParameters"
  }, {
    "key" : "messageParameters"
  }
]
```

```
} ],
  "stateName" : "stateName",
  "tenantId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "name" : "name",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "state" : 0,
  "completed" : "2000-01-23T04:56:07.000+00:00",
  "completedWithErrors" : true,
  "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "user" : "user"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **TaskDetailModel**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

Users



```
get /v1/Users
```

Retrieves the list of Users with pagination (sorting and filtering) (v1UsersGet)

Query parameters

Sorts (optional)

Query Parameter —

Pagination.PageSize (optional)

Query Parameter — The number of records per page, for example 1. Shouldn't exceed 200. format: int32

Pagination.PageNumber (optional)

Query Parameter — The page number to retrieve from results, for example 1 format: int32

Filter.EmailAddress (optional)

Query Parameter — Email

Filter.RoleId (optional)

Query Parameter — Role identifier format: uuid

Filter.LastSignedIn.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

Filter.LastSignedIn.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.Disabled (optional)

Query Parameter — Is user disabled

Filter.Language (optional)

Query Parameter — Language

Return type

[UserListItemModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "accountName" : "accountName",
    "created" : "2000-01-23T04:56:07.000+00:00",
    "roles" : [ {
      "resourceId" : "resourceId",
      "name" : "name",
      "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "resourceType" : "resourceType"
    }, {
      "resourceId" : "resourceId",
```



```
    "name" : "name",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "resourceType" : "resourceType"
  } ],
  "errorInfo" : {
    "userAccountName" : "userAccountName",
    "parentTaskName" : "parentTaskName",
    "initiated" : "2000-01-23T04:56:07.000+00:00",
    "errorCode" : 0,
    "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
  },
  "language" : "language",
  "emailAddress" : "emailAddress",
  "olsonTimeZoneId" : "olsonTimeZoneId",
  "roleName" : "roleName",
  "disabled" : true,
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "locked" : true,
  "dateTimeDisplayFormat" : "dateTimeDisplayFormat",
  "lastSignedIn" : "2000-01-23T04:56:07.000+00:00"
}, {
  "accountName" : "accountName",
  "created" : "2000-01-23T04:56:07.000+00:00",
  "roles" : [ {
    "resourceId" : "resourceId",
    "name" : "name",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "resourceType" : "resourceType"
  }, {
    "resourceId" : "resourceId",
    "name" : "name",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "resourceType" : "resourceType"
  } ],
  "errorInfo" : {
    "userAccountName" : "userAccountName",
    "parentTaskName" : "parentTaskName",
    "initiated" : "2000-01-23T04:56:07.000+00:00",
    "errorCode" : 0,
    "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
  },
  "language" : "language",
  "emailAddress" : "emailAddress",
  "olsonTimeZoneId" : "olsonTimeZoneId",
  "roleName" : "roleName",
  "disabled" : true,
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "locked" : true,
  "dateTimeDisplayFormat" : "dateTimeDisplayFormat",
  "lastSignedIn" : "2000-01-23T04:56:07.000+00:00"
} ],
"pageSize" : 6,
"totalRecordCount" : 1
```

```
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **UserListItemModelPagedResponse**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

500

Server Error



```
post /v1/Users/{id}/AssignRole
```

Assign Role to User (`v1UsersIdAssignRolePost`)

Path parameters

id (required)

Path Parameter — UserId format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [AssignUserToRoleRequest](#) (optional)

Body Parameter — Role assignment request containing Role identifier

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

204

No Content

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



```
patch /v1/Users/{id}/Disable
```

Disables User (v1UsersIdDisablePatch)

Path parameters

id (required)

Path Parameter — UserId format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

204

No Content

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



`patch /v1/Users/{id}/Enable`

Enables User (v1UsersIdEnablePatch)

Path parameters

id (required)

Path Parameter — format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

204

No Content

401Unauthorized **ProblemDetails****404**Not Found **ProblemDetails****423**Client Error **ProblemDetails**`get /v1/Users/{id}`

Retrieves a detail of the User (v1UsersIdGet)

Path parameters

id (required)

Path Parameter — format: uuid**Return type**[UserDetailModel](#)**Example data**

Content-Type: application/json

```
{
  "emailAddress" : "emailAddress",
  "accountName" : "accountName",
  "created" : "2000-01-23T04:56:07.000+00:00",
  "olsonTimeZoneId" : "olsonTimeZoneId",
  "roles" : [ {
    "resourceId" : "resourceId",
    "name" : "name",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "allowPermissions" : [ {
      "resource" : "resource",
      "action" : "action"
    }, {
      "resource" : "resource",
      "action" : "action"
    } ],
    "denyPermissions" : [ null, null ],
    "resourceType" : "resourceType"
  } ]
}
```

```
}, {
  "resourceId" : "resourceId",
  "name" : "name",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "allowPermissions" : [ {
    "resource" : "resource",
    "action" : "action"
  }, {
    "resource" : "resource",
    "action" : "action"
  } ],
  "denyPermissions" : [ null, null ],
  "resourceType" : "resourceType"
} ],
"isFirstSignIn" : true,
"disabled" : true,
"language" : "language",
"allowInvites" : true,
"id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"dateTimeDisplayFormat" : "dateTimeDisplayFormat",
"lastSignedIn" : "2000-01-23T04:56:07.000+00:00"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **UserDetailModel**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

`put /v1/Users/{id}/ModifyUserPreferences`

Modifies User Preferences (v1UsersIdModifyUserPreferencesPut)

Path parameters

id (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ModifyUserPreferencesRequest](#) (optional)

Body Parameter —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

204

No Content

400


Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

409Conflict **ProblemDetails****423**Client Error **ProblemDetails**

Modifies User (v1UsersIdPut)

Path parameters

id (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ModifyUserRequest](#) (optional)**Body Parameter** —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

204

No Content

400Bad Request **ProblemDetails****401**Unauthorized **ProblemDetails****404**Not Found **ProblemDetails****409**Conflict **ProblemDetails****423**Client Error **ProblemDetails**`patch /v1/Users/{id}/ResendInvite`

Resends invitation email to User (v1UsersIdResendInvitePatch)

Path parameters

id (required)

Path Parameter — format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

204

No Content

401Unauthorized **ProblemDetails**

404Not Found **ProblemDetails** `post /v1/Users`

Creates User (v1UsersPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [CreateUserRequest](#) (optional)**Body Parameter** —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

201Created **UUID**

400Bad Request **ProblemDetails****401**Unauthorized **ProblemDetails****409**Conflict **ProblemDetails**

Models

[[Jump to Methods](#)]

Table of Contents

1. [AcceptedDomainDetailModel](#)
2. [AcceptedDomainListItemModel](#)
3. [ActivityAuditDetailModel](#)
4. [ActivityAuditDetailModelPagedResponse](#)
5. [ActivityAuditListItemModel](#)
6. [ActivityAuditListItemModelPagedResponse](#)
7. [ActivityAuditRoleNameModel](#)
8. [ActivityAuditRoleResourceModel](#)
9. [Agent](#)
10. [AgentBuild](#)
11. [AgentHostType](#)
12. [ApiClientDataAuditingDetailModel](#)
13. [Application](#)
14. [Applicationgroup](#)
15. [As](#)
16. [AsOrganization](#)
17. [AssignComputersToGroupRequest](#)
18. [AssignPolicyRevisionToGroupRequest](#)
19. [AssignUserToRoleRequest](#)
20. [Attribute](#)
21. [Authorization](#)
22. [AuthorizationRequestAuditDetailModel](#)
23. [AuthorizationRequestAuditDetailModelPagedResponse](#)
24. [AuthorizationRequestAuditListItemModel](#)
25. [AuthorizationRequestAuditListItemModelPagedResponse](#)
26. [Authorizationrequest](#)
27. [Authorizinguser](#)
28. [Base](#)
29. [Bundle](#)
30. [CertificateInformationModel](#)
31. [ChangedBy](#)
32. [Client](#)
33. [ClientNat](#)
34. [Cloud](#)

35. [CloudAccount](#)
36. [CloudInstance](#)
37. [CloudMachine](#)
38. [CloudOrigin](#)
39. [CloudProject](#)
40. [CloudService](#)
41. [CloudTarget](#)
42. [CodeSignature](#)
43. [Com](#)
44. [ComputerDataAuditingDetailModel](#)
45. [ComputerDetailModel](#)
46. [ComputerFilterModel](#)
47. [ComputerListItemModel](#)
48. [ComputerListItemModelPagedResponse](#)
49. [ComputerLogModel](#)
50. [ComputerRenewCertificateRequest](#)
51. [ComputerRetrieveLogsRequest](#)
52. [ComputerRetrieveStatusInfoRequest](#)
53. [ComputersAuthoriseRequest](#)
54. [ComputersDeactivateRequest](#)
55. [ComputersRejectRequest](#)
56. [ComputersRemoveRequest](#)
57. [Configuration](#)
58. [Container](#)
59. [ContainerCpu](#)
60. [ContainerDisk](#)
61. [ContainerDiskRead](#)
62. [ContainerDiskWrite](#)
63. [ContainerImage](#)
64. [ContainerImageHash](#)
65. [ContainerMemory](#)
66. [ContainerNetwork](#)
67. [ContainerNetworkEgress](#)
68. [ContainerNetworkIngress](#)
69. [Content](#)
70. [Contentgroup](#)
71. [CountRange](#)
72. [CreateAcceptedDomainRequest](#)
73. [CreateGroupRequest](#)
74. [CreateUserRequest](#)

75. [DataStream](#)
76. [DateFilterModel](#)
77. [DateSelectionMode](#)
78. [Destination](#)
79. [DestinationNat](#)
80. [DII](#)
81. [Dns](#)
82. [DnsQuestion](#)
83. [Ecs](#)
84. [Elf](#)
85. [ElfHeader](#)
86. [ElfSections](#)
87. [ElfSegments](#)
88. [Email](#)
89. [EmailAttachments](#)
90. [EmailAttachmentsFile](#)
91. [EmailBcc](#)
92. [EmailCc](#)
93. [EmailFrom](#)
94. [EmailReplyTo](#)
95. [EmailSender](#)
96. [EmailTo](#)
97. [EndpointInformationModel](#)
98. [EpmEcsEvent](#)
99. [EpmEcsEventResponseModel](#)
100. [Epmwinmac](#)
101. [Error](#)
102. [Event](#)
103. [Faas](#)
104. [FaasTrigger](#)
105. [File](#)
106. [Geo](#)
107. [GeoPoint](#)
108. [Gpo](#)
109. [Group](#)
110. [GroupDataAuditingDetailModel](#)
111. [GroupListItemModel](#)
112. [GroupListItemModelPagedResponse](#)
113. [Hash](#)
114. [Host](#)

115. [HostBoot](#)
116. [HostCpu](#)
117. [HostDisk](#)
118. [HostDiskRead](#)
119. [HostDiskWrite](#)
120. [HostNetwork](#)
121. [HostNetworkEgress](#)
122. [HostNetworkIngress](#)
123. [Http](#)
124. [HttpRequest](#)
125. [HttpRequestBody](#)
126. [HttpResponse](#)
127. [HttpResponseBody](#)
128. [InstallationKeyDataAuditingDetailModel](#)
129. [ListItemErrorInfoModel](#)
130. [Log](#)
131. [LogFile](#)
132. [LogOrigin](#)
133. [LogOriginFile](#)
134. [Message](#)
135. [ModifyAcceptedDomainRequest](#)
136. [ModifyGroupRequest](#)
137. [ModifyPolicyRequest](#)
138. [ModifyUserPreferencesRequest](#)
139. [ModifyUserRequest](#)
140. [Network](#)
141. [OS](#)
142. [Observer](#)
143. [OperationValue](#)
144. [Operator](#)
145. [Orchestrator](#)
146. [OrchestratorCluster](#)
147. [OrchestratorResource](#)
148. [OrchestratorResourceParent](#)
149. [Organization](#)
150. [Os](#)
151. [Owner](#)
152. [Package](#)
153. [Pe](#)
154. [PolicyDataAudtingDetailModel](#)

- 155. [PolicyGroupsListItemModel](#)
- 156. [PolicyListItemModel](#)
- 157. [PolicyListItemModelPagedResponse](#)
- 158. [PolicyRevisionDataAuditingDetailModel](#)
- 159. [PolicyRevisionModel](#)
- 160. [PolicyRevisionState](#)
- 161. [Privilegedgroup](#)
- 162. [ProblemDetails](#)
- 163. [Process](#)
- 164. [ProcessEntryLeader](#)
- 165. [ProcessEntryMeta](#)
- 166. [ProcessGroupLeader](#)
- 167. [ProcessParent](#)
- 168. [ProcessPrevious](#)
- 169. [ProcessSessionLeader](#)
- 170. [ProcessThread](#)
- 171. [Registry](#)
- 172. [RegistryData](#)
- 173. [Related](#)
- 174. [RoleElement](#)
- 175. [RoleItemModel](#)
- 176. [RoleListItemModel](#)
- 177. [RoleModel](#)
- 178. [RolePermissionModel](#)
- 179. [Rule](#)
- 180. [Rulescript](#)
- 181. [RulescriptOutcome](#)
- 182. [SCIMEmail](#)
- 183. [SCIMUserName](#)
- 184. [ScimAuthenticationSchemes](#)
- 185. [ScimBulk](#)
- 186. [ScimOperation](#)
- 187. [ScimResourceMeta](#)
- 188. [ScimResourceResponse](#)
- 189. [ScimResourceResponseScimListResponse](#)
- 190. [ScimSchemaResponse](#)
- 191. [ScimSchemaResponseScimListResponse](#)
- 192. [ScimServiceProviderConfigResponse](#)
- 193. [ScimSupported](#)
- 194. [ScimUserMetaModel](#)

- 195. [ScimUserModel](#)
- 196. [ScimUserModelScimListResponse](#)
- 197. [ScimUserPatchRequest](#)
- 198. [Server](#)
- 199. [ServerNat](#)
- 200. [Service](#)
- 201. [ServiceNode](#)
- 202. [ServiceOrigin](#)
- 203. [ServiceTarget](#)
- 204. [Session](#)
- 205. [SettingDataAuditingDetailModel](#)
- 206. [SortDirection](#)
- 207. [SortModel](#)
- 208. [Source](#)
- 209. [SourceNat](#)
- 210. [SubAttribute](#)
- 211. [TaskDetailModel](#)
- 212. [Threat](#)
- 213. [ThreatEnrichments](#)
- 214. [ThreatEnrichmentsMatched](#)
- 215. [ThreatFeed](#)
- 216. [ThreatGroup](#)
- 217. [ThreatIndicator](#)
- 218. [ThreatIndicatorEmail](#)
- 219. [ThreatIndicatorMarking](#)
- 220. [ThreatSoftware](#)
- 221. [ThreatTactic](#)
- 222. [ThreatTechnique](#)
- 223. [ThreatTechniqueSubtechnique](#)
- 224. [Tls](#)
- 225. [TlsClient](#)
- 226. [TlsClientHash](#)
- 227. [TlsServer](#)
- 228. [TlsServerHash](#)
- 229. [Token](#)
- 230. [Tracing](#)
- 231. [TracingSpan](#)
- 232. [TracingTrace](#)
- 233. [TracingTransaction](#)
- 234. [UnassignComputersToGroupRequest](#)

- 235. [Url](#)
- 236. [User](#)
- 237. [UserAgent](#)
- 238. [UserAgentDevice](#)
- 239. [UserChanges](#)
- 240. [UserDataAuditing](#)
- 241. [UserDetailModel](#)
- 242. [UserEffective](#)
- 243. [UserListItemModel](#)
- 244. [UserListItemModelPagedResponse](#)
- 245. [UserRoleResourceItemModel](#)
- 246. [UserTarget](#)
- 247. [Vlan](#)
- 248. [Vulnerability](#)
- 249. [VulnerabilityScanner](#)
- 250. [VulnerabilityScore](#)
- 251. [Workstyle](#)
- 252. [X509](#)
- 253. [X509Issuer](#)
- 254. [X509Subject](#)
- 255. [_event](#)
- 256. [_rule](#)
- 257. [id_AssignComputersByCsv_body](#)



AcceptedDomainDetailModel

id (optional)

UUID Accepted Domain Id format: uuid

domain (optional)

String Accepted Domain name

created (optional)

Date Created date format: date-time



AcceptedDomainListItemModel

Model of Accepted Domain list item

id (optional)

UUID The Id (Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

locked (optional)

Boolean

errorInfo (optional)

ListItemErrorInfoModel

domain (optional)

String Accepted Domain name

created (optional)

Date Created date format: date-time



ActivityAuditDetailModel

Activity audit detail model

id (optional)

Long Id format: int64

details (optional)

String Details

userId (optional)

UUID User id format: uuid

user (optional)

String user name

entity (optional)

String entity

auditType (optional)

String audit type

created (optional)

Date created format: date-time

changedBy (optional)

ChangedBy

apiClientDataAuditing (optional)

ApiClientDataAuditingDetailModel

computerDataAuditing (optional)

ComputerDataAuditingDetailModel

groupDataAuditing (optional)

GroupDataAuditingDetailModel

installationKeyDataAuditing (optional)

InstallationKeyDataAuditingDetailModel

policyDataAuditing (optional)

PolicyDataAuditingDetailModel

policyRevisionDataAuditing (optional)

PolicyRevisionDataAuditingDetailModel

settingsDataAuditing (optional)

SettingDataAuditingDetailModel

userDataAuditing (optional)

UserDataAuditing**ActivityAuditDetailModelPagedResponse**

pageNumber (optional)

Integer format: int32

pageSize (optional)

Integer format: int32

totalRecordCount (optional)

Integer format: int32

pageCount (optional)

Integer format: int32

data (optional)

array[ActivityAuditDetailModel]**ActivityAuditListItemModel**

Model of Activity Audit list item

id (optional)

Long Activity Audit identifier format: int64

locked (optional)

Boolean

errorInfo (optional)

ListItemErrorInfoModel

details (optional)

String Activity Audit Details

user (optional)

String Initiated User email or API Client identifier

created (optional)

Date Created date format: date-time

entity (optional)

String Name of Activity Audit entity

auditType (optional)

String Audit Type Name

changedBy (optional)

ChangedBy



ActivityAuditListItemModelPagedResponse

pageNumber (optional)

Integer format: int32

pageSize (optional)

Integer format: int32

totalRecordCount (optional)

Integer format: int32

pageCount (optional)

Integer format: int32

data (optional)

array[ActivityAuditListItemModel]



ActivityAuditRoleNameModel

activity audit role name mapping model

roleId (optional)

UUID role id format: uuid

roleName (optional)

String role name



ActivityAuditRoleResourceModel

Role Resource Model for activity audits

resourceType (optional)

String Type of resource

resourceId (optional)

UUID Id of the resource format: uuid
resourceName (optional)
String Resource name
newRoles (optional)
array[ActivityAuditRoleNameModel] List of new roles
oldRoles (optional)
array[ActivityAuditRoleNameModel] List of oldRoles

Agent

version (optional)
String
build (optional)
AgentBuild
name (optional)
String
type (optional)
String
id (optional)
String
ephemeral_id (optional)
String

AgentBuild

original (optional)
String

AgentHostType

enum
String

- Undefined
- MicrosoftWindows
- AppleMacOS
- Linux



ApiClientDataAuditingDetailModel

newName (optional)

String

oldName (optional)

String

newDescription (optional)

String

oldDescription (optional)

String

secretUpdated (optional)

Boolean

deleted (optional)

Boolean



Application

Type (optional)

String

Description (optional)

String

Identifier (optional)

String



Applicationgroup

Name (optional)

String

Description (optional)

String

Identifier (optional)

String



number (optional)

Long format: int64

organization (optional)

AsOrganization



name (optional)

String



computerIds (optional)

array[UUID] computer ids which will be assigned to the group format: uuid

excludedComputerIds (optional)

array[UUID] computer ids which will not be assigned to group format: uuid

filter (optional)

ComputerFilterModel

allComputers (optional)

Boolean assigns all computers to the group



policyRevisionId (optional)

UUID format: uuid



AssignUserToRoleRequest

Model for assigning role to user
roleId

UUID Role identifier format: uuid



Attribute

attributes of schemas

name (optional)

String name of attribute

description (optional)

String description of attribute

type (optional)

String type of attribute

caseExact (optional)

Boolean Flag for whether or not the attribute's casing should be exact

multiValued (optional)

Boolean Flag for whether or not the attribute has multi values

mutability (optional)

String Mutability of the attribute

required (optional)

Boolean Flag for whether or not the attribute is required

returned (optional)

String how the attribute is returned

uniqueness (optional)

String Is the value unique

subAttributes (optional)

array[SubAttribute] List of subattributes



Authorization

ChallengeCode (optional)

String

ResponseStatus (optional)

String



AuthorizationRequestAuditDetailModel

id (optional)

Long format: int64

ticketId (optional)

String

productName (optional)

String

user (optional)

String

computerName (optional)

String

reason (optional)

String

decisionPerformedByUser (optional)

String

timeOfRequest (optional)

Date format: date-time

decisionTime (optional)

Date format: date-time

decision (optional)

String

startTime (optional)

Date format: date-time

duration (optional)

String



AuthorizationRequestAuditDetailModelPagedResponse

pageNumber (optional)

Integer format: int32

pageSize (optional)

Integer format: int32

totalRecordCount (optional)

Integer format: int32

pageCount (optional)

Integer format: int32

data (optional)

array[AuthorizationRequestAuditDetailModel]



AuthorizationRequestAuditListItemModel

id (optional)

Long format: int64

ticketId (optional)

String

productName (optional)

String

user (optional)

String

computerName (optional)

String

reason (optional)

String

decisionPerformedByUser (optional)

String

timeOfRequest (optional)

Date format: date-time

decisionTime (optional)

Date format: date-time

decision (optional)

String

duration (optional)

String

startTime (optional)

Date format: date-time



AuthorizationRequestAuditListItemModelPagedResponse

pageNumber (optional)

Integer format: int32

pageSize (optional)

Integer format: int32

totalRecordCount (optional)

Integer format: int32

pageCount (optional)

Integer format: int32

data (optional)

array[AuthorizationRequestAuditListItemModel]



Authorizationrequest

ControlAuthorization (optional)

Boolean

AuthRequestURI (optional)

String



Authorizinguser

Identifier (optional)

String

Name (optional)

String

DomainIdentifier (optional)

String

DomainName (optional)

String

 **Base**

@timestamp (optional)

Date format: date-time

tags (optional)

array[String]

labels (optional)

String

message (optional)

String

 **Bundle**

Name (optional)

String

Type (optional)

String

Creator (optional)

String

InfoDescription (optional)

String

Version (optional)

String

DownloadSource (optional)

String

 **CertificateInformationModel**

validFrom (optional)

Date format: date-time

validTo (optional)

Date format: date-time

lastIssued (optional)

Date format: date-time



ChangedBy

enum

String

- API
- Portal



Client

address (optional)

String

ip (optional)

String

port (optional)

Long format: int64

mac (optional)

String

domain (optional)

String

registered_domain (optional)

String

top_level_domain (optional)

String

subdomain (optional)

String

bytes (optional)

Long format: int64

packets (optional)

Long format: int64

nat (optional)

ClientNat

as (optional)

As

geo (optional)

Geo

user (optional)

User

 **ClientNat**

ip (optional)

String

port (optional)

Long format: int64

 **Cloud**

provider (optional)

String

availability_zone (optional)

String

region (optional)

String

instance (optional)

CloudInstance

machine (optional)

CloudMachine

account (optional)

CloudAccount

service (optional)

CloudService

project (optional)

CloudProject

origin (optional)

CloudOrigin

target (optional)

CloudTarget

 **CloudAccount**

id (optional)

String

name (optional)

String



CloudInstance

id (optional)

String

name (optional)

String



CloudMachine

type (optional)

String



CloudOrigin

provider (optional)

String

availability_zone (optional)

String

region (optional)

String

instance (optional)

CloudInstance

machine (optional)

CloudMachine

account (optional)

CloudAccount

service (optional)

CloudService

project (optional)

CloudProject

**CloudProject**

id (optional)

String

name (optional)

String**CloudService**

name (optional)

String**CloudTarget**

provider (optional)

String

availability_zone (optional)

String

region (optional)

String

instance (optional)

CloudInstance

machine (optional)

CloudMachine

account (optional)

CloudAccount

service (optional)

CloudService

project (optional)

CloudProject



CodeSignature

exists (optional)

Boolean

subject_name (optional)

String

valid (optional)

Boolean

trusted (optional)

Boolean

status (optional)

String

team_id (optional)

String

signing_id (optional)

String

digest_algorithm (optional)

String

timestamp (optional)

Date format: date-time



Com

AppID (optional)

String

CLSID (optional)

String

DisplayName (optional)

String



ComputerDataAuditingDetailModel

updatedPoliciesOn (optional)

map[String, String]

deactivatedAgents (optional)

map[String, String]
newDeletedAgents (optional)
array[String]



ComputerDetailModel

id (optional)
UUID format: uuid
hostType (optional)
String
created (optional)
Date format: date-time
adapterVersion (optional)
String
agentVersion (optional)
String
authorisationState (optional)
String
authorised (optional)
Date format: date-time
connected (optional)
Boolean
lastConnected (optional)
Date format: date-time
deactivated (optional)
Boolean
autoDeactivated (optional)
Boolean
pendingDeactivation (optional)
Boolean
deactivatedOn (optional)
Date format: date-time
groupId (optional)
UUID format: uuid
groupName (optional)
String
policyId (optional)
UUID format: uuid

policyName (optional)

String

policyRevision (optional)

Integer format: int32

policyRevisionStatus (optional)

String

endpointInformation (optional)

EndpointInformationModel

certificateInformation (optional)

CertificateInformationModel

hostPolicyId (optional)

UUID format: uuid

hostPolicyName (optional)

String

hostPolicyRevision (optional)

Integer format: int32

hostLastUpdated (optional)

Date format: date-time

agentLogs (optional)

array[ComputerLogModel]

duplicateCount (optional)

Integer format: int32

credentialType (optional)

String



ComputerFilterModel

computerId (optional)

UUID The Id of the Computer(Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

host (optional)

String The host name of the Computer, for example - Computer1

hostType (optional)

AgentHostType

agentVersion (optional)

String The agent version of the Computer, example - 5.6.126.0

adapterVersion (optional)

String The adapter version of the Computer, example - 20.5.195.0

authorisationState (optional)

String The state of the Computer, example - Authorised, Pending
lastConnected (optional)
DateFilterModel
policyRevisionStatus (optional)
String Policy Revision Status, example - AwaitingLatestPolicy
policyId (optional)
UUID Policy Id, example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid
policyName (optional)
String Policy Name, example - Policy1
groupId (optional)
UUID Group Id, example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid
groupName (optional)
String Group Name, example - Group1
os (optional)
OS
domain (optional)
String Domain Name, example - BeyondTrust
created (optional)
DateFilterModel
duplicateCount (optional)
CountRange



ComputerListItemModel

id (optional)
UUID The Id (Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid
locked (optional)
Boolean
errorInfo (optional)
ListItemErrorInfoModel
created (optional)
Date Created Date of the computer, example - 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562 format: date-time
host (optional)
String The host name of the Computer, for example - Computer1
hostType (optional)
AgentHostType
os (optional)
String OS Name, example - Windows

domain (optional)

String Domain Name, example - BeyondTrust

adapterVersion (optional)

String The adapter version of the Computer, example - 20.5.195.0

agentVersion (optional)

String The agent version of the Computer, example - 5.6.126.0

authorisationState (optional)

String The state of the Computer, example - Authorised, Pending

lastConnected (optional)

Date Date when computer is last connected, example - 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562 format: date-time

deactivated (optional)

Boolean if computer is deactivated, example - false

deactivatedOn (optional)

Date Date when computer turned into deactivation state, example - 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562 format: date-time

pendingDeactivation (optional)

Boolean if computer is in PendingDeactivation state, example - false

rejected (optional)

Boolean if computer is deactivated, example - false

duplicate (optional)

Boolean if computer has/is duplicate, example - false

duplicateCount (optional)

Integer Computer duplicate count, Min and Max Ranges, example - 1,2,3 format: int32

policyRevisionId (optional)

UUID format: uuid

policyId (optional)

UUID Policy Id, example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

policyName (optional)

String Policy Name, example - Policy1

policyRevisionStatus (optional)

String

groupId (optional)

UUID Group Id, example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

groupName (optional)

String Group Name, example - Group1

credentialType (optional)

String



ComputerListItemModelPagedResponse

pageNumber (optional)

Integer format: int32

pageSize (optional)

Integer format: int32

totalRecordCount (optional)

Integer format: int32

pageCount (optional)

Integer format: int32

data (optional)

array[ComputerListItemModel]



ComputerLogModel

id (optional)

UUID format: uuid

created (optional)

Date format: date-time

returned (optional)

Date format: date-time



ComputerRenewCertificateRequest

computerId (optional)

UUID format: uuid



ComputerRetrieveLogsRequest

computerId (optional)

UUID format: uuid



ComputerRetrieveStatusInfoRequest

computerId (optional)

UUID format: uuid



ComputersAuthoriseRequest

computerIds (optional)

array[UUID] format: uuid

excludedComputerIds (optional)

array[UUID] format: uuid

filter (optional)

ComputerFilterModel

allComputers (optional)

Boolean

groupId (optional)

UUID format: uuid



ComputersDeactivateRequest

computerIds (optional)

array[UUID] format: uuid

excludedComputerIds (optional)

array[UUID] format: uuid

filter (optional)

ComputerFilterModel

allComputers (optional)

Boolean



ComputersRejectRequest

Request to reject Computer(s)

computerIds (optional)

array[UUID] List of Computers identifiers to be rejected format: uuid

excludedComputerIds (optional)

array[UUID] List of Computers identifiers to be excluded from the rejection list format: uuid

filter (optional)

ComputerFilterModel

allComputers (optional)

Boolean Is all Computers matching BT.Common.ManagementApi.Computer.ComputerFilterModel and ExcludedComputerIds should be rejected



ComputersRemoveRequest

Request to remove Computer(s)

computerIds (optional)

array[UUID] List of Computers identifiers to be removed format: uuid

excludedComputerIds (optional)

array[UUID] List of Computers identifiers to be excluded from the deletion list format: uuid

filter (optional)

ComputerFilterModel

allComputers (optional)

Boolean Is all Computers matching BT.Common.ManagementApi.Computer.ComputerFilterModel and ExcludedComputerIds should be removed



Configuration

Identifier (optional)

String

RevisionNumber (optional)

String

Source (optional)

String

Name (optional)

String

Path (optional)

String

Application (optional)

Application

ApplicationGroup (optional)

Applicationgroup

Content (optional)

Content

ContentGroup (optional)

Contentgroup

GPO (optional)

Gpo

Message (optional)

Message

Rule (optional)

Rule

RuleScript (optional)

Rulescript

Token (optional)

Token

Workstyle (optional)

Workstyle



Container

cpu (optional)

ContainerCpu

disk (optional)

ContainerDisk

id (optional)

String

image (optional)

ContainerImage

labels (optional)

String

memory (optional)

ContainerMemory

name (optional)

String

network (optional)

ContainerNetwork

runtime (optional)

String

ContainerCpu

usage (optional)

Double format: double

ContainerDisk

read (optional)

ContainerDiskRead

write (optional)

ContainerDiskWrite

ContainerDiskRead

bytes (optional)

Long format: int64

ContainerDiskWrite

bytes (optional)

Long format: int64

ContainerImage

name (optional)


String

tag (optional)

`array[String]`
hash (optional)
ContainerImageHash

 **ContainerImageHash**

all (optional)
`array[String]`

 **ContainerMemory**

usage (optional)
Double format: double

 **ContainerNetwork**

ingress (optional)
ContainerNetworkIngress
egress (optional)
ContainerNetworkEgress

 **ContainerNetworkEgress**

bytes (optional)
Long format: int64

 **ContainerNetworkIngress**

bytes (optional)

Long format: int64

Content

Type (optional)

String

Description (optional)

String

Identifier (optional)

String

Contentgroup

Name (optional)

String

Description (optional)

String

Identifier (optional)

String

CountRange

min (optional)

Integer Min Value of CountRange, example - 1,2,3 format: int32

max (optional)

Integer Max Value of CountRange, example - 1,2,3 format: int32

CreateAcceptedDomainRequest

Create Accepted Domain Model

domainName (optional)

String Accepted Domain Name



CreateGroupRequest

name (optional)

String name of the group, for example - Alianse Group

description (optional)

String description of the group, for example - Alianse Group Description

isDefault (optional)

Boolean



CreateUserRequest

CreateUserRequest

emailAddress (optional)

String EmailAddress

olsonTimeZoneld (optional)

String OlsonTimeZoneld

dateTimeDisplayFormat (optional)

String DateTimeDisplayFormat

roleId (optional)

UUID RoleId format: uuid

language (optional)

String Language

enabled (optional)

Boolean Enabled



DataStream

type (optional)

String

dataset (optional)

String

namespace (optional)

String



DateFilterModel

dates (optional)

array[Date] Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

selectionMode (optional)

DateSelectionMode



DateSelectionMode

enum

String

- Single
- Multiple
- Range



Destination

address (optional)

String

ip (optional)

String

port (optional)

Long format: int64

mac (optional)

String

domain (optional)

String

registered_domain (optional)

String

top_level_domain (optional)

String

subdomain (optional)

String

bytes (optional)
Long format: int64
packets (optional)
Long format: int64
nat (optional)
DestinationNat
as (optional)
As
geo (optional)
Geo
user (optional)
User



DestinationNat

ip (optional)
String
port (optional)
Long format: int64



D11

name (optional)
String
path (optional)
String
hash (optional)
Hash
pe (optional)
Pe
code_signature (optional)
CodeSignature

 **Dns**

type (optional)

String

id (optional)

String

op_code (optional)

String

header_flags (optional)

array[String]

response_code (optional)

String

question (optional)


DnsQuestion

answers (optional)

String

resolved_ip (optional)

array[String]

 **DnsQuestion**

name (optional)

String

type (optional)

String

class (optional)

String

registered_domain (optional)

String

top_level_domain (optional)

String

subdomain (optional)

String

 **Ecs**

version (optional)

String

 **Elf**

creation_date (optional)

Date format: date-time

architecture (optional)

String

byte_order (optional)

String

cpu_type (optional)

String

header (optional)

ElfHeader

sections (optional)

array[ElfSections]

exports (optional)

map[String, String]

imports (optional)

map[String, String]

shared_libraries (optional)

array[String]

telhash (optional)

String

segments (optional)

array[ElfSegments]

 **ElfHeader**

class (optional)

String

data (optional)

String

os_abi (optional)

String

type (optional)

String

version (optional)

String

abi_version (optional)

String

entrypoint (optional)

Long format: int64

object_version (optional)

String**ElfSections**

flags (optional)

String

name (optional)

String

physical_offset (optional)

String

type (optional)

String

physical_size (optional)

Long format: int64

virtual_address (optional)

Long format: int64

virtual_size (optional)

Long format: int64

entropy (optional)

Long format: int64

chi2 (optional)

Long format: int64

**ElfSegments**

type (optional)

String

sections (optional)

String**Email**

attachments (optional)

array[EmailAttachments]

bcc (optional)

EmailBcc

cc (optional)

EmailCc

content_type (optional)

String

delivery_timestamp (optional)

Date format: date-time

direction (optional)

String

from (optional)

EmailFrom

local_id (optional)

String

message_id (optional)

String

origination_timestamp (optional)

Date format: date-time

reply_to (optional)

EmailReplyTo

sender (optional)

EmailSender

subject (optional)

String

to (optional)

EmailTo

x_mailer (optional)

String



EmailAttachments

file (optional)

EmailAttachmentsFile



EmailAttachmentsFile

extension (optional)

String

mime_type (optional)

String

name (optional)

String

size (optional)

Long format: int64

hash (optional)

Hash



EmailBcc

address (optional)

array[String]



EmailCc

address (optional)

array[String]

 **EmailFrom**

address (optional)
array[String]

 **EmailReplyTo**

address (optional)
array[String]

 **EmailSender**

address (optional)
String

 **EmailTo**

address (optional)
array[String]

 **EndpointInformationModel**

macAddress (optional)
String
osArchitecture (optional)
String
osCaption (optional)
String
osCodeSet (optional)
String

osComputerDescription (optional)

String

osCountryCode (optional)

String

osInstallDate (optional)

Date format: date-time

osManufacturer (optional)

String

osOrganization (optional)

String

osSerialNumber (optional)

String

osSystemDirectory (optional)

String

osSystemDrive (optional)

String

osVersion (optional)

String

osVersionString (optional)

String

processorCaption (optional)

String

processorDescription (optional)

String

processorManufacturer (optional)

String

processorName (optional)

String

systemDnsHostName (optional)

String

systemDomain (optional)

String

systemManufacturer (optional)

String

systemModel (optional)

String

systemName (optional)

String

systemPrimaryOwnerName (optional)

String

systemSystemType (optional)

String

systemWorkgroup (optional)

String



EpmEcsEvent

agent (optional)

Agent

base (optional)

Base

client (optional)

Client

cloud (optional)

Cloud

container (optional)

Container

data_stream (optional)

DataStream

destination (optional)

Destination

dll (optional)

Dll

dns (optional)

Dns

ecs (optional)

Ecs

email (optional)

Email

error (optional)

Error

event (optional)

_event

faas (optional)

Faas

file (optional)

File

group (optional)

Group

host (optional)

Host

http (optional)

Http

log (optional)

Log

network (optional)

Network

observer (optional)

Observer

orchestrator (optional)

Orchestrator

organization (optional)

Organization

package (optional)

Package

process (optional)

Process

registry (optional)

Registry

related (optional)

Related

rule (optional)

_rule

server (optional)

Server

service (optional)

Service

source (optional)

Source

threat (optional)

Threat

tls (optional)

Tls

tracing (optional)

Tracing

url (optional)

Url

user (optional)

User

user_agent (optional)

UserAgent

vulnerability (optional)

Vulnerability

EPMWinMac (optional)

Epmwinmac**EpmEcsEventResponseModel**

This class holds Epm Ecs Event response

totalRecordsReturned (optional)

Long Total records returned by query format: int64

events (optional)

array[EpmEcsEvent] List of events returned by query**Epmwinmac**

SchemaVersion (optional)

String

GroupId (optional)

String

TenantId (optional)

String

AuthorizationRequest (optional)

Authorizationrequest

AuthorizingUser (optional)

Authorizinguser

COM (optional)

Com

Configuration (optional)

Configuration

Event (optional)

Event

PrivilegedGroup (optional)

Privilegedgroup

Session (optional)

Session



Error

id (optional)

String

message (optional)

String

code (optional)

String

type (optional)

String

stack_trace (optional)

String



Event

Type (optional)

String

Action (optional)

String



FaaS

name (optional)

String

id (optional)

String

version (optional)

String

coldstart (optional)

Boolean

execution (optional)

String
trigger (optional)
FaaSTrigger



FaaSTrigger

type (optional)
String
request_id (optional)
String



File

name (optional)
String
attributes (optional)
array[String]
directory (optional)
String
drive_letter (optional)
String
path (optional)
String
target_path (optional)
String
extension (optional)
String
type (optional)
String
device (optional)
String
inode (optional)
String
uid (optional)
String
owner (optional)

String

gid (optional)

String

group (optional)

String

mode (optional)

String

size (optional)

Long format: int64

mtime (optional)

Date format: date-time

ctime (optional)

Date format: date-time

created (optional)

Date format: date-time

accessed (optional)

Date format: date-time

mime_type (optional)

String

fork_name (optional)

String

DriveType (optional)

String

SourceUrl (optional)

String

ZoneTag (optional)

String

hash (optional)

Hash

pe (optional)

Pe

x509 (optional)

X509

Bundle (optional)

Bundle

Owner (optional)

Owner

code_signature (optional)

CodeSignature

elf (optional)

Elf



location (optional)

GeoPoint

continent_code (optional)

String

continent_name (optional)

String

country_name (optional)

String

region_name (optional)

String

city_name (optional)

String

country_iso_code (optional)

String

postal_code (optional)

String

region_iso_code (optional)

String

timezone (optional)

String

name (optional)

String



lon (optional)

Double format: double

lat (optional)

Double format: double

 **Gpo**

Version (optional)

String

DisplayName (optional)

String

ActiveDirectoryPath (optional)

String

LinkInformation (optional)

String

 **Group**

id (optional)

String

name (optional)

String

domain (optional)

String

 **GroupDataAuditingDetailModel**

newName (optional)

String

oldName (optional)

String

newDescription (optional)

String

oldDescription (optional)

String

newsDefault (optional)

Boolean

oldsDefault (optional)

Boolean

addPolicyRevisions (optional)

map[String, String]
removePolicyRevisions (optional)
map[String, String]
newAgents (optional)
map[String, String]
removeAgents (optional)
map[String, String]



GroupListItemModel

locked (optional)

Boolean

errorInfo (optional)

ListItemErrorInfoModel

id (optional)

UUID The Id of the group(Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

name (optional)

String The name of the group

description (optional)

String The description of the group

computerCount (optional)

Integer The Computer count of the group format: int32

activeComputers (optional)

Integer Active Computers in the Group format: int32

created (optional)

Date The created date of resource e.g 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00

format: date-time

policyRevisionId (optional)

UUID format: uuid

policyId (optional)

UUID format: uuid

policyRevisionStatus (optional)

PolicyRevisionState

policyName (optional)

String

revision (optional)

Integer format: int32

default (optional)

Boolean



GroupListItemModelPagedResponse

pageNumber (optional)

Integer format: int32

pageSize (optional)

Integer format: int32

totalRecordCount (optional)

Integer format: int32

pageCount (optional)

Integer format: int32

data (optional)

array[GroupListItemModel]



Hash

md5 (optional)

String

sha1 (optional)

String

sha256 (optional)

String

sha384 (optional)

String

sha512 (optional)

String

ssdeep (optional)

String

t1sh (optional)

String

 **Host**

hostname (optional)

String

name (optional)

String

id (optional)

String

ip (optional)

array[String]

mac (optional)

String

type (optional)

String

uptime (optional)

Long format: int64

architecture (optional)

String

domain (optional)

String

cpu (optional)

HostCpu

disk (optional)

HostDisk

network (optional)

HostNetwork

boot (optional)

HostBoot

pid_ns_ino (optional)

String

DomainIdentifier (optional)

String

geo (optional)

Geo

os (optional)

Os

 **HostBoot**

id (optional)

String **HostCpu**

usage (optional)

Double format: double **HostDisk**

read (optional)

HostDiskRead

write (optional)

HostDiskWrite **HostDiskRead**

bytes (optional)

Long format: int64 **HostDiskWrite**

bytes (optional)

Long format: int64

**HostNetwork**

ingress (optional)

HostNetworkIngress

egress (optional)

HostNetworkEgress

**HostNetworkEgress**

bytes (optional)

Long format: int64

packets (optional)

Long format: int64

**HostNetworkIngress**

bytes (optional)

Long format: int64

packets (optional)

Long format: int64

**Http**

request (optional)

HttpRequest

response (optional)

HttpResponse

version (optional)

String



HttpRequest

id (optional)

String

method (optional)

String

mime_type (optional)

String

body (optional)

HttpRequestBody

referrer (optional)

String

bytes (optional)

Long format: int64



HttpRequestBody

content (optional)

String

bytes (optional)

Long format: int64



HttpResponse

status_code (optional)

Long format: int64

mime_type (optional)

String

body (optional)

HttpResponseBody

bytes (optional)

Long format: int64



HttpResponseBody

content (optional)

String

bytes (optional)

Long format: int64



InstallationKeyDataAuditingDetailModel

oldLabel (optional)

String

newLabel (optional)

String

newDisabled (optional)

Boolean

oldDisabled (optional)

Boolean

deleted (optional)

Boolean



ListItemErrorInfoModel

parentTaskName (optional)

String

errorCode (optional)

Integer format: int32

userId (optional)

UUID format: uuid

userAccountName (optional)

String

initiated (optional)

Date format: date-time

 **Log**

level (optional)

String

file (optional)

LogFile

logger (optional)

String

origin (optional)

LogOrigin

syslog (optional)

String

 **LogFile**

path (optional)

String


 **LogOrigin**

file (optional)

LogOriginFile

function (optional)

String

 **LogOriginFile**

name (optional)

String

line (optional)

Long format: int64

 **Message**

Type (optional)

String

Name (optional)

String

Description (optional)

String

UserReason (optional)

String

Identifier (optional)

String

Authorization (optional)

Authorization

 **ModifyAcceptedDomainRequest**

domain (optional)

String

 **ModifyGroupRequest**

id (optional)

UUID id of the group, for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

name (optional)

String name of the group, for example - Alianse Group

description (optional)

String description of the group, for example - Alianse Group desc

 **ModifyPolicyRequest**

name (optional)

String
description (optional)

String



ModifyUserPreferencesRequest

olsonTimeZoneld (optional)

String

dateTimeDisplayFormat (optional)

String

preferredLanguage (optional)

String



ModifyUserRequest

emailAddress (optional)

String

olsonTimeZoneld (optional)

String

dateTimeDisplayFormat (optional)

String

language (optional)

String



Network

name (optional)

String

type (optional)

String

iana_number (optional)

String

transport (optional)

String

application (optional)

String

protocol (optional)

String

direction (optional)

String

forwarded_ip (optional)

String

community_id (optional)

String

bytes (optional)

Long format: int64

packets (optional)

Long format: int64

inner (optional)

String

vlan (optional)

Vlan



enum

String

- Windows
- Mac



mac (optional)

String

ip (optional)

array[String]

hostname (optional)

String

name (optional)

String

product (optional)
String
vendor (optional)
String
version (optional)
String
serial_number (optional)
String
type (optional)
String
ingress (optional)
String
egress (optional)
String
geo (optional)
Geo
os (optional)
Os



OperationValue

Storing the values of the scim operation
value (optional)
String Generic string value location if no specific field is specified.
valueBoolean (optional)
Boolean Generic boolean value if no specific field is specified.
active (optional)
Boolean Active value of a user
timezone (optional)
String Timezone value of a user
locale (optional)
String Locale/language value of a user
email (optional)
String Email of a user
role (optional)
String Role of a user



Operator

enum

String

- EqualTo
- LessThan
- GreaterThan
- LessThanOrEqualTo
- GreaterThanOrEqualTo



Orchestrator

cluster (optional)

OrchestratorCluster

type (optional)

String

organization (optional)

String

namespace (optional)

String

resource (optional)

OrchestratorResource

api_version (optional)

String



OrchestratorCluster

name (optional)

String

id (optional)

String

url (optional)

String

version (optional)

String



OrchestratorResource

name (optional)

String

type (optional)

String

parent (optional)

OrchestratorResourceParent

ip (optional)

array[String]

id (optional)

String



OrchestratorResourceParent

type (optional)

String



Organization

name (optional)

String

id (optional)

String



Os

type (optional)

String

platform (optional)

String

name (optional)

String

full (optional)

String

family (optional)

String

version (optional)

String

kernel (optional)

String



Owner

Identifier (optional)

String

Name (optional)

String

DomainIdentifier (optional)

String

DomainName (optional)

String



Package

name (optional)

String

version (optional)

String

build_version (optional)

String

description (optional)

String

size (optional)

Long format: int64

installed (optional)
Date format: date-time
path (optional)
String
architecture (optional)
String
checksum (optional)
String
install_scope (optional)
String
license (optional)
String
reference (optional)
String
type (optional)
String



original_file_name (optional)
String
file_version (optional)
String
description (optional)
String
product (optional)
String
company (optional)
String
imphash (optional)
String
architecture (optional)
String
pehash (optional)
String



PolicyDataAudtingDetailModel

newName (optional)

String

oldName (optional)

String

newDescription (optional)

String

oldDescription (optional)

String



PolicyGroupsListItemModel

id (optional)

UUID format: uuid

name (optional)

String

description (optional)

String

policyRevisionId (optional)

UUID format: uuid

policyId (optional)

UUID format: uuid

isDefault (optional)

Boolean



PolicyListItemModel

id (optional)

UUID The Id (Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

locked (optional)

Boolean

errorInfo (optional)

ListItemErrorInfoModel

name (optional)

String

size (optional)

Integer format: int32

revision (optional)

Integer format: int32

totalRevisions (optional)

Integer format: int32

totalAssignedRevisions (optional)

Integer format: int32

latestAssignedRevisions (optional)

Integer format: int32

created (optional)

Date format: date-time

lastModified (optional)

Date format: date-time

lastModifiedUserId (optional)

UUID format: uuid

lastModifiedUser (optional)

String

hasOpenDraft (optional)

Boolean

openDraftId (optional)

UUID format: uuid

isAssignedToGroup (optional)

Boolean

draftUserId (optional)

UUID format: uuid

draftUser (optional)

String

lastPolicyToGroupAssignment (optional)

Date format: date-time

checkedOutDate (optional)

Date format: date-time

description (optional)

String

periodLocked (optional)

String



PolicyListItemModelPagedResponse

pageNumber (optional)

Integer format: int32

pageSize (optional)

Integer format: int32

totalRecordCount (optional)

Integer format: int32

pageCount (optional)

Integer format: int32

data (optional)

array[PolicyListItemModel]



PolicyRevisionDataAuditingDetailModel

newGroups (optional)

map[String, String]



PolicyRevisionModel

id (optional)

UUID format: uuid

created (optional)

Date format: date-time

revision (optional)

Integer format: int32

size (optional)

Integer format: int32

comment (optional)

String

user (optional)

String

isAssignedGroup (optional)

Boolean



PolicyRevisionState

enum

String

- OnLatestPolicy
- OnAnEarlierPolicy
- NoPolicy
- AwaitingLatestPolicy
- AwaitingAnEarlierPolicy



Privilegedgroup

Name (optional)

String

RID (optional)

String

Access (optional)

String



ProblemDetails

type

String

title

String

status

integer(\$int32)

detail

String

instance

String



Process

pid (optional)

Long format: int64

entity_id (optional)

String

name (optional)

String

pgid (optional)

Long format: int64

command_line (optional)

String

args (optional)

array[String]

args_count (optional)

Long format: int64

executable (optional)

String

title (optional)

String

thread (optional)

ProcessThread

start (optional)

Date format: date-time

uptime (optional)

Long format: int64

working_directory (optional)

String

exit_code (optional)

Long format: int64

end (optional)

Date format: date-time

interactive (optional)

Boolean

same_as_process (optional)

Boolean

env_vars (optional)

String

entry_meta (optional)

ProcessEntryMeta

tty (optional)

String

group (optional)

Group

real_group (optional)

Group

saved_group (optional)

Group

supplemental_groups (optional)

Group

hash (optional)

Hash

pe (optional)

Pe

code_signature (optional)

CodeSignature

elf (optional)

Elf

HostedFile (optional)

File

user (optional)

User

saved_user (optional)

User

real_user (optional)

User

parent (optional)

ProcessParent

entry_leader (optional)

ProcessEntryLeader

session_leader (optional)

ProcessSessionLeader

group_leader (optional)

ProcessGroupLeader

previous (optional)

ProcessPrevious



ProcessEntryLeader

pid (optional)

Long format: int64

entity_id (optional)

String

name (optional)

String

pgid (optional)

Long format: int64

command_line (optional)

String

args (optional)

array[String]

args_count (optional)

Long format: int64

executable (optional)

String

title (optional)

String

thread (optional)

ProcessThread

start (optional)

Date format: date-time

uptime (optional)

Long format: int64

working_directory (optional)

String

exit_code (optional)

Long format: int64

end (optional)

Date format: date-time

interactive (optional)

Boolean

same_as_process (optional)

Boolean

env_vars (optional)

String

entry_meta (optional)

ProcessEntryMeta

tty (optional)

String

group (optional)

Group

real_group (optional)

Group

saved_group (optional)

Group

supplemental_groups (optional)

Group

hash (optional)

Hash

pe (optional)

Pe

code_signature (optional)

CodeSignature

elf (optional)

Elf

HostedFile (optional)

File

user (optional)

User

saved_user (optional)

User

real_user (optional)

User

parent (optional)

ProcessParent**ProcessEntryMeta**

type (optional)

String

source (optional)

Source



ProcessGroupLeader

pid (optional)

Long format: int64

entity_id (optional)

String

name (optional)

String

pgid (optional)

Long format: int64

command_line (optional)

String

args (optional)

array[String]

args_count (optional)

Long format: int64

executable (optional)

String

title (optional)

String

thread (optional)

ProcessThread

start (optional)

Date format: date-time

uptime (optional)

Long format: int64

working_directory (optional)

String

exit_code (optional)

Long format: int64

end (optional)

Date format: date-time

interactive (optional)

Boolean

same_as_process (optional)

Boolean

env_vars (optional)

String

entry_meta (optional)

ProcessEntryMeta

tty (optional)

String

group (optional)

Group

real_group (optional)

Group

saved_group (optional)

Group

supplemental_groups (optional)

Group

hash (optional)

Hash

pe (optional)

Pe

code_signature (optional)

CodeSignature

elf (optional)

Elf

HostedFile (optional)

File

user (optional)

User

saved_user (optional)

User

real_user (optional)

User**ProcessParent**

pid (optional)

Long format: int64

entity_id (optional)

String

name (optional)

String

pgid (optional)

Long format: int64

command_line (optional)

String

args (optional)

array[String]

args_count (optional)

Long format: int64

executable (optional)

String

title (optional)

String

thread (optional)

ProcessThread

start (optional)

Date format: date-time

uptime (optional)

Long format: int64

working_directory (optional)

String

exit_code (optional)

Long format: int64

end (optional)

Date format: date-time

interactive (optional)

Boolean

same_as_process (optional)

Boolean

env_vars (optional)

String

entry_meta (optional)

ProcessEntryMeta

tty (optional)

String

group (optional)

Group

real_group (optional)

Group

saved_group (optional)

Group

supplemental_groups (optional)

Group

hash (optional)
Hash
pe (optional)
Pe
code_signature (optional)
CodeSignature
elf (optional)
Elf
HostedFile (optional)
File
user (optional)
User
saved_user (optional)
User
real_user (optional)
User
group_leader (optional)
ProcessGroupLeader



ProcessPrevious

pid (optional)
Long format: int64
entity_id (optional)
String
name (optional)
String
pgid (optional)
Long format: int64
command_line (optional)
String
args (optional)
array[String]
args_count (optional)
Long format: int64
executable (optional)
String
title (optional)

String

thread (optional)

ProcessThread

start (optional)

Date format: date-time

uptime (optional)

Long format: int64

working_directory (optional)

String

exit_code (optional)

Long format: int64

end (optional)

Date format: date-time

interactive (optional)

Boolean

same_as_process (optional)

Boolean

env_vars (optional)

String

entry_meta (optional)

ProcessEntryMeta

tty (optional)

String

group (optional)

Group

real_group (optional)

Group

saved_group (optional)

Group

supplemental_groups (optional)

Group

hash (optional)

Hash

pe (optional)

Pe

code_signature (optional)

CodeSignature

elf (optional)

Elf

HostedFile (optional)

File

user (optional)

User

saved_user (optional)

User

real_user (optional)

User**ProcessSessionLeader**

pid (optional)

Long format: int64

entity_id (optional)

String

name (optional)

String

pgid (optional)

Long format: int64

command_line (optional)

String

args (optional)

array[String]

args_count (optional)

Long format: int64

executable (optional)

String

title (optional)

String

thread (optional)

ProcessThread

start (optional)

Date format: date-time

uptime (optional)

Long format: int64

working_directory (optional)

String

exit_code (optional)

Long format: int64

end (optional)
Date format: date-time
interactive (optional)
Boolean
same_as_process (optional)
Boolean
env_vars (optional)
String
entry_meta (optional)
ProcessEntryMeta
tty (optional)
String
group (optional)
Group
real_group (optional)
Group
saved_group (optional)
Group
supplemental_groups (optional)
Group
hash (optional)
Hash
pe (optional)
Pe
code_signature (optional)
CodeSignature
elf (optional)
Elf
HostedFile (optional)
File
user (optional)
User
saved_user (optional)
User
real_user (optional)
User
parent (optional)
ProcessParent



ProcessThread

id (optional)

Long format: int64

name (optional)

String



Registry

hive (optional)

String

key (optional)

String

value (optional)

String

path (optional)

String

data (optional)

RegistryData



RegistryData

type (optional)

String

strings (optional)

array[String]

bytes (optional)

String



Related

ip (optional)

array[String]

user (optional)

array[String]

hash (optional)

array[String]

hosts (optional)

array[String]



RoleElement

role object

primary (optional)

Boolean booleana flag for whether or not this is the primary role

value (optional)

String User role value



RoleItemModel

Model of role list item

id (optional)

UUID Identifier format: uuid

name (optional)

String Name

resourceId (optional)

String

resourceType (optional)

String



RoleListItemModel

id (optional)

UUID format: uuid

name (optional)

String

allowPermissions (optional)
array[RolePermissionModel]
denyPermissions (optional)
array[RolePermissionModel] deprecated. rbac only support allow permissions

RoleModel

id (optional)
UUID format: uuid
name (optional)
String
allowPermissions (optional)
array[RolePermissionModel]
denyPermissions (optional)
array[RolePermissionModel] deprecated. rbac only support allow permissions

RolePermissionModel

resource (optional)
String
action (optional)
String

Rule

Identifier (optional)
String
OnDemand (optional)
Boolean
Action (optional)
String

 **Rulescript**

FileName (optional)


String

Publisher (optional)

String

Outcome (optional)

RulescriptOutcome

 **RulescriptOutcome**

Version (optional)

String

Name (optional)

String

RuleAffected (optional)

Boolean

Result (optional)

String

Output (optional)

String

 **SCIMEmail**

primary (optional)

Boolean

value (optional)

String

type (optional)

String

**SCIMUserName**

givenName (optional)

String

familyName (optional)

String

middleName (optional)

String

**ScimAuthenticationSchemes**

authentication schemes for scim

name (optional)

String name of authentication

description (optional)

String description of authentication

type (optional)

String type of authentication

primary (optional)

Boolean flag for whether or not the authentication scheme is the primary

**ScimBulk**

flag to see if scim bulk operations is supported

maxOperations (optional)

Integer max operations format: int32

maxPayloadSize (optional)

Integer max payload size format: int32

supported (optional)

Boolean flag for bulk operations



ScimOperation

SCIM Operations going to be performed on a user
op (optional)

String Operation to be performed on a user. add or replace
path (optional)

String Which field the operation should affect. optional
value (optional)

array[OperationValue] Values of the fields going that are going to be changed



ScimResourceMeta

resource type meta data
resourceType (optional)

String resource type meta data



ScimResourceResponse

Json structure for resource type response
schemas (optional)

array[String] schema

name (optional)

String name of resource type

description (optional)

String description of resource type

endpoint (optional)

String endpoint

schema (optional)

String schema

meta (optional)

ScimResourceMeta



ScimResourceResponseScimListResponse

schemas (optional)

array[String]

totalResults (optional)

Integer format: int32

startIndex (optional)

Integer format: int32

itemsPerPage (optional)

Integer format: int32

Resources (optional)

array[ScimResourceResponse]



ScimSchemaResponse

Structure of the schema response

schemas (optional)

array[String] schema

id (optional)

String id of schema

name (optional)

String name of schema

description (optional)

String description of schema

attributes (optional)

array[Attribute] available attributes

meta (optional)

ScimResourceMeta



ScimSchemaResponseScimListResponse

schemas (optional)

array[String]

totalResults (optional)

Integer format: int32

startIndex (optional)
Integer format: int32
itemsPerPage (optional)
Integer format: int32
Resources (optional)
array[ScimSchemaResponse]



ScimServiceProviderConfigResponse

schemas (optional)
array[String] service provider config schema
patch (optional)
ScimSupported
bulk (optional)
ScimBulk
filter (optional)
ScimSupported
changePassword (optional)
ScimSupported
sort (optional)
ScimSupported
etag (optional)
ScimSupported
authenticationSchemes (optional)
ScimAuthenticationSchemes
meta (optional)
ScimResourceMeta



ScimSupported

Flag to see if scim feature if supported
supported (optional)
Boolean flag to see if scim feature is supported



ScimUserMetaModel

resourceType (optional)

String

created (optional)

Date format: date-time



ScimUserModel

schemas (optional)

array[String]

id (optional)

UUID format: uuid

userName (optional)

String

name (optional)

SCIMUserName

emails (optional)

array[SCIMEmail]

displayName (optional)

String

locale (optional)

String

timezone (optional)

String

externalId (optional)

String

dateTimeFormat (optional)

String

groups (optional)

array[null]

password (optional)

String

active (optional)

Boolean boolean flag of whether or not a user is active

roles (optional)

array[RoleElement] A complex role object for scim

meta (optional)

ScimUserMetaModel



ScimUserModelScimListResponse

schemas (optional)

array[String]

totalResults (optional)

Integer format: int32

startIndex (optional)

Integer format: int32

itemsPerPage (optional)

Integer format: int32

Resources (optional)

array[ScimUserModel]



ScimUserPatchRequest

Patch request used to update a user through SCIM

schemas (optional)

array[String] Schema of the request, should be urn:ietf:params:scim:api:messages:2.0:PatchOp

operations (optional)

array[ScimOperation] SCIM Operations going to be performed on a user



Server

address (optional)

String

ip (optional)

String

port (optional)

Long format: int64

mac (optional)

String

domain (optional)
String
registered_domain (optional)
String
top_level_domain (optional)
String
subdomain (optional)
String
bytes (optional)
Long format: int64
packets (optional)
Long format: int64
nat (optional)
ServerNat
as (optional)
As
geo (optional)
Geo
user (optional)
User



ServerNat

ip (optional)
String
port (optional)
Long format: int64



Service

environment (optional)
String
id (optional)
String
name (optional)
String

node (optional)
ServiceNode
type (optional)
String
state (optional)
String
version (optional)
String
ephemeral_id (optional)
String
address (optional)
String
origin (optional)
ServiceOrigin
target (optional)
ServiceTarget



ServiceNode

name (optional)
String
role (optional)
String



ServiceOrigin

environment (optional)
String
id (optional)
String
name (optional)
String
node (optional)
ServiceNode
type (optional)
String

state (optional)

String

version (optional)

String

ephemeral_id (optional)

String

address (optional)

String



ServiceTarget

environment (optional)

String

id (optional)

String

name (optional)

String

node (optional)

ServiceNode

type (optional)

String

state (optional)

String

version (optional)

String

ephemeral_id (optional)

String

address (optional)

String



Session

Administrator (optional)

Boolean

Locale (optional)

String

Identifier (optional)

String

PowerUser (optional)

Boolean

WindowsSessionId (optional)

String

UILanguage (optional)

String



SettingDataAuditingDetailModel

addDomain (optional)

String

removeDomain (optional)

String

modifyDomainOldValue (optional)

String

modifyDomainNewValue (optional)

String



SortDirection

enum

String

- Asc
- Desc



SortModel

by (optional)

String The property on which to sort e.g. name

order (optional)

SortDirection



Source

address (optional)

String

ip (optional)

String

port (optional)

Long format: int64

mac (optional)

String

domain (optional)

String

registered_domain (optional)

String

top_level_domain (optional)

String

subdomain (optional)

String

bytes (optional)

Long format: int64

packets (optional)

Long format: int64

nat (optional)

SourceNat

as (optional)

As

geo (optional)

Geo

user (optional)

User



SourceNat

ip (optional)

String

port (optional)

Long format: int64



SubAttribute

Schema for subattributes

name (optional)

String name of attribute

description (optional)

String description of attribute

type (optional)

String type of attribute

canonicalValues (optional)

array[String] list of canonical values

caseExact (optional)

Boolean Flag for whether or not the attribute's casing should be exact

multiValued (optional)

Boolean Flag for whether or not the attribute has multi values

mutability (optional)

String Mutability of the attribute

required (optional)

Boolean Flag for whether or not the attribute is required

returned (optional)

String how the attribute is returned

uniqueness (optional)

String Is the value unique



TaskDetailModel

id (optional)

UUID format: uuid

tenantId (optional)

UUID format: uuid

name (optional)

String

state (optional)

Integer format: int32

stateName (optional)

String

initiated (optional)

Date format: date-time
completed (optional)
Date format: date-time
userId (optional)
UUID format: uuid
user (optional)
String
completedWithErrors (optional)
Boolean
messageParameters (optional)
array[map[String, String]]

Threat

enrichments (optional)
array[ThreatEnrichments]
feed (optional)
ThreatFeed
framework (optional)
String
group (optional)
ThreatGroup
indicator (optional)
ThreatIndicator
software (optional)
ThreatSoftware
tactic (optional)
ThreatTactic
technique (optional)
ThreatTechnique

ThreatEnrichments

indicator (optional)
String
matched (optional)

ThreatEnrichmentsMatched**ThreatEnrichmentsMatched**

atomic (optional)

String

field (optional)

String

id (optional)

String

index (optional)

String

occurred (optional)

Date format: date-time

type (optional)

String**ThreatFeed**

dashboard_id (optional)

String

name (optional)

String

description (optional)

String

reference (optional)

String**ThreatGroup**

alias (optional)

array[String]

id (optional)

String

name (optional)
String
reference (optional)
String



ThreatIndicator

first_seen (optional)
Date format: date-time
last_seen (optional)
Date format: date-time
modified_at (optional)
Date format: date-time
sightings (optional)
Long format: int64
type (optional)
String
description (optional)
String
scanner_stats (optional)
Long format: int64
confidence (optional)
String
ip (optional)
String
port (optional)
Long format: int64
email (optional)
ThreatIndicatorEmail
marking (optional)
ThreatIndicatorMarking
reference (optional)
String
provider (optional)
String
x509 (optional)
X509
as (optional)

As

file (optional)

File

geo (optional)

Geo

registry (optional)

Registry

url (optional)

Url**ThreatIndicatorEmail**

address (optional)

String**ThreatIndicatorMarking**

tip (optional)

String**ThreatSoftware**

id (optional)

String

name (optional)

String

alias (optional)

array[String]

platforms (optional)

array[String]

reference (optional)

String

type (optional)

String



ThreatTactic

id (optional)

array[String]

name (optional)

array[String]

reference (optional)

array[String]



ThreatTechnique

id (optional)

array[String]

name (optional)

array[String]

reference (optional)

array[String]

subtechnique (optional)

ThreatTechniqueSubtechnique



ThreatTechniqueSubtechnique

id (optional)

array[String]

name (optional)

array[String]

reference (optional)

array[String]



Tls

version (optional)

String
version_protocol (optional)

String
cipher (optional)

String
curve (optional)

String
resumed (optional)

Boolean
established (optional)

Boolean
next_protocol (optional)

String
client (optional)

TlsClient
server (optional)

TlsServer



TlsClient

ja3 (optional)

String
server_name (optional)

String
supported_ciphers (optional)

array[String]
subject (optional)

String
issuer (optional)

String
not_before (optional)

Date format: date-time
not_after (optional)

Date format: date-time
certificate_chain (optional)

array[String]
certificate (optional)

String

hash (optional)

TlsClientHash

x509 (optional)

X509



TlsClientHash

md5 (optional)

String

sha1 (optional)

String

sha256 (optional)

String



TlsServer

ja3s (optional)

String

subject (optional)

String

issuer (optional)

String

not_before (optional)

Date format: date-time

not_after (optional)

Date format: date-time

certificate_chain (optional)

array[String]

certificate (optional)

String

hash (optional)

TlsServerHash

x509 (optional)

X509

**TlsServerHash**

md5 (optional)

String

sha1 (optional)

String

sha256 (optional)

String**Token**

Name (optional)

String

Description (optional)

String

Identifier (optional)

String**Tracing**

trace (optional)

TracingTrace

transaction (optional)

TracingTransaction

span (optional)

TracingSpan**TracingSpan**

id (optional)

String

**TracingTrace**

id (optional)

String**TracingTransaction**

id (optional)

String**UnassignComputersToGroupRequest**

allComputers (optional)

Boolean

filter (optional)

ComputerFilterModel

excludedComputerIds (optional)

array[UUID] format: uuid

selectionComputerIds (optional)

array[UUID] selection computers ids will work when "allComputers" : false format: uuid**Url**

original (optional)

String

full (optional)

String

scheme (optional)

String

domain (optional)

String

registered_domain (optional)

String
top_level_domain (optional)

String
subdomain (optional)

String
port (optional)

Long format: int64
path (optional)

String
query (optional)

String
extension (optional)

String
fragment (optional)

String
username (optional)

String
password (optional)

String



id (optional)

String
name (optional)

String
full_name (optional)

String
email (optional)

String
hash (optional)

String
domain (optional)

String
roles (optional)

array[String]
DomainIdentifier (optional)

String

group (optional)

Group

target (optional)

UserTarget

effective (optional)

UserEffective

changes (optional)

UserChanges**UserAgent**

original (optional)

String

name (optional)

String

version (optional)

String

device (optional)

UserAgentDevice

os (optional)

Os**UserAgentDevice**

name (optional)

String**UserChanges**

id (optional)

String

name (optional)

String

full_name (optional)

String

email (optional)

String

hash (optional)

String

domain (optional)

String

roles (optional)

array[String]

DomainIdentifier (optional)

String

group (optional)

Group**UserDataAuditing**

Activity Audit User Data

newEmailAddress (optional)

String New Email Address

oldEmailAddress (optional)

String Old Email Address

newOlsonTimeZoneId (optional)

String New Timezone

oldOlsonTimeZoneId (optional)

String Old Timezone

newDateTimeDisplayFormat (optional)

String New Datetime Display Format

oldDateTimeDisplayFormat (optional)

String Old Datetime Display Format

newPreferredLanguage (optional)

String New Preferred Language

oldPreferredLanguage (optional)

String Old Preferred Language

newDisabled (optional)

Boolean New Disabled

oldDisabled (optional)

Boolean Old Disabled

newUserType (optional)

String new user type
oldUserType (optional)
String old user type
roles (optional)
array[ActivityAuditRoleResourceModel] Role audit data



UserDetailModel

id (optional)
UUID format: uuid
accountName (optional)
String
emailAddress (optional)
String
created (optional)
Date format: date-time
isFirstSignIn (optional)
Boolean
lastSignedIn (optional)
Date format: date-time
disabled (optional)
Boolean
roles (optional)
array[UserRoleResourceItemModel]
olsonTimeZoneld (optional)
String
dateTimeDisplayFormat (optional)
String
language (optional)
String
allowInvites (optional)
Boolean



UserEffective

id (optional)

String
name (optional)

String
full_name (optional)

String
email (optional)

String
hash (optional)

String
domain (optional)

String
roles (optional)

array[String]
DomainIdentifier (optional)

String
group (optional)

Group



UserListItemModel

Model of user list item

locked (optional)

Boolean
errorInfo (optional)

ListItemErrorInfoModel
id (optional)

UUID User identifier format: uuid

accountName (optional)

String Account name

emailAddress (optional)

String Email

created (optional)

Date Creation date format: date-time

lastSignedIn (optional)

Date Last logged in date format: date-time

disabled (optional)

Boolean Is user disabled

roles (optional)

array[RoleItemModel] List of user roles

roleName (optional)

String Role name

olsonTimeZoneld (optional)

String Time zone

dateTimeDisplayFormat (optional)

String Date and time display format

language (optional)

String Preferred language



UserListItemModelPagedResponse

pageNumber (optional)

Integer format: int32

pageSize (optional)

Integer format: int32

totalRecordCount (optional)

Integer format: int32

pageCount (optional)

Integer format: int32

data (optional)

array[UserListItemModel]



UserRoleResourceItemModel

id (optional)

UUID format: uuid

name (optional)

String

allowPermissions (optional)

array[RolePermissionModel]

denyPermissions (optional)

array[RolePermissionModel] deprecated. rbac only support allow permissions

resourceId (optional)

String

resourceType (optional)

String

UserTarget

id (optional)

String

name (optional)

String

full_name (optional)

String

email (optional)

String

hash (optional)

String

domain (optional)

String

roles (optional)

array[String]

DomainIdentifier (optional)

String

group (optional)

Group

Vlan

id (optional)

String

name (optional)

String

Vulnerability

classification (optional)

String

enumeration (optional)

String

reference (optional)

String

score (optional)

VulnerabilityScore

category (optional)

array[String]

description (optional)

String

id (optional)

String

scanner (optional)

VulnerabilityScanner

severity (optional)

String

report_id (optional)

String



VulnerabilityScanner

vendor (optional)

String



VulnerabilityScore

base (optional)

Double format: double

temporal (optional)

Double format: double

environmental (optional)

Double format: double

version (optional)

String

 **Workstyle**

Name (optional)

String

Description (optional)

String

Identifier (optional)

String

 **x509**

version_number (optional)

String

serial_number (optional)

String

issuer (optional)

X509Issuer

signature_algorithm (optional)

String

not_before (optional)

Date format: date-time

not_after (optional)

Date format: date-time

subject (optional)

X509Subject

public_key_algorithm (optional)

String

public_key_size (optional)

Long format: int64

public_key_exponent (optional)

Long format: int64

public_key_curve (optional)

String

alternative_names (optional)

array[String]

**X509Issuer**

distinguished_name (optional)

String

common_name (optional)

array[String]

organizational_unit (optional)

array[String]

organization (optional)

array[String]

locality (optional)

array[String]

state_or_province (optional)

array[String]

country (optional)

array[String]

**X509Subject**

distinguished_name (optional)

String

common_name (optional)

array[String]

organizational_unit (optional)

array[String]

organization (optional)

array[String]

locality (optional)

array[String]

state_or_province (optional)

array[String]

country (optional)

array[String]

 `_event`

id (optional)

String

code (optional)

String

kind (optional)

String

category (optional)

array[String]

action (optional)

String

outcome (optional)

String

type (optional)

array[String]

module (optional)

String

dataset (optional)

String

provider (optional)

String

severity (optional)

Long format: int64

original (optional)

String

hash (optional)

String

duration (optional)

Long format: int64

sequence (optional)

Long format: int64

timezone (optional)

String

created (optional)

Date format: date-time

start (optional)

Date format: date-time

end (optional)

Date format: date-time
risk_score (optional)
Double format: double
risk_score_norm (optional)
Double format: double
ingested (optional)
Date format: date-time
reference (optional)
String
url (optional)
String
reason (optional)
String
agent_id_status (optional)
String



id (optional)
String
uuid (optional)
String
version (optional)
String
name (optional)
String
description (optional)
String
category (optional)
String
ruleset (optional)
String
reference (optional)
String
author (optional)
array[String]
license (optional)
String

`id_AssignComputersByCsv_body`

csvFile (optional)

byte[] format: binary