



BeyondTrust

Privilege Management Cloud 22.9 API Guide - Version 1

Table of Contents

Privilege Management Cloud API - Version 1	11
Authenticate to the PM Cloud API	11
Methods	13
AcceptedDomains	15
ActivityAudits	21
AuthorizationRequestAudits	29
Computers	33
Events	49
File	95
Groups	96
Policies	110
Roles	120
ScimResourceTypes	123
ScimSchemas	125
ScimServiceProviderConfig	129
ScimUsers	130
Tasks	138
Users	139
Models	152
AcceptedDomainDetailModel	158
AcceptedDomainListItemModel	159
Activex	159
ActivityAuditDetailModel	159
ActivityAuditDetailModelPagedResponse	160
ActivityAuditListItemModel	161
ActivityAuditListItemModelPagedResponse	161
ActivityAuditRoleNameModel	162
ActivityAuditRoleResourceModel	162
Agent	162
AgentBuild	163
AgentHostType	163

ApiClientDataAuditingDetailModel	163
Application	164
Applicationgroup	164
As	164
AsOrganization	164
AssignComputersToGroupRequest	165
AssignPolicyRevisionToGroupRequest	165
AssignUserToRoleRequest	165
Attribute	165
Authentication	166
Authorization	166
AuthorizationRequestAuditDetailModel	166
AuthorizationRequestAuditDetailModelPagedResponse	167
AuthorizationRequestAuditListItemModel	167
AuthorizationRequestAuditListItemModelPagedResponse	168
Authorizationrequest	169
Authorizinguser	169
Bundle	169
CertificateInformationModel	170
ChangedBy	170
Client	170
ClientNat	171
Cloud	171
CloudAccount	172
CloudInstance	172
CloudMachine	172
CloudOrigin	173
CloudProject	173
CloudService	173
CloudTarget	174
CodeSignature	174
Com	175
ComputerDataAuditingDetailModel	175

ComputerDetailModel	175
ComputerFilterModel	177
ComputerListItemModel	178
ComputerListItemModelPagedResponse	179
ComputerLogModel	179
ComputerRenewCertificateRequest	180
ComputerRetrieveLogsRequest	180
ComputerRetrieveStatusInfoRequest	180
ComputersAuthoriseRequest	180
ComputersDeactivateRequest	181
ComputersRejectRequest	181
ComputersRemoveRequest	181
Configuration	182
Container	183
ContainerCpu	183
ContainerDisk	183
ContainerDiskRead	184
ContainerDiskWrite	184
ContainerImage	184
ContainerImageHash	184
ContainerMemory	185
ContainerNetwork	185
ContainerNetworkEgress	185
ContainerNetworkIngress	185
Content	185
Contentgroup	186
CountRange	186
CreateAcceptedDomainRequest	186
CreateGroupRequest	186
CreateUserRequest	187
DataStream	187
DateFilterModel	187
DateSelectionMode	188

Destination	188
DestinationNat	189
Dll	189
Dns	189
DnsQuestion	190
Ecs	190
Elf	190
ElfHeader	191
ElfSections	192
ElfSegments	192
Email	192
EmailAttachments	193
EmailAttachmentsFile	193
EmailBcc	194
EmailCc	194
EmailFrom	194
EmailReplyTo	194
EmailSender	195
EmailTo	195
EndpointInformationModel	195
EpmEcsEvent	196
EpmEcsEventResponseModel	199
EpmEcsEventSpan	199
EpmEcsEventTrace	199
EpmEcsEventTransaction	199
Epmwinmac	199
Error	200
Event	201
FaaS	201
FaaSTrigger	201
File	202
Geo	204
GeoPoint	204

Gpo	205
Group	205
GroupDataAuditingDetailModel	205
GroupListItemModel	206
GroupListItemModelPagedResponse	207
Hash	207
Host	208
HostBoot	209
HostCpu	209
HostDisk	209
HostDiskRead	209
HostDiskWrite	210
HostNetwork	210
HostNetworkEgress	210
HostNetworkIngress	210
Http	210
HttpRequest	211
HttpRequestBody	211
HttpResponse	211
HttpResponseBody	212
InstallationKeyDataAuditingDetailModel	212
Installer	212
ListItemErrorInfoModel	213
Log	213
LogFile	213
LogOrigin	214
LogOriginFile	214
Message	214
ModifyAcceptedDomainRequest	215
ModifyGroupRequest	215
ModifyPolicyRequest	215
ModifyUserPreferencesRequest	215
ModifyUserRequest	216

Network	216
OS	217
Observer	217
OperationValue	218
Operator	218
Orchestrator	219
OrchestratorCluster	219
OrchestratorResource	219
OrchestratorResourceParent	220
Organization	220
Os	220
Owner	221
Package	221
Pe	222
PolicyDataAuditingDetailModel	222
PolicyGroupsListItemModel	223
PolicyListItemModel	223
PolicyListItemModelPagedResponse	224
PolicyRevisionDataAuditingDetailModel	225
PolicyRevisionModel	225
PolicyRevisionState	225
Privilegedgroup	226
ProblemDetails	226
Process	226
ProcessEntryLeader	228
ProcessEntryMeta	230
ProcessGroupLeader	230
ProcessParent	232
ProcessPrevious	234
ProcessSessionLeader	236
ProcessThread	238
Registry	238
RegistryData	238

Related	238
Remotepowershell	239
RoleElement	239
RoleItemModel	239
RoleListItemModel	240
RoleModel	240
RolePermissionModel	240
Rule	240
Rulescript	241
RulescriptOutcome	241
SCIMEmail	241
SCIMUserName	242
ScimAuthenticationSchemes	242
ScimBulk	242
ScimOperation	243
ScimResourceMeta	243
ScimResourceResponse	243
ScimResourceResponseScimListResponse	244
ScimSchemaResponse	244
ScimSchemaResponseScimListResponse	244
ScimServiceProviderConfigResponse	245
ScimSupported	245
ScimUserMetaModel	246
ScimUserModel	246
ScimUserModelScimListResponse	247
ScimUserPatchRequest	247
Server	247
ServerNat	248
Service	248
ServiceNode	249
ServiceOrigin	249
ServiceTarget	250
Servicecontrol	250

ServicecontrolService	251
Session	251
SettingDataAuditingDetailModel	251
SortDirection	252
SortModel	252
Source	252
SourceNat	253
Storeapp	253
SubAttribute	253
TaskDetailModel	254
Threat	255
ThreatEnrichments	255
ThreatEnrichmentsMatched	255
ThreatFeed	256
ThreatGroup	256
ThreatIndicator	256
ThreatIndicatorEmail	258
ThreatIndicatorMarking	258
ThreatSoftware	258
ThreatTactic	258
ThreatTechnique	259
ThreatTechniqueSubtechnique	259
Tls	259
TlsClient	260
TlsClientHash	261
TlsServer	261
TlsServerHash	261
Token	262
Trustedapplication	262
UnassignComputersToGroupRequest	262
Url	263
User	263
UserAgent	264


UserAgentDevice	265
UserChanges	265
UserDataAuditing	266
UserDetailModel	267
UserEffective	267
UserListItemModel	268
UserListItemModelPagedResponse	269
UserRoleResourceItemModel	269
UserTarget	270
Vlan	271
Vulnerability	271
VulnerabilityScanner	271
VulnerabilityScore	272
Workstyle	272
X509	272
X509Issuer	273
X509Subject	273
_event	274
_rule	275
id_AssignComputersByCsv_body	276

Privilege Management Cloud API - Version 1

Authenticate to the PM Cloud API

API requests are executed by sending an HTTP request to PM Cloud. Send the request using any HTTPS-capable socket library or scripting language module, URL fetcher such as cURL, or an OAuth library specific to your platform. BeyondTrust's web APIs use OAuth as the authentication method.

To authenticate to the API, you must create an API account on the **Configuration > Settings > API Settings** page. The account must have permission to access the necessary APIs. API requests require a token to be first created and then submitted with each API request.

 For more information about creating an API account, please see [Configure Access to the Management API](#) in the *Privilege Management Cloud Administration Guide*.

Create a Token

Create a token by POSTing to the URL of your BeyondTrust site followed by `/oauth/connect/token`:

```
https://example-services.pm.beyondtrustcloud.com/oauth/connect/token
```

Replace "example" with your production sub-domain name, as shown:


```
https://[yourProductionSub-domainName]-services.pm.beyondtrustcloud.com/oauth/connect/token
```

The OAuth client ID and client secret associated with the API account should be included in the POST body:

```
grant_type=client_credentials&client_id=[yourClientId]&client_secret=[yourGeneratedClientSecret]
```

If the request is processed without error, you will get an access token JSON response:

```
{
  "access_token": "<token>",
  "token_type": "Bearer",
  "expires_in": 3600,
  "scope": "urn:management:api"
}
```

 **Note:** The client secret cannot be modified, but it can be regenerated on the **Configuration > Settings > API Settings** page. Regenerating a client secret and then saving the account immediately invalidates any OAuth tokens associated with the account. Any API calls using those tokens will be unable to access the API. A new token must be generated using the new client secret.

Request an API Resource

Now that you have an access token, you can make GET/POST requests via HTTPS to the web API:

```
https://example-services.pm.beyondtrustcloud.com/management-api/v1/Groups
```

The obtained token is used for HTTP authentication and must be included in an HTTP authorization header with each request:

```
Authorization: Bearer <token>
```

If the token is valid, you gain access to the requested URL.

Authentication Errors

Requests made to the web API with expired or invalid tokens result in a "HTTP 401 Unauthorized" response.

Methods

[[Jump to Models](#)]

Table of Contents

AcceptedDomains

- [get /v1/AcceptedDomains](#)
- [delete /v1/AcceptedDomains/{id}](#)
- [get /v1/AcceptedDomains/{id}](#)
- [put /v1/AcceptedDomains/{id}](#)
- [post /v1/AcceptedDomains](#)

ActivityAudits

- [get /v1/ActivityAudits](#)
- [get /v1/ActivityAudits/{id}](#)

AuthorizationRequestAudits

- [get /v1/AuthorizationRequestAudits](#)
- [get /v1/AuthorizationRequestAudits/{id}](#)

Computers

- [post /v1/Computers/Authorise](#)
- [post /v1/Computers/Certificate/Renew](#)
- [post /v1/Computers/Deactivate](#)
- [delete /v1/Computers](#)
- [post /v1/Computers/Details/Request](#)
- [get /v1/Computers](#)
- [get /v1/Computers/{id}/CommandLog](#)
- [get /v1/Computers/{id}](#)
- [get /v1/Computers/{id}/Logs](#)
- [get /v1/Computers/Logs/{id}/Content](#)
- [post /v1/Computers/Logs/Request](#)
- [post /v1/Computers/Reject](#)

Events

- [get /v1/Events/FromStartDate](#)

File

- [get /v1/File/download/GetYamlApiDefinitionFile](#)

Groups

- [post /v1/Groups/AutoAssignPolicyRevision](#)
- [get /v1/Groups](#)
- [post /v1/Groups/{id}/AssignComputersByCsv](#)
- [post /v1/Groups/{id}/AssignComputers](#)
- [post /v1/Groups/{id}/AssignPolicyRevision](#)
- [patch /v1/Groups/{id}/ClearPolicy](#)
- [delete /v1/Groups/{id}](#)
- [get /v1/Groups/{id}](#)
- [patch /v1/Groups/{id}/MarkAsDefault](#)
- [post /v1/Groups](#)
- [put /v1/Groups](#)
- [post /v1/Groups/UnassignComputers](#)

Policies

- [get /v1/Policies](#)
- [get /v1/Policies/{id}/AssignedGroups](#)
- [get /v1/Policies/{id}/Content](#)
- [delete /v1/Policies/{id}](#)
- [patch /v1/Policies/{id}/DiscardDraft](#)
- [get /v1/Policies/{id}](#)
- [put /v1/Policies/{id}](#)
- [get /v1/Policies/{id}/Revisions](#)
- [get /v1/Policies/PolicyRevision/{policyRevisionId}/Content](#)

Roles

- [get /v1/Roles](#)
- [get /v1/Roles/{id}](#)

ScimResourceTypes

- [get /scim/v2/ResourceTypes](#)
- [get /scim/v2/ResourceTypes/User](#)

ScimSchemas

- [get /scim/v2/Schemas](#)

ScimServiceProviderConfig

- [get /scim/v2/ServiceProviderConfig](#)

ScimUsers

- [get /scim/v2/Users](#)
- [post /scim/v2/Users](#)
- [get /scim/v2/Users/{userID}](#)
- [patch /scim/v2/Users/{userID}](#)
- [put /scim/v2/Users/{userID}](#)

Tasks

- [get /v1/Tasks/{id}](#)

Users

- [get /v1/Users](#)
- [post /v1/Users/{id}/AssignRole](#)
- [patch /v1/Users/{id}/Disable](#)
- [patch /v1/Users/{id}/Enable](#)
- [get /v1/Users/{id}](#)
- [put /v1/Users/{id}/ModifyUserPreferences](#)
- [put /v1/Users/{id}](#)
- [patch /v1/Users/{id}/ResendInvite](#)
- [post /v1/Users](#)

AcceptedDomains

`get /v1/AcceptedDomains`

Retrieves list of Accepted Domains (v1AcceptedDomainsGet)

Return type

array[[AcceptedDomainListItemModel](#)]

Example data

Content-Type: application/json

```
[ {
  "created" : "2000-01-23T04:56:07.000+00:00",
  "domain" : "domain",
  "errorInfo" : {
    "userAccountName" : "userAccountName",
    "parentTaskName" : "parentTaskName",
    "initiated" : "2000-01-23T04:56:07.000+00:00",
    "errorCode" : 0,
    "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
  },
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "locked" : true
}, {
  "created" : "2000-01-23T04:56:07.000+00:00",
  "domain" : "domain",
  "errorInfo" : {
    "userAccountName" : "userAccountName",
    "parentTaskName" : "parentTaskName",
    "initiated" : "2000-01-23T04:56:07.000+00:00",
    "errorCode" : 0,
    "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
  },
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "locked" : true
} ]
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

500

Server Error



```
delete /v1/AcceptedDomains/{id}
```

Deletes Accepted Domain (v1AcceptedDomainsIdDelete)

Path parameters

id (required)

Path Parameter — format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

204

No Content

404

Not Found **ProblemDetails**

409Conflict **ProblemDetails****423**Client Error **ProblemDetails** `get /v1/AcceptedDomains/{id}`

Retrieves Record of Accepted Domain (v1AcceptedDomainsIdGet)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

[AcceptedDomainDetailModel](#)

Example data

Content-Type: application/json

```
{
  "created" : "2000-01-23T04:56:07.000+00:00",
  "domain" : "domain",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200Success **AcceptedDomainDetailModel**

401Unauthorized **ProblemDetails****404**Not Found **ProblemDetails**`put /v1/AcceptedDomains/{id}`

Modifies Accepted Domain (v1AcceptedDomainsIdPut)

Path parameters

id (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ModifyAcceptedDomainRequest](#) (optional)**Body Parameter** —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

204

No Content

400Bad Request **ProblemDetails****401**Unauthorized **ProblemDetails****404**Not Found **ProblemDetails****409**Conflict **ProblemDetails****423**Client Error **ProblemDetails****post /v1/AcceptedDomains**

Creates Accepted Domain (v1AcceptedDomainsPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request bodybody [CreateAcceptedDomainRequest](#) (optional)**Body Parameter** —**Return type**

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

201

Created `UUID`

409

Conflict `ProblemDetails`

ActivityAudits



`get /v1/ActivityAudits`

Retrieves list of Activity Audits with pagination (sorting and filtering) (`v1ActivityAuditsGet`)

Query parameters

Sorts (optional)

Query Parameter —

`Pagination.PageSize` (optional)

Query Parameter — The number of records per page, for example 1. Shouldn't exceed 200. format: int32

`Pagination.PageNumber` (optional)

Query Parameter — The page number to retrieve from results, for example 1 format: int32

`Filter.User` (optional)

Query Parameter — Initiated User email or API Client identifier

`Filter.Details` (optional)

Query Parameter — Details of activity

`Filter.Created.Dates` (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

`Filter.Created.SelectionMode` (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.Entity (optional)

Query Parameter — Name of Activity Audit entity

Filter.AuditType (optional)

Query Parameter — Audit Type Name

Filter.ChangedBy (optional)

Query Parameter — Audit ChangedBy

Return type

[ActivityAuditListItemModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "created" : "2000-01-23T04:56:07.000+00:00",
    "changedBy" : "API",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "details" : "details",
    "id" : 5,
    "auditType" : "auditType",
    "locked" : true,
    "user" : "user",
    "entity" : "entity"
  }, {
    "created" : "2000-01-23T04:56:07.000+00:00",
    "changedBy" : "API",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "details" : "details",
    "id" : 5,
    "auditType" : "auditType",
    "locked" : true,
```

```
    "user" : "user",
    "entity" : "entity"
  } ],
  "pageSize" : 6,
  "totalRecordCount" : 1
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **ActivityAuditListItemModelPagedResponse**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

500

Server Error



```
get /v1/ActivityAudits/{id}
```

Retrieves Record of Activity Audit (v1ActivityAuditsIdGet)

Path parameters

id (required)

Path Parameter — format: int64

Return type

[ActivityAuditDetailModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "computerDataAuditing" : {
      "deactivatedAgents" : {
        "key" : "deactivatedAgents"
      },
      "newDeletedAgents" : [ "newDeletedAgents", "newDeletedAgents" ],
      "updatedPoliciesOn" : {
        "key" : "updatedPoliciesOn"
      }
    },
    "groupDataAuditing" : {
      "oldDescription" : "oldDescription",
      "addPolicyRevisions" : {
        "key" : "addPolicyRevisions"
      },
      "newName" : "newName",
      "removePolicyRevisions" : {
        "key" : "removePolicyRevisions"
      },
      "oldName" : "oldName",
      "newAgents" : {
        "key" : "newAgents"
      },
      "oldIsDefault" : true,
      "newDescription" : "newDescription",
      "newIsDefault" : true,
      "removeAgents" : {
        "key" : "removeAgents"
      }
    },
    "created" : "2000-01-23T04:56:07.000+00:00",
    "policyDataAuditing" : {
      "oldDescription" : "oldDescription",
      "newName" : "newName",
      "oldName" : "oldName",
      "newDescription" : "newDescription"
    },
    "policyRevisionDataAuditing" : {
      "newGroups" : {
        "key" : "newGroups"
      }
    }
  } ]
}
```



```
    }
  },
  "auditType" : "auditType",
  "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "settingsDataAuditing" : {
    "modifyDomainOldValue" : "modifyDomainOldValue",
    "modifyDomainNewValue" : "modifyDomainNewValue",
    "removeDomain" : "removeDomain",
    "addDomain" : "addDomain"
  },
  "apiClientDataAuditing" : {
    "oldDescription" : "oldDescription",
    "newName" : "newName",
    "deleted" : true,
    "secretUpdated" : true,
    "oldName" : "oldName",
    "newDescription" : "newDescription"
  },
  "installationKeyDataAuditing" : {
    "newDisabled" : true,
    "oldDisabled" : true,
    "deleted" : true,
    "newLabel" : "newLabel",
    "oldLabel" : "oldLabel"
  },
  "userDataAuditing" : {
    "oldDisabled" : true,
    "newUserType" : "newUserType",
    "oldEmailAddress" : "oldEmailAddress",
    "roles" : [ {
      "resourceId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "newRoles" : [ {
        "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
        "roleName" : "roleName"
      } ], {
        "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
        "roleName" : "roleName"
      } ],
      "oldRoles" : [ null, null ],
      "resourceName" : "resourceName",
      "resourceType" : "resourceType"
    }, {
      "resourceId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "newRoles" : [ {
        "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
        "roleName" : "roleName"
      } ], {
        "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
        "roleName" : "roleName"
      } ],
      "oldRoles" : [ null, null ],
      "resourceName" : "resourceName",
      "resourceType" : "resourceType"
    }
  ]
}
```

```
    } ],
    "newPreferredLanguage" : "newPreferredLanguage",
    "oldDateTimeDisplayFormat" : "oldDateTimeDisplayFormat",
    "newDisabled" : true,
    "newDateTimeDisplayFormat" : "newDateTimeDisplayFormat",
    "oldOlsonTimeZoneId" : "oldOlsonTimeZoneId",
    "oldUserType" : "oldUserType",
    "oldPreferredLanguage" : "oldPreferredLanguage",
    "newOlsonTimeZoneId" : "newOlsonTimeZoneId",
    "newEmailAddress" : "newEmailAddress"
  },
  "changedBy" : "API",
  "details" : "details",
  "id" : 5,
  "user" : "user",
  "entity" : "entity"
}, {
  "computerDataAuditing" : {
    "deactivatedAgents" : {
      "key" : "deactivatedAgents"
    },
    "newDeletedAgents" : [ "newDeletedAgents", "newDeletedAgents" ],
    "updatedPoliciesOn" : {
      "key" : "updatedPoliciesOn"
    }
  },
  "groupDataAuditing" : {
    "oldDescription" : "oldDescription",
    "addPolicyRevisions" : {
      "key" : "addPolicyRevisions"
    },
    "newName" : "newName",
    "removePolicyRevisions" : {
      "key" : "removePolicyRevisions"
    },
    "oldName" : "oldName",
    "newAgents" : {
      "key" : "newAgents"
    },
    "oldIsDefault" : true,
    "newDescription" : "newDescription",
    "newIsDefault" : true,
    "removeAgents" : {
      "key" : "removeAgents"
    }
  },
  "created" : "2000-01-23T04:56:07.000+00:00",
  "policyDataAuditing" : {
    "oldDescription" : "oldDescription",
    "newName" : "newName",
    "oldName" : "oldName",
    "newDescription" : "newDescription"
  }
},
```

```
"policyRevisionDataAuditing" : {
  "newGroups" : {
    "key" : "newGroups"
  }
},
"auditType" : "auditType",
"userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"settingsDataAuditing" : {
  "modifyDomainOldValue" : "modifyDomainOldValue",
  "modifyDomainNewValue" : "modifyDomainNewValue",
  "removeDomain" : "removeDomain",
  "addDomain" : "addDomain"
},
"apiClientDataAuditing" : {
  "oldDescription" : "oldDescription",
  "newName" : "newName",
  "deleted" : true,
  "secretUpdated" : true,
  "oldName" : "oldName",
  "newDescription" : "newDescription"
},
"installationKeyDataAuditing" : {
  "newDisabled" : true,
  "oldDisabled" : true,
  "deleted" : true,
  "newLabel" : "newLabel",
  "oldLabel" : "oldLabel"
},
"userDataAuditing" : {
  "oldDisabled" : true,
  "newUserType" : "newUserType",
  "oldEmailAddress" : "oldEmailAddress",
  "roles" : [ {
    "resourceId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "newRoles" : [ {
      "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "roleName" : "roleName"
    } ],
    "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "roleName" : "roleName"
  } ],
  "oldRoles" : [ null, null ],
  "resourceName" : "resourceName",
  "resourceType" : "resourceType"
}, {
  "resourceId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "newRoles" : [ {
    "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "roleName" : "roleName"
  } ],
  "roleId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "roleName" : "roleName"
} ],
```

```
    "oldRoles" : [ null, null ],
    "resourceName" : "resourceName",
    "resourceType" : "resourceType"
  } ],
  "newPreferredLanguage" : "newPreferredLanguage",
  "oldDateTimeDisplayFormat" : "oldDateTimeDisplayFormat",
  "newDisabled" : true,
  "newDateTimeDisplayFormat" : "newDateTimeDisplayFormat",
  "oldOlsonTimeZoneId" : "oldOlsonTimeZoneId",
  "oldUserType" : "oldUserType",
  "oldPreferredLanguage" : "oldPreferredLanguage",
  "newOlsonTimeZoneId" : "newOlsonTimeZoneId",
  "newEmailAddress" : "newEmailAddress"
},
"changedBy" : "API",
"details" : "details",
"id" : 5,
"user" : "user",
"entity" : "entity"
} ],
"pageSize" : 6,
"totalRecordCount" : 1
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **ActivityAuditDetailModelPagedResponse**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

AuthorizationRequestAudits

 `get /v1/AuthorizationRequestAudits`

Retrieves the list of Authorization Request Audit with pagination (sorting and filtering) (v1AuthorizationRequestAuditsGet)

Query parameters

Sorts (optional)

Query Parameter —

Pagination.PageSize (optional)

Query Parameter — The number of records per page, for example 1. Shouldn't exceed 200. format: int32

Pagination.PageNumber (optional)

Query Parameter — The page number to retrieve from results, for example 1 format: int32

Filter.TicketId (optional)

Query Parameter —

Filter.User (optional)

Query Parameter —

Filter.ComputerName (optional)

Query Parameter —

Filter.ProductName (optional)

Query Parameter —

Filter.Reason (optional)

Query Parameter —

Filter.DecisionPerformedByUser (optional)

Query Parameter —

Filter.Decision (optional)

Query Parameter —

Filter.TimeOfRequest.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

Filter.TimeOfRequest.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.DecisionTime.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

Filter.DecisionTime.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.StartTime.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

Filter.StartTime.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.Duration (optional)

Query Parameter —

Return type

[AuthorizationRequestAuditListItemModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "duration" : "duration",
    "reason" : "reason",
    "decision" : "decision",
    "computerName" : "computerName",
    "decisionTime" : "2000-01-23T04:56:07.000+00:00",
    "timeOfRequest" : "2000-01-23T04:56:07.000+00:00",
    "startTime" : "2000-01-23T04:56:07.000+00:00",
    "id" : 5,
    "user" : "user",
    "ticketId" : "ticketId",
    "productName" : "productName",
    "decisionPerformedByUser" : "decisionPerformedByUser"
  }, {
    "duration" : "duration",
    "reason" : "reason",
    "decision" : "decision",
    "computerName" : "computerName",
    "decisionTime" : "2000-01-23T04:56:07.000+00:00",
    "timeOfRequest" : "2000-01-23T04:56:07.000+00:00",
    "startTime" : "2000-01-23T04:56:07.000+00:00",
    "id" : 5,
    "user" : "user",
    "ticketId" : "ticketId",
    "productName" : "productName",
    "decisionPerformedByUser" : "decisionPerformedByUser"
  } ],
  "pageSize" : 6,
  "totalRecordCount" : 1
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **AuthorizationRequestAuditListItemModelPagedResponse**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

403

Forbidden **ProblemDetails**



```
get /v1/AuthorizationRequestAudits/{id}
```

Retrieves Record of Authorization Request Audit (v1AuthorizationRequestAuditsIdGet)

Path parameters

id (required)

Path Parameter — format: int64

Return type

[AuthorizationRequestAuditDetailModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "duration" : "duration",
    "reason" : "reason",
    "decision" : "decision",
    "computerName" : "computerName",
    "decisionTime" : "2000-01-23T04:56:07.000+00:00",
    "timeOfRequest" : "2000-01-23T04:56:07.000+00:00",
    "startTime" : "2000-01-23T04:56:07.000+00:00",
    "id" : 5,
    "user" : "user",
    "ticketId" : "ticketId",
    "productName" : "productName",
    "decisionPerformedByUser" : "decisionPerformedByUser"
  }, {
    "duration" : "duration",
    "reason" : "reason",
    "decision" : "decision",
    "computerName" : "computerName",
    "decisionTime" : "2000-01-23T04:56:07.000+00:00",
    "timeOfRequest" : "2000-01-23T04:56:07.000+00:00",
    "startTime" : "2000-01-23T04:56:07.000+00:00",
    "id" : 5,
    "user" : "user",
    "ticketId" : "ticketId",
    "productName" : "productName",
    "decisionPerformedByUser" : "decisionPerformedByUser"
  } ],
  "pageSize" : 6,
  "totalRecordCount" : 1
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **AuthorizationRequestAuditDetailModelPagedResponse**

401

Unauthorized **ProblemDetails**

403Forbidden **ProblemDetails****404**Not Found **ProblemDetails**

Computers

 `post /v1/Computers/Authorise`

Authorises Computers (v1ComputersAuthorisePost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ComputersAuthoriseRequest](#) (optional)**Body Parameter** —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success

201Created **UUID**

400Bad Request **ProblemDetails****401**Unauthorized **ProblemDetails****404**Not Found **ProblemDetails****409**Conflict **ProblemDetails****423**Client Error **ProblemDetails****post /v1/Computers/Certificate/Renew**

Request to Renew Computer Certificate (v1ComputersCertificateRenewPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- **application/json**
- **text/json**
- **application/*+json**

Request bodybody [ComputerRenewCertificateRequest](#) (optional)**Body Parameter** —**Produces**

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

202

Accepted

400

Bad Request **ProblemDetails**

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**



`post /v1/Computers/Deactivate`

Deactivates Computers (v1ComputersDeactivatePost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ComputersDeactivateRequest](#) (optional)

Body Parameter —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success

201

Created **UUID**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



`delete /v1/Computers`

Deletes Computers (v1ComputersDelete)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ComputersRemoveRequest](#) (optional)

Body Parameter — Request containing data to filter Computers to be removed

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success

201

Created **UUID**

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



```
post /v1/Computers/Details/Request
```

Retrieves Computer Status Info (`v1ComputersDetailsRequestPost`)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ComputerRetrieveStatusInfoRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

201

Created **UUID**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



```
get /v1/Computers
```

Retrieves the list of Computers with pagination (sorting and filtering) (v1ComputersGet)

Query parameters

Sorts (optional)

Query Parameter —

Pagination.PageSize (optional)

Query Parameter — The number of records per page, for example 1. Shouldn't exceed 200. format: int32

Pagination.PageNumber (optional)

Query Parameter — The page number to retrieve from results, for example 1 format: int32

Filter.ComputerId (optional)

Query Parameter — The Id of the Computer(Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

Filter.Host (optional)

Query Parameter — The host name of the Computer, for example - Computer1

Filter.HostType (optional)

Query Parameter — The host type of the Computer, for example - MicrosoftWindows, Linux

Filter.AgentVersion (optional)

Query Parameter — The agent version of the Computer, example - 5.6.126.0

Filter.AdapterVersion (optional)

Query Parameter — The adapter version of the Computer, example - 20.5.195.0

Filter.AuthorisationState (optional)

Query Parameter — The state of the Computer, example - Authorised, Pending

Filter.LastConnected.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

Filter.LastConnected.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.PolicyRevisionStatus (optional)

Query Parameter — Policy Revision Status, example - AwaitingLatestPolicy

Filter.PolicyId (optional)

Query Parameter — Policy Id, example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

Filter.PolicyName (optional)

Query Parameter — Policy Name, example - Policy1

Filter.GroupId (optional)

Query Parameter — Group Id, example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

Filter.GroupName (optional)

Query Parameter — Group Name, example - Group1

Filter.OS (optional)

Query Parameter — OS Name, example - Windows

Filter.Domain (optional)

Query Parameter — Domain Name, example - BeyondTrust

Filter.Created.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24

19:09:47.6816562 +00:00 format: date-time

Filter.Created.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.DuplicateCount.Min (optional)

Query Parameter — Min Value of CountRange, example - 1,2,3 format: int32

Filter.DuplicateCount.Max (optional)

Query Parameter — Max Value of CountRange, example - 1,2,3 format: int32

Return type

[ComputerListItemModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "rejected" : true,
    "deactivatedOn" : "2000-01-23T04:56:07.000+00:00",
    "groupId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "deactivated" : true,
    "authorisationState" : "authorisationState",
    "lastConnected" : "2000-01-23T04:56:07.000+00:00",
    "hostType" : "Undefined",
    "host" : "host",
    "adapterVersion" : "adapterVersion",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "locked" : true,
    "os" : "os",
    "policyName" : "policyName",
    "created" : "2000-01-23T04:56:07.000+00:00",
    "pendingDeactivation" : true,
    "duplicate" : true,
    "policyRevisionId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "credentialType" : "credentialType",
    "groupName" : "groupName",
```



```
"policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"duplicateCount" : 5,
"domain" : "domain",
"agentVersion" : "agentVersion",
"policyRevisionStatus" : "policyRevisionStatus"
}, {
  "rejected" : true,
  "deactivatedOn" : "2000-01-23T04:56:07.000+00:00",
  "groupId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "errorInfo" : {
    "userAccountName" : "userAccountName",
    "parentTaskName" : "parentTaskName",
    "initiated" : "2000-01-23T04:56:07.000+00:00",
    "errorCode" : 0,
    "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
  },
  "deactivated" : true,
  "authorisationState" : "authorisationState",
  "lastConnected" : "2000-01-23T04:56:07.000+00:00",
  "hostType" : "Undefined",
  "host" : "host",
  "adapterVersion" : "adapterVersion",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "locked" : true,
  "os" : "os",
  "policyName" : "policyName",
  "created" : "2000-01-23T04:56:07.000+00:00",
  "pendingDeactivation" : true,
  "duplicate" : true,
  "policyRevisionId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "credentialType" : "credentialType",
  "groupName" : "groupName",
  "policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "duplicateCount" : 5,
  "domain" : "domain",
  "agentVersion" : "agentVersion",
  "policyRevisionStatus" : "policyRevisionStatus"
} ],
"pageSize" : 6,
"totalRecordCount" : 1
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **ComputerListItemModelPagedResponse**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**



```
get /v1/Computers/{id}/CommandLog
```

Gets Computer Command Logs List (v1ComputersIdCommandLogGet)

Path parameters

id (required)

Path Parameter — format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success

404

Not Found **ProblemDetails**



```
get /v1/Computers/{id}
```

Retrieves a detail of the Computer (v1ComputersIdGet)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

[ComputerDetailModel](#)

Example data

Content-Type: application/json

```
{
  "deactivatedOn" : "2000-01-23T04:56:07.000+00:00",
  "groupId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "hostPolicyName" : "hostPolicyName",
  "policyRevision" : 0,
  "autoDeactivated" : true,
  "agentLogs" : [ {
    "created" : "2000-01-23T04:56:07.000+00:00",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "returned" : "2000-01-23T04:56:07.000+00:00"
  }, {
    "created" : "2000-01-23T04:56:07.000+00:00",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "returned" : "2000-01-23T04:56:07.000+00:00"
  } ],
  "deactivated" : true,
  "authorisationState" : "authorisationState",
  "certificateInformation" : {
    "lastIssued" : "2000-01-23T04:56:07.000+00:00",
    "validFrom" : "2000-01-23T04:56:07.000+00:00",
    "validTo" : "2000-01-23T04:56:07.000+00:00"
  },
  "lastConnected" : "2000-01-23T04:56:07.000+00:00",
  "hostType" : "hostType",
  "authorised" : "2000-01-23T04:56:07.000+00:00",
  "adapterVersion" : "adapterVersion",
  "hostLastUpdated" : "2000-01-23T04:56:07.000+00:00",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "policyName" : "policyName",
  "created" : "2000-01-23T04:56:07.000+00:00",
  "pendingDeactivation" : true,
  "endpointInformation" : {
    "systemModel" : "systemModel",
    "systemPrimaryOwnerName" : "systemPrimaryOwnerName",
    "osArchitecture" : "osArchitecture",
```

```
"systemSystemType" : "systemSystemType",
"systemDomain" : "systemDomain",
"processorManufacturer" : "processorManufacturer",
"osVersion" : "osVersion",
"systemName" : "systemName",
"osVersionString" : "osVersionString",
"osCaption" : "osCaption",
"systemManufacturer" : "systemManufacturer",
"processorName" : "processorName",
"osCodeSet" : "osCodeSet",
"osSystemDrive" : "osSystemDrive",
"osOrganization" : "osOrganization",
"processorDescription" : "processorDescription",
"osCountryCode" : "osCountryCode",
"osInstallDate" : "2000-01-23T04:56:07.000+00:00",
"osSystemDirectory" : "osSystemDirectory",
"osComputerDescription" : "osComputerDescription",
"osSerialNumber" : "osSerialNumber",
"macAddress" : "macAddress",
"processorCaption" : "processorCaption",
"systemDnsHostName" : "systemDnsHostName",
"osManufacturer" : "osManufacturer",
"systemWorkgroup" : "systemWorkgroup"
},
"connected" : true,
"credentialType" : "credentialType",
"groupName" : "groupName",
"policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"duplicateCount" : 1,
"agentVersion" : "agentVersion",
"hostPolicyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"policyRevisionStatus" : "policyRevisionStatus",
"hostPolicyRevision" : 6
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **ComputerDetailModel**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

`get /v1/Computers/{id}/Logs`

Gets Computer Logs (v1ComputersIdLogsGet)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

array[[ComputerLogModel](#)]

Example data

Content-Type: application/json

```
[ {
  "created" : "2000-01-23T04:56:07.000+00:00",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "returned" : "2000-01-23T04:56:07.000+00:00"
}, {
  "created" : "2000-01-23T04:56:07.000+00:00",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "returned" : "2000-01-23T04:56:07.000+00:00"
} ]
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success

400Bad Request **ProblemDetails****401**Unauthorized **ProblemDetails**`get /v1/Computers/Logs/{id}/Content`

Downloads Computer Log (v1ComputersLogsIdContentGet)

Path parameters

id (required)

Path Parameter — format: uuid**Produces**

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses**404**Not Found **ProblemDetails****409**Conflict **ProblemDetails**`post /v1/Computers/Logs/Request`

Retrieves Computer Logs (v1ComputersLogsRequestPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request body

body [ComputerRetrieveLogsRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

201

Created **UUID**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

409Conflict **ProblemDetails****423**Client Error **ProblemDetails** `post /v1/Computers/Reject`

Rejects Computers (v1ComputersRejectPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request bodybody [ComputersRejectRequest](#) (optional)**Body Parameter** — Request containing data to filter Computers to be rejected**Produces**

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses**200**

Success

201Created **UUID****404**Not Found **ProblemDetails**

409Conflict **ProblemDetails****423**Client Error **ProblemDetails**

Events

 `get /v1/Events/FromStartDate`

Gets the list of events by start date (v1EventsFromStartDateGet)

Query parameters

StartDate (required)

Query Parameter — Start Date(UTC) to search events from (Elastic Ingestion Timestamp in UTC). Example: 2022-08-12T17:34:28.694Z

RecordSize (optional)

Query Parameter — Maximum records that can be returned. Min size: 1, Max size: 1000, Example: 100 default: 1000 format: int32

Return type

[EpmEcsEventResponseModel](#)

Example data

Content-Type: application/json

```
{
  "totalRecordsReturned" : 0,
  "events" : [ {
    "container" : {
      "image" : {
        "name" : "name",
        "tag" : [ "tag", "tag" ],
        "hash" : {
          "all" : [ "all", "all" ]
        }
      },
      "disk" : {
        "read" : {
```

```
        "bytes" : 4
      },
      "write" : {
        "bytes" : 5
      }
    },
    "memory" : {
      "usage" : 9.965781217890562
    },
    "name" : "name",
    "cpu" : {
      "usage" : 1.1730742509559433
    },
    "runtime" : "runtime",
    "id" : "id",
    "labels" : "labels",
    "network" : {
      "ingress" : {
        "bytes" : 9
      },
      "egress" : {
        "bytes" : 6
      }
    }
  },
  "server" : {
    "nat" : {
      "port" : 7,
      "ip" : "ip"
    },
    "address" : "address",
    "top_level_domain" : "top_level_domain",
    "ip" : "ip",
    "mac" : "mac",
    "packets" : 0,
    "registered_domain" : "registered_domain",
    "port" : 4,
    "bytes" : 0,
    "domain" : "domain",
    "subdomain" : "subdomain"
  },
  "agent" : {
    "build" : {
      "original" : "original"
    },
    "name" : "name",
    "id" : "id",
    "type" : "type",
    "ephemeral_id" : "ephemeral_id",
    "version" : "version"
  },
  "faas" : {
    "execution" : "execution",
```

```
"coldstart" : true,
"name" : "name",
"id" : "id",
"trigger" : {
  "type" : "type",
  "request_id" : "request_id"
},
"version" : "version"
},
"log" : {
  "file" : {
    "path" : "path"
  },
  "level" : "level",
  "logger" : "logger",
  "origin" : {
    "file" : {
      "line" : 7,
      "name" : "name"
    },
    "function" : "function"
  },
  "syslog" : "syslog"
},
"destination" : {
  "nat" : {
    "port" : 3,
    "ip" : "ip"
  },
  "address" : "address",
  "top_level_domain" : "top_level_domain",
  "ip" : "ip",
  "mac" : "mac",
  "packets" : 6,
  "registered_domain" : "registered_domain",
  "port" : 8,
  "bytes" : 9,
  "domain" : "domain",
  "subdomain" : "subdomain"
},
"rule" : {
  "reference" : "reference",
  "license" : "license",
  "author" : [ "author", "author" ],
  "name" : "name",
  "ruleset" : "ruleset",
  "description" : "description",
  "id" : "id",
  "category" : "category",
  "uuid" : "uuid",
  "version" : "version"
},
"error" : {
```

```
    "code" : "code",
    "id" : "id",
    "stack_trace" : "stack_trace",
    "message" : "message",
    "type" : "type"
  },
  "network" : {
    "transport" : "transport",
    "type" : "type",
    "inner" : "inner",
    "packets" : 0,
    "protocol" : "protocol",
    "forwarded_ip" : "forwarded_ip",
    "community_id" : "community_id",
    "application" : "application",
    "vlan" : {
      "name" : "name",
      "id" : "id"
    },
    "bytes" : 9,
    "name" : "name",
    "iana_number" : "iana_number",
    "direction" : "direction"
  },
  "cloud" : {
    "availability_zone" : "availability_zone",
    "instance" : {
      "name" : "name",
      "id" : "id"
    },
    "provider" : "provider",
    "machine" : {
      "type" : "type"
    },
    "service" : {
      "name" : "name"
    },
    "origin" : {
      "availability_zone" : "availability_zone",
      "provider" : "provider",
      "region" : "region"
    },
    "project" : {
      "name" : "name",
      "id" : "id"
    },
    "region" : "region",
    "account" : {
      "name" : "name",
      "id" : "id"
    },
    "target" : {
      "availability_zone" : "availability_zone",
```

```
    "provider" : "provider",
    "region" : "region"
  }
},
"observer" : {
  "product" : "product",
  "ip" : [ "ip", "ip" ],
  "serial_number" : "serial_number",
  "type" : "type",
  "version" : "version",
  "mac" : [ "mac", "mac" ],
  "egress" : "egress",
  "ingress" : "ingress",
  "hostname" : "hostname",
  "vendor" : "vendor",
  "name" : "name"
},
"trace" : {
  "id" : "id"
},
"file" : {
  "extension" : "extension",
  "SourceUrl" : "SourceUrl",
  "Owner" : {
    "Identifier" : "Identifier",
    "DomainName" : "DomainName",
    "DomainNetBIOSName" : "DomainNetBIOSName",
    "Name" : "Name",
    "DomainIdentifier" : "DomainIdentifier"
  },
  "gid" : "gid",
  "Description" : "Description",
  "drive_letter" : "drive_letter",
  "ProductVersion" : "ProductVersion",
  "type" : "type",
  "mtime" : "2000-01-23T04:56:07.000+00:00",
  "accessed" : "2000-01-23T04:56:07.000+00:00",
  "directory" : "directory",
  "inode" : "inode",
  "mode" : "mode",
  "path" : "path",
  "uid" : "uid",
  "Version" : "Version",
  "ctime" : "2000-01-23T04:56:07.000+00:00",
  "fork_name" : "fork_name",
  "elf" : {
    "imports" : {
      "key" : "imports"
    },
    "shared_libraries" : [ "shared_libraries", "shared_libraries" ],
    "byte_order" : "byte_order",
    "exports" : {
      "key" : "exports"
    }
  }
}
```

```
    },
    "cpu_type" : "cpu_type",
    "header" : {
      "object_version" : "object_version",
      "data" : "data",
      "os_abi" : "os_abi",
      "entrypoint" : 7,
      "abi_version" : "abi_version",
      "type" : "type",
      "class" : "class",
      "version" : "version"
    },
    "creation_date" : "2000-01-23T04:56:07.000+00:00",
    "sections" : [ {
      "chi2" : 4,
      "virtual_address" : 7,
      "entropy" : 0,
      "physical_offset" : "physical_offset",
      "flags" : "flags",
      "name" : "name",
      "physical_size" : 0,
      "type" : "type",
      "virtual_size" : 6
    }, {
      "chi2" : 4,
      "virtual_address" : 7,
      "entropy" : 0,
      "physical_offset" : "physical_offset",
      "flags" : "flags",
      "name" : "name",
      "physical_size" : 0,
      "type" : "type",
      "virtual_size" : 6
    } ],
    "telfhash" : "telfhash",
    "architecture" : "architecture",
    "segments" : [ {
      "type" : "type",
      "sections" : "sections"
    }, {
      "type" : "type",
      "sections" : "sections"
    } ]
  },
  "group" : "group",
  "owner" : "owner",
  "created" : "2000-01-23T04:56:07.000+00:00",
  "Bundle" : {
    "Type" : "Type",
    "DownloadSource" : "DownloadSource",
    "Version" : "Version",
    "InfoDescription" : "InfoDescription",
    "Creator" : "Creator",
```

```
    "Uri" : "Uri",
    "Name" : "Name"
  },
  "target_path" : "target_path",
  "DriveType" : "DriveType",
  "x509" : {
    "not_after" : "2000-01-23T04:56:07.000+00:00",
    "public_key_exponent" : 3,
    "not_before" : "2000-01-23T04:56:07.000+00:00",
    "subject" : {
      "state_or_province" : [ "state_or_province", "state_or_province" ],
      "country" : [ "country", "country" ],
      "organization" : [ "organization", "organization" ],
      "distinguished_name" : "distinguished_name",
      "locality" : [ "locality", "locality" ],
      "common_name" : [ "common_name", "common_name" ],
      "organizational_unit" : [ "organizational_unit", "organizational_unit" ]
    },
    "public_key_algorithm" : "public_key_algorithm",
    "public_key_curve" : "public_key_curve",
    "signature_algorithm" : "signature_algorithm",
    "version_number" : "version_number",
    "serial_number" : "serial_number",
    "public_key_size" : 3,
    "alternative_names" : [ "alternative_names", "alternative_names" ],
    "issuer" : {
      "state_or_province" : [ "state_or_province", "state_or_province" ],
      "country" : [ "country", "country" ],
      "organization" : [ "organization", "organization" ],
      "distinguished_name" : "distinguished_name",
      "locality" : [ "locality", "locality" ],
      "common_name" : [ "common_name", "common_name" ],
      "organizational_unit" : [ "organizational_unit", "organizational_unit" ]
    }
  },
  "size" : 6,
  "mime_type" : "mime_type",
  "ZoneTag" : "ZoneTag",
  "name" : "name",
  "attributes" : [ "attributes", "attributes" ],
  "device" : "device"
},
"ecs" : {
  "version" : "version"
},
"related" : {
  "hosts" : [ "hosts", "hosts" ],
  "ip" : [ "ip", "ip" ],
  "user" : [ "user", "user" ],
  "hash" : [ "hash", "hash" ]
},
"host" : {
  "DefaultUILanguage" : "DefaultUILanguage",
```

```
"os" : {
  "kernel" : "kernel",
  "name" : "name",
  "ProductType" : "ProductType",
  "type" : "type",
  "family" : "family",
  "version" : "version",
  "platform" : "platform",
  "full" : "full"
},
"DomainNetBIOSName" : "DomainNetBIOSName",
"ip" : [ "ip", "ip" ],
"cpu" : {
  "usage" : 7.740351818741173
},
"pid_ns_ino" : "pid_ns_ino",
"type" : "type",
"mac" : [ "mac", "mac" ],
"uptime" : 8,
"network" : {
  "ingress" : {
    "bytes" : 7,
    "packets" : 5
  },
  "egress" : {
    "bytes" : 3,
    "packets" : 4
  }
},
"DefaultLocale" : "DefaultLocale",
"hostname" : "hostname",
"disk" : {
  "read" : {
    "bytes" : 3
  },
  "write" : {
    "bytes" : 3
  }
},
"ClientName" : "ClientName",
"domain" : "domain",
"NetBIOSName" : "NetBIOSName",
"name" : "name",
"id" : "id",
"ChassisType" : "ChassisType",
"boot" : {
  "id" : "id"
},
"architecture" : "architecture",
"DomainIdentifier" : "DomainIdentifier"
},
"client" : {
  "nat" : {
```



```
    "port" : 5,
    "ip" : "ip"
  },
  "address" : "address",
  "top_level_domain" : "top_level_domain",
  "ip" : "ip",
  "mac" : "mac",
  "packets" : 5,
  "geo" : {
    "continent_name" : "continent_name",
    "region_iso_code" : "region_iso_code",
    "city_name" : "city_name",
    "country_iso_code" : "country_iso_code",
    "timezone" : "timezone",
    "country_name" : "country_name",
    "name" : "name",
    "continent_code" : "continent_code",
    "location" : {
      "lon" : 7.061401241503109,
      "lat" : 9.301444243932576
    },
    "region_name" : "region_name",
    "postal_code" : "postal_code",
    "TimezoneOffset" : 3
  },
  "registered_domain" : "registered_domain",
  "as" : {
    "number" : 2,
    "organization" : {
      "name" : "name"
    }
  },
  "port" : 6,
  "bytes" : 1,
  "domain" : "domain",
  "subdomain" : "subdomain",
  "user" : {
    "DefaultUILanguage" : "DefaultUILanguage",
    "DomainNetBIOSName" : "DomainNetBIOSName",
    "roles" : [ "roles", "roles" ],
    "changes" : {
      "DefaultUILanguage" : "DefaultUILanguage",
      "DomainNetBIOSName" : "DomainNetBIOSName",
      "roles" : [ "roles", "roles" ],
      "LocalIdentifier" : 7,
      "DefaultTimezoneOffset" : 6,
      "DefaultLocale" : "DefaultLocale",
      "full_name" : "full_name",
      "domain" : "domain",
      "name" : "name",
      "id" : "id",
      "email" : "email",
      "hash" : "hash",
```

```
    "DomainIdentifier" : "DomainIdentifier"
  },
  "LocalIdentifier" : 4,
  "target" : {
    "DefaultUILanguage" : "DefaultUILanguage",
    "DomainNetBIOSName" : "DomainNetBIOSName",
    "roles" : [ "roles", "roles" ],
    "LocalIdentifier" : 1,
    "DefaultTimezoneOffset" : 7,
    "DefaultLocale" : "DefaultLocale",
    "full_name" : "full_name",
    "domain" : "domain",
    "name" : "name",
    "id" : "id",
    "email" : "email",
    "hash" : "hash",
    "DomainIdentifier" : "DomainIdentifier"
  },
  "DefaultTimezoneOffset" : 2,
  "DefaultLocale" : "DefaultLocale",
  "effective" : {
    "DefaultUILanguage" : "DefaultUILanguage",
    "DomainNetBIOSName" : "DomainNetBIOSName",
    "roles" : [ "roles", "roles" ],
    "LocalIdentifier" : 1,
    "DefaultTimezoneOffset" : 1,
    "DefaultLocale" : "DefaultLocale",
    "full_name" : "full_name",
    "domain" : "domain",
    "name" : "name",
    "id" : "id",
    "email" : "email",
    "hash" : "hash",
    "DomainIdentifier" : "DomainIdentifier"
  },
  "full_name" : "full_name",
  "domain" : "domain",
  "name" : "name",
  "id" : "id",
  "email" : "email",
  "hash" : "hash",
  "DomainIdentifier" : "DomainIdentifier",
  "group" : {
    "domain" : "domain",
    "name" : "name",
    "id" : "id"
  }
}
},
"event" : {
  "reason" : "reason",
  "code" : "code",
  "timezone" : "timezone",
```

```
"type" : [ "type", "type" ],
"duration" : 2,
"reference" : "reference",
"agent_id_status" : "agent_id_status",
"ingested" : "2000-01-23T04:56:07.000+00:00",
"provider" : "provider",
"action" : "action",
"end" : "2000-01-23T04:56:07.000+00:00",
"id" : "id",
"outcome" : "outcome",
"severity" : 1,
"original" : "original",
"risk_score" : 6.878052220127876,
"kind" : "kind",
"created" : "2000-01-23T04:56:07.000+00:00",
"module" : "module",
"start" : "2000-01-23T04:56:07.000+00:00",
"url" : "url",
"sequence" : 6,
"risk_score_norm" : 5.944895607614016,
"category" : [ "category", "category" ],
"dataset" : "dataset",
"hash" : "hash"
},
"email" : {
  "cc" : {
    "address" : [ "address", "address" ]
  },
  "origination_timestamp" : "2000-01-23T04:56:07.000+00:00",
  "attachments" : [ {
    "file" : {
      "extension" : "extension",
      "size" : 6,
      "mime_type" : "mime_type",
      "name" : "name"
    }
  }, {
    "file" : {
      "extension" : "extension",
      "size" : 6,
      "mime_type" : "mime_type",
      "name" : "name"
    }
  } ],
  "bcc" : {
    "address" : [ "address", "address" ]
  },
  "local_id" : "local_id",
  "subject" : "subject",
  "message_id" : "message_id",
  "x_mailer" : "x_mailer",
  "content_type" : "content_type",
  "reply_to" : {
```

```
    "address" : [ "address", "address" ]
  },
  "sender" : {
    "address" : "address"
  },
  "delivery_timestamp" : "2000-01-23T04:56:07.000+00:00",
  "from" : {
    "address" : [ "address", "address" ]
  },
  "to" : {
    "address" : [ "address", "address" ]
  },
  "direction" : "direction"
},
"user_agent" : {
  "original" : "original",
  "name" : "name",
  "version" : "version",
  "device" : {
    "name" : "name"
  }
},
"registry" : {
  "hive" : "hive",
  "path" : "path",
  "data" : {
    "strings" : [ "strings", "strings" ],
    "bytes" : "bytes",
    "type" : "type"
  },
  "value" : "value",
  "key" : "key"
},
"process" : {
  "parent" : {
    "ElevationRequired" : true,
    "interactive" : true,
    "pid" : 1,
    "working_directory" : "working_directory",
    "title" : "title",
    "end" : "2000-01-23T04:56:07.000+00:00",
    "same_as_process" : true,
    "group_leader" : {
      "ElevationRequired" : true,
      "interactive" : true,
      "pid" : 9,
      "working_directory" : "working_directory",
      "title" : "title",
      "end" : "2000-01-23T04:56:07.000+00:00",
      "same_as_process" : true,
      "pgid" : 1,
      "start" : "2000-01-23T04:56:07.000+00:00",
      "entity_id" : "entity_id",
```

```
    "executable" : "executable",
    "uptime" : 9,
    "env_vars" : "env_vars",
    "args" : [ "args", "args" ],
    "name" : "name",
    "exit_code" : 8,
    "tty" : "tty",
    "args_count" : 3,
    "command_line" : "command_line"
  },
  "pgid" : 8,
  "start" : "2000-01-23T04:56:07.000+00:00",
  "entity_id" : "entity_id",
  "executable" : "executable",
  "uptime" : 4,
  "env_vars" : "env_vars",
  "args" : [ "args", "args" ],
  "name" : "name",
  "exit_code" : 8,
  "tty" : "tty",
  "args_count" : 6,
  "command_line" : "command_line"
},
"ElevationRequired" : true,
"interactive" : true,
"pid" : 0,
"working_directory" : "working_directory",
"title" : "title",
"end" : "2000-01-23T04:56:07.000+00:00",
"same_as_process" : true,
"previous" : {
  "ElevationRequired" : true,
  "interactive" : true,
  "pid" : 0,
  "working_directory" : "working_directory",
  "title" : "title",
  "end" : "2000-01-23T04:56:07.000+00:00",
  "same_as_process" : true,
  "pgid" : 3,
  "start" : "2000-01-23T04:56:07.000+00:00",
  "entity_id" : "entity_id",
  "executable" : "executable",
  "uptime" : 3,
  "env_vars" : "env_vars",
  "args" : [ "args", "args" ],
  "name" : "name",
  "exit_code" : 8,
  "tty" : "tty",
  "args_count" : 2,
  "command_line" : "command_line"
},
"pgid" : 7,
"start" : "2000-01-23T04:56:07.000+00:00",
```

```
"entry_meta" : {
  "source" : {
    "nat" : {
      "port" : 2,
      "ip" : "ip"
    },
    "address" : "address",
    "top_level_domain" : "top_level_domain",
    "ip" : "ip",
    "mac" : "mac",
    "packets" : 0,
    "registered_domain" : "registered_domain",
    "port" : 4,
    "bytes" : 3,
    "domain" : "domain",
    "subdomain" : "subdomain"
  },
  "type" : "type"
},
"thread" : {
  "name" : "name",
  "id" : 4
},
"entity_id" : "entity_id",
"executable" : "executable",
"uptime" : 6,
"env_vars" : "env_vars",
"args" : [ "args", "args" ],
"session_leader" : {
  "ElevationRequired" : true,
  "interactive" : true,
  "pid" : 3,
  "working_directory" : "working_directory",
  "title" : "title",
  "end" : "2000-01-23T04:56:07.000+00:00",
  "same_as_process" : true,
  "pgid" : 3,
  "start" : "2000-01-23T04:56:07.000+00:00",
  "entity_id" : "entity_id",
  "executable" : "executable",
  "uptime" : 5,
  "env_vars" : "env_vars",
  "args" : [ "args", "args" ],
  "name" : "name",
  "exit_code" : 7,
  "tty" : "tty",
  "args_count" : 9,
  "command_line" : "command_line"
},
"entry_leader" : {
  "ElevationRequired" : true,
  "interactive" : true,
  "pid" : 0,
```

```
    "working_directory" : "working_directory",
    "title" : "title",
    "end" : "2000-01-23T04:56:07.000+00:00",
    "same_as_process" : true,
    "pgid" : 5,
    "start" : "2000-01-23T04:56:07.000+00:00",
    "entity_id" : "entity_id",
    "executable" : "executable",
    "uptime" : 8,
    "env_vars" : "env_vars",
    "args" : [ "args", "args" ],
    "name" : "name",
    "exit_code" : 7,
    "tty" : "tty",
    "args_count" : 5,
    "command_line" : "command_line"
  },
  "name" : "name",
  "exit_code" : 8,
  "tty" : "tty",
  "args_count" : 5,
  "command_line" : "command_line"
},
"package" : {
  "installed" : "2000-01-23T04:56:07.000+00:00",
  "build_version" : "build_version",
  "description" : "description",
  "type" : "type",
  "version" : "version",
  "reference" : "reference",
  "path" : "path",
  "license" : "license",
  "install_scope" : "install_scope",
  "size" : 9,
  "name" : "name",
  "checksum" : "checksum",
  "architecture" : "architecture"
},
"dll" : {
  "path" : "path",
  "code_signature" : {
    "valid" : true,
    "digest_algorithm" : "digest_algorithm",
    "signing_id" : "signing_id",
    "trusted" : true,
    "subject_name" : "subject_name",
    "exists" : true,
    "team_id" : "team_id",
    "status" : "status",
    "timestamp" : "2000-01-23T04:56:07.000+00:00"
  },
  "pe" : {
    "file_version" : "file_version",
```

```
    "product" : "product",
    "imphash" : "imphash",
    "description" : "description",
    "original_file_name" : "original_file_name",
    "company" : "company",
    "pehash" : "pehash",
    "architecture" : "architecture"
  },
  "name" : "name",
  "hash" : {
    "sha1" : "sha1",
    "sha384" : "sha384",
    "sha256" : "sha256",
    "sha512" : "sha512",
    "tlsh" : "tlsh",
    "ssdeep" : "ssdeep",
    "md5" : "md5"
  }
},
"dns" : {
  "op_code" : "op_code",
  "response_code" : "response_code",
  "resolved_ip" : [ "resolved_ip", "resolved_ip" ],
  "question" : {
    "registered_domain" : "registered_domain",
    "top_level_domain" : "top_level_domain",
    "name" : "name",
    "subdomain" : "subdomain",
    "type" : "type",
    "class" : "class"
  },
  "answers" : "answers",
  "id" : "id",
  "header_flags" : [ "header_flags", "header_flags" ],
  "type" : "type"
},
"vulnerability" : {
  "reference" : "reference",
  "severity" : "severity",
  "score" : {
    "environmental" : 4.8789878742268815,
    "version" : "version",
    "temporal" : 6.173804034172511,
    "base" : 2.535258963197524
  },
  "report_id" : "report_id",
  "scanner" : {
    "vendor" : "vendor"
  },
  "description" : "description",
  "id" : "id",
  "classification" : "classification",
  "enumeration" : "enumeration",
```



```
    "category" : [ "category", "category" ]
  },
  "message" : "message",
  "tags" : [ "tags", "tags" ],
  "labels" : "labels",
  "orchestrator" : {
    "cluster" : {
      "name" : "name",
      "id" : "id",
      "version" : "version",
      "url" : "url"
    },
    "resource" : {
      "parent" : {
        "type" : "type"
      },
      "ip" : [ "ip", "ip" ],
      "name" : "name",
      "id" : "id",
      "type" : "type"
    },
    "organization" : "organization",
    "namespace" : "namespace",
    "type" : "type",
    "api_version" : "api_version"
  },
  "@timestamp" : "2000-01-23T04:56:07.000+00:00",
  "EPMWinMac" : {
    "COM" : {
      "AppID" : "AppID",
      "CLSID" : "CLSID",
      "DisplayName" : "DisplayName"
    },
    "AuthorizingUser" : {
      "Identifier" : "Identifier",
      "DomainNetBIOSName" : "DomainNetBIOSName",
      "DomainName" : "DomainName",
      "Name" : "Name",
      "DomainIdentifier" : "DomainIdentifier",
      "CredentialSource" : "CredentialSource"
    },
    "PrivilegedGroup" : {
      "Access" : "Access",
      "RID" : "RID",
      "Name" : "Name"
    },
    "AuthorizationRequest" : {
      "AuthRequestURI" : "AuthRequestURI",
      "ControlAuthorization" : true
    },
    "SchemaVersion" : "SchemaVersion",
    "Configuration" : {
      "Path" : "Path",
```

```
"Message" : {
  "Authorization" : {
    "ResponseStatus" : "ResponseStatus",
    "ChallengeCode" : "ChallengeCode"
  },
  "AuthMethods" : [ "AuthMethods", "AuthMethods" ],
  "Type" : "Type",
  "Description" : "Description",
  "Identifier" : "Identifier",
  "Authentication" : {
    "User" : "User"
  },
  "UserReason" : "UserReason",
  "Name" : "Name"
},
"GPO" : {
  "Version" : "Version",
  "DisplayName" : "DisplayName",
  "LinkInformation" : "LinkInformation",
  "ActiveDirectoryPath" : "ActiveDirectoryPath"
},
"LoadAuditMode" : [ "LoadAuditMode", "LoadAuditMode" ],
"Token" : {
  "Description" : "Description",
  "Identifier" : "Identifier",
  "Name" : "Name"
},
"ContentGroup" : {
  "Description" : "Description",
  "Identifier" : "Identifier",
  "Name" : "Name"
},
"RuleScript" : {
  "Outcome" : {
    "Version" : "Version",
    "Output" : "Output",
    "RuleAffected" : true,
    "Name" : "Name",
    "Result" : "Result"
  },
  "FileName" : "FileName",
  "Publisher" : "Publisher"
},
"RevisionNumber" : "RevisionNumber",
"Workstyle" : {
  "Description" : "Description",
  "Identifier" : "Identifier",
  "Name" : "Name"
},
"Source" : "Source",
"Name" : "Name",
"ApplicationGroup" : {
  "Description" : "Description",
```

```
    "Identifier" : "Identifier",
    "Name" : "Name"
  },
  "Identifier" : "Identifier",
  "Content" : {
    "Type" : "Type",
    "Description" : "Description",
    "Identifier" : "Identifier"
  },
  "SigningEnforcement" : "SigningEnforcement",
  "Rule" : {
    "Action" : "Action",
    "Identifier" : "Identifier",
    "OnDemand" : true
  },
  "Application" : {
    "Type" : "Type",
    "Description" : "Description",
    "Identifier" : "Identifier"
  }
},
"Installer" : {
  "Action" : "Action",
  "ProductCode" : "ProductCode",
  "UpgradeCode" : "UpgradeCode"
},
"ActiveX" : {
  "Version" : "Version",
  "CLSID" : "CLSID",
  "Codebase" : "Codebase"
},
"GroupId" : "GroupId",
"TenantId" : "TenantId",
"StoreApp" : {
  "Version" : "Version",
  "Publisher" : "Publisher",
  "Name" : "Name"
},
"ServiceControl" : {
  "Service" : {
    "DisplayName" : "DisplayName",
    "Name" : "Name"
  }
},
"TrustedApplication" : {
  "Version" : "Version",
  "Name" : "Name"
},
"Event" : {
  "Type" : "Type",
  "Action" : "Action"
},
"RemotePowerShell" : {
```

```
    "Command" : "Command"
  },
  "AdapterVersion" : "AdapterVersion",
  "Session" : {
    "Locale" : "Locale",
    "PowerUser" : true,
    "WindowsSessionId" : "WindowsSessionId",
    "Administrator" : true,
    "Identifier" : "Identifier",
    "UILanguage" : "UILanguage"
  }
},
"data_stream" : {
  "namespace" : "namespace",
  "type" : "type",
  "dataset" : "dataset"
},
"service" : {
  "node" : {
    "role" : "role",
    "name" : "name"
  },
  "environment" : "environment",
  "address" : "address",
  "origin" : {
    "environment" : "environment",
    "address" : "address",
    "name" : "name",
    "id" : "id",
    "state" : "state",
    "type" : "type",
    "ephemeral_id" : "ephemeral_id",
    "version" : "version"
  },
  "name" : "name",
  "id" : "id",
  "state" : "state",
  "type" : "type",
  "ephemeral_id" : "ephemeral_id",
  "version" : "version",
  "target" : {
    "environment" : "environment",
    "address" : "address",
    "name" : "name",
    "id" : "id",
    "state" : "state",
    "type" : "type",
    "ephemeral_id" : "ephemeral_id",
    "version" : "version"
  }
},
"organization" : {
  "name" : "name",
```

```
    "id" : "id"
  },
  "http" : {
    "request" : {
      "referrer" : "referrer",
      "method" : "method",
      "mime_type" : "mime_type",
      "bytes" : 6,
      "id" : "id",
      "body" : {
        "bytes" : 0,
        "content" : "content"
      }
    },
    "response" : {
      "status_code" : 4,
      "mime_type" : "mime_type",
      "bytes" : 4,
      "body" : {
        "bytes" : 1,
        "content" : "content"
      }
    },
    "version" : "version"
  },
  "tls" : {
    "cipher" : "cipher",
    "established" : true,
    "server" : {
      "not_after" : "2000-01-23T04:56:07.000+00:00",
      "ja3s" : "ja3s",
      "subject" : "subject",
      "not_before" : "2000-01-23T04:56:07.000+00:00",
      "certificate" : "certificate",
      "issuer" : "issuer",
      "certificate_chain" : [ "certificate_chain", "certificate_chain" ],
      "hash" : {
        "sha1" : "sha1",
        "sha256" : "sha256",
        "md5" : "md5"
      }
    },
    "curve" : "curve",
    "next_protocol" : "next_protocol",
    "client" : {
      "not_after" : "2000-01-23T04:56:07.000+00:00",
      "server_name" : "server_name",
      "supported_ciphers" : [ "supported_ciphers", "supported_ciphers" ],
      "subject" : "subject",
      "not_before" : "2000-01-23T04:56:07.000+00:00",
      "certificate" : "certificate",
      "ja3" : "ja3",
      "issuer" : "issuer",
```

```
    "certificate_chain" : [ "certificate_chain", "certificate_chain" ],
    "hash" : {
      "sha1" : "sha1",
      "sha256" : "sha256",
      "md5" : "md5"
    }
  },
  "resumed" : true,
  "version" : "version",
  "version_protocol" : "version_protocol"
},
"threat" : {
  "indicator" : {
    "first_seen" : "2000-01-23T04:56:07.000+00:00",
    "last_seen" : "2000-01-23T04:56:07.000+00:00",
    "confidence" : "confidence",
    "ip" : "ip",
    "sightings" : 4,
    "description" : "description",
    "type" : "type",
    "url" : {
      "extension" : "extension",
      "original" : "original",
      "scheme" : "scheme",
      "top_level_domain" : "top_level_domain",
      "query" : "query",
      "path" : "path",
      "registered_domain" : "registered_domain",
      "fragment" : "fragment",
      "password" : "password",
      "port" : 0,
      "domain" : "domain",
      "subdomain" : "subdomain",
      "full" : "full",
      "username" : "username"
    },
    "scanner_stats" : 2,
    "reference" : "reference",
    "marking" : {
      "tlp" : "tlp"
    },
    "port" : 9,
    "provider" : "provider",
    "modified_at" : "2000-01-23T04:56:07.000+00:00",
    "email" : {
      "address" : "address"
    }
  },
  "feed" : {
    "reference" : "reference",
    "name" : "name",
    "description" : "description",
    "dashboard_id" : "dashboard_id"
  }
}
```

```
    },
    "framework" : "framework",
    "software" : {
      "reference" : "reference",
      "name" : "name",
      "alias" : [ "alias", "alias" ],
      "id" : "id",
      "type" : "type",
      "platforms" : [ "platforms", "platforms" ]
    },
    "technique" : {
      "reference" : [ "reference", "reference" ],
      "name" : [ "name", "name" ],
      "subtechnique" : {
        "reference" : [ "reference", "reference" ],
        "name" : [ "name", "name" ],
        "id" : [ "id", "id" ]
      },
      "id" : [ "id", "id" ]
    },
    "enrichments" : [ {
      "indicator" : "indicator",
      "matched" : {
        "field" : "field",
        "occurred" : "2000-01-23T04:56:07.000+00:00",
        "atomic" : "atomic",
        "index" : "index",
        "id" : "id",
        "type" : "type"
      }
    }, {
      "indicator" : "indicator",
      "matched" : {
        "field" : "field",
        "occurred" : "2000-01-23T04:56:07.000+00:00",
        "atomic" : "atomic",
        "index" : "index",
        "id" : "id",
        "type" : "type"
      }
    } ],
    "group" : {
      "reference" : "reference",
      "name" : "name",
      "alias" : [ "alias", "alias" ],
      "id" : "id"
    },
    "tactic" : {
      "reference" : [ "reference", "reference" ],
      "name" : [ "name", "name" ],
      "id" : [ "id", "id" ]
    }
  },
},
```

```
"transaction" : {
  "id" : "id"
},
"span" : {
  "id" : "id"
}
}, {
  "container" : {
    "image" : {
      "name" : "name",
      "tag" : [ "tag", "tag" ],
      "hash" : {
        "all" : [ "all", "all" ]
      }
    },
    "disk" : {
      "read" : {
        "bytes" : 4
      },
      "write" : {
        "bytes" : 5
      }
    },
    "memory" : {
      "usage" : 9.965781217890562
    },
    "name" : "name",
    "cpu" : {
      "usage" : 1.1730742509559433
    },
    "runtime" : "runtime",
    "id" : "id",
    "labels" : "labels",
    "network" : {
      "ingress" : {
        "bytes" : 9
      },
      "egress" : {
        "bytes" : 6
      }
    }
  },
  "server" : {
    "nat" : {
      "port" : 7,
      "ip" : "ip"
    },
    "address" : "address",
    "top_level_domain" : "top_level_domain",
    "ip" : "ip",
    "mac" : "mac",
    "packets" : 0,
    "registered_domain" : "registered_domain",
```



```
"port" : 4,
"bytes" : 0,
"domain" : "domain",
"subdomain" : "subdomain"
},
"agent" : {
  "build" : {
    "original" : "original"
  },
  "name" : "name",
  "id" : "id",
  "type" : "type",
  "ephemeral_id" : "ephemeral_id",
  "version" : "version"
},
"faas" : {
  "execution" : "execution",
  "coldstart" : true,
  "name" : "name",
  "id" : "id",
  "trigger" : {
    "type" : "type",
    "request_id" : "request_id"
  },
  "version" : "version"
},
"log" : {
  "file" : {
    "path" : "path"
  },
  "level" : "level",
  "logger" : "logger",
  "origin" : {
    "file" : {
      "line" : 7,
      "name" : "name"
    },
    "function" : "function"
  },
  "syslog" : "syslog"
},
"destination" : {
  "nat" : {
    "port" : 3,
    "ip" : "ip"
  },
  "address" : "address",
  "top_level_domain" : "top_level_domain",
  "ip" : "ip",
  "mac" : "mac",
  "packets" : 6,
  "registered_domain" : "registered_domain",
  "port" : 8,
```

```
    "bytes" : 9,
    "domain" : "domain",
    "subdomain" : "subdomain"
  },
  "rule" : {
    "reference" : "reference",
    "license" : "license",
    "author" : [ "author", "author" ],
    "name" : "name",
    "ruleset" : "ruleset",
    "description" : "description",
    "id" : "id",
    "category" : "category",
    "uuid" : "uuid",
    "version" : "version"
  },
  "error" : {
    "code" : "code",
    "id" : "id",
    "stack_trace" : "stack_trace",
    "message" : "message",
    "type" : "type"
  },
  "network" : {
    "transport" : "transport",
    "type" : "type",
    "inner" : "inner",
    "packets" : 0,
    "protocol" : "protocol",
    "forwarded_ip" : "forwarded_ip",
    "community_id" : "community_id",
    "application" : "application",
    "vlan" : {
      "name" : "name",
      "id" : "id"
    },
    "bytes" : 9,
    "name" : "name",
    "iana_number" : "iana_number",
    "direction" : "direction"
  },
  "cloud" : {
    "availability_zone" : "availability_zone",
    "instance" : {
      "name" : "name",
      "id" : "id"
    },
    "provider" : "provider",
    "machine" : {
      "type" : "type"
    },
    "service" : {
      "name" : "name"
    }
  }
}
```

```
    },
    "origin" : {
      "availability_zone" : "availability_zone",
      "provider" : "provider",
      "region" : "region"
    },
    "project" : {
      "name" : "name",
      "id" : "id"
    },
    "region" : "region",
    "account" : {
      "name" : "name",
      "id" : "id"
    },
    "target" : {
      "availability_zone" : "availability_zone",
      "provider" : "provider",
      "region" : "region"
    }
  },
  "observer" : {
    "product" : "product",
    "ip" : [ "ip", "ip" ],
    "serial_number" : "serial_number",
    "type" : "type",
    "version" : "version",
    "mac" : [ "mac", "mac" ],
    "egress" : "egress",
    "ingress" : "ingress",
    "hostname" : "hostname",
    "vendor" : "vendor",
    "name" : "name"
  },
  "trace" : {
    "id" : "id"
  },
  "file" : {
    "extension" : "extension",
    "SourceUrl" : "SourceUrl",
    "Owner" : {
      "Identifier" : "Identifier",
      "DomainName" : "DomainName",
      "DomainNetBIOSName" : "DomainNetBIOSName",
      "Name" : "Name",
      "DomainIdentifier" : "DomainIdentifier"
    },
    "gid" : "gid",
    "Description" : "Description",
    "drive_letter" : "drive_letter",
    "ProductVersion" : "ProductVersion",
    "type" : "type",
    "mtime" : "2000-01-23T04:56:07.000+00:00",
```

```
"accessed" : "2000-01-23T04:56:07.000+00:00",
"directory" : "directory",
"inode" : "inode",
"mode" : "mode",
"path" : "path",
"uid" : "uid",
"Version" : "Version",
"ctime" : "2000-01-23T04:56:07.000+00:00",
"fork_name" : "fork_name",
"elf" : {
  "imports" : {
    "key" : "imports"
  },
  "shared_libraries" : [ "shared_libraries", "shared_libraries" ],
  "byte_order" : "byte_order",
  "exports" : {
    "key" : "exports"
  },
  "cpu_type" : "cpu_type",
  "header" : {
    "object_version" : "object_version",
    "data" : "data",
    "os_abi" : "os_abi",
    "entrypoint" : 7,
    "abi_version" : "abi_version",
    "type" : "type",
    "class" : "class",
    "version" : "version"
  },
  "creation_date" : "2000-01-23T04:56:07.000+00:00",
  "sections" : [ {
    "chi2" : 4,
    "virtual_address" : 7,
    "entropy" : 0,
    "physical_offset" : "physical_offset",
    "flags" : "flags",
    "name" : "name",
    "physical_size" : 0,
    "type" : "type",
    "virtual_size" : 6
  }, {
    "chi2" : 4,
    "virtual_address" : 7,
    "entropy" : 0,
    "physical_offset" : "physical_offset",
    "flags" : "flags",
    "name" : "name",
    "physical_size" : 0,
    "type" : "type",
    "virtual_size" : 6
  } ],
  "telfhash" : "telfhash",
  "architecture" : "architecture",
```

```
"segments" : [ {
  "type" : "type",
  "sections" : "sections"
}, {
  "type" : "type",
  "sections" : "sections"
} ]
},
"group" : "group",
"owner" : "owner",
"created" : "2000-01-23T04:56:07.000+00:00",
"Bundle" : {
  "Type" : "Type",
  "DownloadSource" : "DownloadSource",
  "Version" : "Version",
  "InfoDescription" : "InfoDescription",
  "Creator" : "Creator",
  "Uri" : "Uri",
  "Name" : "Name"
},
"target_path" : "target_path",
"DriveType" : "DriveType",
"x509" : {
  "not_after" : "2000-01-23T04:56:07.000+00:00",
  "public_key_exponent" : 3,
  "not_before" : "2000-01-23T04:56:07.000+00:00",
  "subject" : {
    "state_or_province" : [ "state_or_province", "state_or_province" ],
    "country" : [ "country", "country" ],
    "organization" : [ "organization", "organization" ],
    "distinguished_name" : "distinguished_name",
    "locality" : [ "locality", "locality" ],
    "common_name" : [ "common_name", "common_name" ],
    "organizational_unit" : [ "organizational_unit", "organizational_unit" ]
  },
  "public_key_algorithm" : "public_key_algorithm",
  "public_key_curve" : "public_key_curve",
  "signature_algorithm" : "signature_algorithm",
  "version_number" : "version_number",
  "serial_number" : "serial_number",
  "public_key_size" : 3,
  "alternative_names" : [ "alternative_names", "alternative_names" ],
  "issuer" : {
    "state_or_province" : [ "state_or_province", "state_or_province" ],
    "country" : [ "country", "country" ],
    "organization" : [ "organization", "organization" ],
    "distinguished_name" : "distinguished_name",
    "locality" : [ "locality", "locality" ],
    "common_name" : [ "common_name", "common_name" ],
    "organizational_unit" : [ "organizational_unit", "organizational_unit" ]
  }
},
"size" : 6,
```

```
"mime_type" : "mime_type",
"ZoneTag" : "ZoneTag",
"name" : "name",
"attributes" : [ "attributes", "attributes" ],
"device" : "device"
},
"ecs" : {
  "version" : "version"
},
"related" : {
  "hosts" : [ "hosts", "hosts" ],
  "ip" : [ "ip", "ip" ],
  "user" : [ "user", "user" ],
  "hash" : [ "hash", "hash" ]
},
"host" : {
  "DefaultUILanguage" : "DefaultUILanguage",
  "os" : {
    "kernel" : "kernel",
    "name" : "name",
    "ProductType" : "ProductType",
    "type" : "type",
    "family" : "family",
    "version" : "version",
    "platform" : "platform",
    "full" : "full"
  },
  "DomainNetBIOSName" : "DomainNetBIOSName",
  "ip" : [ "ip", "ip" ],
  "cpu" : {
    "usage" : 7.740351818741173
  },
  "pid_ns_ino" : "pid_ns_ino",
  "type" : "type",
  "mac" : [ "mac", "mac" ],
  "uptime" : 8,
  "network" : {
    "ingress" : {
      "bytes" : 7,
      "packets" : 5
    },
    "egress" : {
      "bytes" : 3,
      "packets" : 4
    }
  },
  "DefaultLocale" : "DefaultLocale",
  "hostname" : "hostname",
  "disk" : {
    "read" : {
      "bytes" : 3
    },
    "write" : {
```

```
        "bytes" : 3
      }
    },
    "ClientName" : "ClientName",
    "domain" : "domain",
    "NetBIOSName" : "NetBIOSName",
    "name" : "name",
    "id" : "id",
    "ChassisType" : "ChassisType",
    "boot" : {
      "id" : "id"
    },
    "architecture" : "architecture",
    "DomainIdentifier" : "DomainIdentifier"
  },
  "client" : {
    "nat" : {
      "port" : 5,
      "ip" : "ip"
    },
    "address" : "address",
    "top_level_domain" : "top_level_domain",
    "ip" : "ip",
    "mac" : "mac",
    "packets" : 5,
    "geo" : {
      "continent_name" : "continent_name",
      "region_iso_code" : "region_iso_code",
      "city_name" : "city_name",
      "country_iso_code" : "country_iso_code",
      "timezone" : "timezone",
      "country_name" : "country_name",
      "name" : "name",
      "continent_code" : "continent_code",
      "location" : {
        "lon" : 7.061401241503109,
        "lat" : 9.301444243932576
      },
      "region_name" : "region_name",
      "postal_code" : "postal_code",
      "TimezoneOffset" : 3
    },
    "registered_domain" : "registered_domain",
    "as" : {
      "number" : 2,
      "organization" : {
        "name" : "name"
      }
    }
  },
  "port" : 6,
  "bytes" : 1,
  "domain" : "domain",
  "subdomain" : "subdomain",
```

```
"user" : {
  "DefaultUILanguage" : "DefaultUILanguage",
  "DomainNetBIOSName" : "DomainNetBIOSName",
  "roles" : [ "roles", "roles" ],
  "changes" : {
    "DefaultUILanguage" : "DefaultUILanguage",
    "DomainNetBIOSName" : "DomainNetBIOSName",
    "roles" : [ "roles", "roles" ],
    "LocalIdentifier" : 7,
    "DefaultTimezoneOffset" : 6,
    "DefaultLocale" : "DefaultLocale",
    "full_name" : "full_name",
    "domain" : "domain",
    "name" : "name",
    "id" : "id",
    "email" : "email",
    "hash" : "hash",
    "DomainIdentifier" : "DomainIdentifier"
  },
  "LocalIdentifier" : 4,
  "target" : {
    "DefaultUILanguage" : "DefaultUILanguage",
    "DomainNetBIOSName" : "DomainNetBIOSName",
    "roles" : [ "roles", "roles" ],
    "LocalIdentifier" : 1,
    "DefaultTimezoneOffset" : 7,
    "DefaultLocale" : "DefaultLocale",
    "full_name" : "full_name",
    "domain" : "domain",
    "name" : "name",
    "id" : "id",
    "email" : "email",
    "hash" : "hash",
    "DomainIdentifier" : "DomainIdentifier"
  },
  "DefaultTimezoneOffset" : 2,
  "DefaultLocale" : "DefaultLocale",
  "effective" : {
    "DefaultUILanguage" : "DefaultUILanguage",
    "DomainNetBIOSName" : "DomainNetBIOSName",
    "roles" : [ "roles", "roles" ],
    "LocalIdentifier" : 1,
    "DefaultTimezoneOffset" : 1,
    "DefaultLocale" : "DefaultLocale",
    "full_name" : "full_name",
    "domain" : "domain",
    "name" : "name",
    "id" : "id",
    "email" : "email",
    "hash" : "hash",
    "DomainIdentifier" : "DomainIdentifier"
  },
  "full_name" : "full_name",
```



```
    "domain" : "domain",
    "name" : "name",
    "id" : "id",
    "email" : "email",
    "hash" : "hash",
    "DomainIdentifier" : "DomainIdentifier",
    "group" : {
      "domain" : "domain",
      "name" : "name",
      "id" : "id"
    }
  }
},
"event" : {
  "reason" : "reason",
  "code" : "code",
  "timezone" : "timezone",
  "type" : [ "type", "type" ],
  "duration" : 2,
  "reference" : "reference",
  "agent_id_status" : "agent_id_status",
  "ingested" : "2000-01-23T04:56:07.000+00:00",
  "provider" : "provider",
  "action" : "action",
  "end" : "2000-01-23T04:56:07.000+00:00",
  "id" : "id",
  "outcome" : "outcome",
  "severity" : 1,
  "original" : "original",
  "risk_score" : 6.878052220127876,
  "kind" : "kind",
  "created" : "2000-01-23T04:56:07.000+00:00",
  "module" : "module",
  "start" : "2000-01-23T04:56:07.000+00:00",
  "url" : "url",
  "sequence" : 6,
  "risk_score_norm" : 5.944895607614016,
  "category" : [ "category", "category" ],
  "dataset" : "dataset",
  "hash" : "hash"
},
"email" : {
  "cc" : {
    "address" : [ "address", "address" ]
  },
  "origination_timestamp" : "2000-01-23T04:56:07.000+00:00",
  "attachments" : [ {
    "file" : {
      "extension" : "extension",
      "size" : 6,
      "mime_type" : "mime_type",
      "name" : "name"
    }
  }
}
```

```
    }, {
      "file" : {
        "extension" : "extension",
        "size" : 6,
        "mime_type" : "mime_type",
        "name" : "name"
      }
    } ],
    "bcc" : {
      "address" : [ "address", "address" ]
    },
    "local_id" : "local_id",
    "subject" : "subject",
    "message_id" : "message_id",
    "x_mailer" : "x_mailer",
    "content_type" : "content_type",
    "reply_to" : {
      "address" : [ "address", "address" ]
    },
    "sender" : {
      "address" : "address"
    },
    "delivery_timestamp" : "2000-01-23T04:56:07.000+00:00",
    "from" : {
      "address" : [ "address", "address" ]
    },
    "to" : {
      "address" : [ "address", "address" ]
    },
    "direction" : "direction"
  },
  "user_agent" : {
    "original" : "original",
    "name" : "name",
    "version" : "version",
    "device" : {
      "name" : "name"
    }
  },
  "registry" : {
    "hive" : "hive",
    "path" : "path",
    "data" : {
      "strings" : [ "strings", "strings" ],
      "bytes" : "bytes",
      "type" : "type"
    },
    "value" : "value",
    "key" : "key"
  },
  "process" : {
    "parent" : {
      "ElevationRequired" : true,
```

```
"interactive" : true,
"pid" : 1,
"working_directory" : "working_directory",
"title" : "title",
"end" : "2000-01-23T04:56:07.000+00:00",
"same_as_process" : true,
"group_leader" : {
  "ElevationRequired" : true,
  "interactive" : true,
  "pid" : 9,
  "working_directory" : "working_directory",
  "title" : "title",
  "end" : "2000-01-23T04:56:07.000+00:00",
  "same_as_process" : true,
  "pgid" : 1,
  "start" : "2000-01-23T04:56:07.000+00:00",
  "entity_id" : "entity_id",
  "executable" : "executable",
  "uptime" : 9,
  "env_vars" : "env_vars",
  "args" : [ "args", "args" ],
  "name" : "name",
  "exit_code" : 8,
  "tty" : "tty",
  "args_count" : 3,
  "command_line" : "command_line"
},
"pgid" : 8,
"start" : "2000-01-23T04:56:07.000+00:00",
"entity_id" : "entity_id",
"executable" : "executable",
"uptime" : 4,
"env_vars" : "env_vars",
"args" : [ "args", "args" ],
"name" : "name",
"exit_code" : 8,
"tty" : "tty",
"args_count" : 6,
"command_line" : "command_line"
},
"ElevationRequired" : true,
"interactive" : true,
"pid" : 0,
"working_directory" : "working_directory",
"title" : "title",
"end" : "2000-01-23T04:56:07.000+00:00",
"same_as_process" : true,
"previous" : {
  "ElevationRequired" : true,
  "interactive" : true,
  "pid" : 0,
  "working_directory" : "working_directory",
  "title" : "title",
```

```
    "end" : "2000-01-23T04:56:07.000+00:00",
    "same_as_process" : true,
    "pgid" : 3,
    "start" : "2000-01-23T04:56:07.000+00:00",
    "entity_id" : "entity_id",
    "executable" : "executable",
    "uptime" : 3,
    "env_vars" : "env_vars",
    "args" : [ "args", "args" ],
    "name" : "name",
    "exit_code" : 8,
    "tty" : "tty",
    "args_count" : 2,
    "command_line" : "command_line"
  },
  "pgid" : 7,
  "start" : "2000-01-23T04:56:07.000+00:00",
  "entry_meta" : {
    "source" : {
      "nat" : {
        "port" : 2,
        "ip" : "ip"
      },
      "address" : "address",
      "top_level_domain" : "top_level_domain",
      "ip" : "ip",
      "mac" : "mac",
      "packets" : 0,
      "registered_domain" : "registered_domain",
      "port" : 4,
      "bytes" : 3,
      "domain" : "domain",
      "subdomain" : "subdomain"
    },
    "type" : "type"
  },
  "thread" : {
    "name" : "name",
    "id" : 4
  },
  "entity_id" : "entity_id",
  "executable" : "executable",
  "uptime" : 6,
  "env_vars" : "env_vars",
  "args" : [ "args", "args" ],
  "session_leader" : {
    "ElevationRequired" : true,
    "interactive" : true,
    "pid" : 3,
    "working_directory" : "working_directory",
    "title" : "title",
    "end" : "2000-01-23T04:56:07.000+00:00",
    "same_as_process" : true,
```

```
    "pgid" : 3,
    "start" : "2000-01-23T04:56:07.000+00:00",
    "entity_id" : "entity_id",
    "executable" : "executable",
    "uptime" : 5,
    "env_vars" : "env_vars",
    "args" : [ "args", "args" ],
    "name" : "name",
    "exit_code" : 7,
    "tty" : "tty",
    "args_count" : 9,
    "command_line" : "command_line"
  },
  "entry_leader" : {
    "ElevationRequired" : true,
    "interactive" : true,
    "pid" : 0,
    "working_directory" : "working_directory",
    "title" : "title",
    "end" : "2000-01-23T04:56:07.000+00:00",
    "same_as_process" : true,
    "pgid" : 5,
    "start" : "2000-01-23T04:56:07.000+00:00",
    "entity_id" : "entity_id",
    "executable" : "executable",
    "uptime" : 8,
    "env_vars" : "env_vars",
    "args" : [ "args", "args" ],
    "name" : "name",
    "exit_code" : 7,
    "tty" : "tty",
    "args_count" : 5,
    "command_line" : "command_line"
  },
  "name" : "name",
  "exit_code" : 8,
  "tty" : "tty",
  "args_count" : 5,
  "command_line" : "command_line"
},
"package" : {
  "installed" : "2000-01-23T04:56:07.000+00:00",
  "build_version" : "build_version",
  "description" : "description",
  "type" : "type",
  "version" : "version",
  "reference" : "reference",
  "path" : "path",
  "license" : "license",
  "install_scope" : "install_scope",
  "size" : 9,
  "name" : "name",
  "checksum" : "checksum",
```

```
    "architecture" : "architecture"
  },
  "dll" : {
    "path" : "path",
    "code_signature" : {
      "valid" : true,
      "digest_algorithm" : "digest_algorithm",
      "signing_id" : "signing_id",
      "trusted" : true,
      "subject_name" : "subject_name",
      "exists" : true,
      "team_id" : "team_id",
      "status" : "status",
      "timestamp" : "2000-01-23T04:56:07.000+00:00"
    },
    "pe" : {
      "file_version" : "file_version",
      "product" : "product",
      "imphash" : "imphash",
      "description" : "description",
      "original_file_name" : "original_file_name",
      "company" : "company",
      "pehash" : "pehash",
      "architecture" : "architecture"
    },
    "name" : "name",
    "hash" : {
      "sha1" : "sha1",
      "sha384" : "sha384",
      "sha256" : "sha256",
      "sha512" : "sha512",
      "tlsh" : "tlsh",
      "ssdeep" : "ssdeep",
      "md5" : "md5"
    }
  },
  "dns" : {
    "op_code" : "op_code",
    "response_code" : "response_code",
    "resolved_ip" : [ "resolved_ip", "resolved_ip" ],
    "question" : {
      "registered_domain" : "registered_domain",
      "top_level_domain" : "top_level_domain",
      "name" : "name",
      "subdomain" : "subdomain",
      "type" : "type",
      "class" : "class"
    },
    "answers" : "answers",
    "id" : "id",
    "header_flags" : [ "header_flags", "header_flags" ],
    "type" : "type"
  },
}
```

```
"vulnerability" : {
  "reference" : "reference",
  "severity" : "severity",
  "score" : {
    "environmental" : 4.8789878742268815,
    "version" : "version",
    "temporal" : 6.173804034172511,
    "base" : 2.535258963197524
  },
  "report_id" : "report_id",
  "scanner" : {
    "vendor" : "vendor"
  },
  "description" : "description",
  "id" : "id",
  "classification" : "classification",
  "enumeration" : "enumeration",
  "category" : [ "category", "category" ]
},
"message" : "message",
"tags" : [ "tags", "tags" ],
"labels" : "labels",
"orchestrator" : {
  "cluster" : {
    "name" : "name",
    "id" : "id",
    "version" : "version",
    "url" : "url"
  },
  "resource" : {
    "parent" : {
      "type" : "type"
    },
    "ip" : [ "ip", "ip" ],
    "name" : "name",
    "id" : "id",
    "type" : "type"
  },
  "organization" : "organization",
  "namespace" : "namespace",
  "type" : "type",
  "api_version" : "api_version"
},
"@timestamp" : "2000-01-23T04:56:07.000+00:00",
"EPMWinMac" : {
  "COM" : {
    "AppID" : "AppID",
    "CLSID" : "CLSID",
    "DisplayName" : "DisplayName"
  },
  "AuthorizingUser" : {
    "Identifier" : "Identifier",
    "DomainNetBIOSName" : "DomainNetBIOSName",
```

```
    "DomainName" : "DomainName",
    "Name" : "Name",
    "DomainIdentifier" : "DomainIdentifier",
    "CredentialSource" : "CredentialSource"
  },
  "PrivilegedGroup" : {
    "Access" : "Access",
    "RID" : "RID",
    "Name" : "Name"
  },
  "AuthorizationRequest" : {
    "AuthRequestURI" : "AuthRequestURI",
    "ControlAuthorization" : true
  },
  "SchemaVersion" : "SchemaVersion",
  "Configuration" : {
    "Path" : "Path",
    "Message" : {
      "Authorization" : {
        "ResponseStatus" : "ResponseStatus",
        "ChallengeCode" : "ChallengeCode"
      },
      "AuthMethods" : [ "AuthMethods", "AuthMethods" ],
      "Type" : "Type",
      "Description" : "Description",
      "Identifier" : "Identifier",
      "Authentication" : {
        "User" : "User"
      },
      "UserReason" : "UserReason",
      "Name" : "Name"
    },
    "GPO" : {
      "Version" : "Version",
      "DisplayName" : "DisplayName",
      "LinkInformation" : "LinkInformation",
      "ActiveDirectoryPath" : "ActiveDirectoryPath"
    },
    "LoadAuditMode" : [ "LoadAuditMode", "LoadAuditMode" ],
    "Token" : {
      "Description" : "Description",
      "Identifier" : "Identifier",
      "Name" : "Name"
    },
    "ContentGroup" : {
      "Description" : "Description",
      "Identifier" : "Identifier",
      "Name" : "Name"
    },
    "RuleScript" : {
      "Outcome" : {
        "Version" : "Version",
        "Output" : "Output",
```



```
    "RuleAffected" : true,
    "Name" : "Name",
    "Result" : "Result"
  },
  "FileName" : "FileName",
  "Publisher" : "Publisher"
},
"RevisionNumber" : "RevisionNumber",
"Workstyle" : {
  "Description" : "Description",
  "Identifier" : "Identifier",
  "Name" : "Name"
},
"Source" : "Source",
"Name" : "Name",
"ApplicationGroup" : {
  "Description" : "Description",
  "Identifier" : "Identifier",
  "Name" : "Name"
},
"Identifier" : "Identifier",
"Content" : {
  "Type" : "Type",
  "Description" : "Description",
  "Identifier" : "Identifier"
},
"SigningEnforcement" : "SigningEnforcement",
"Rule" : {
  "Action" : "Action",
  "Identifier" : "Identifier",
  "OnDemand" : true
},
"Application" : {
  "Type" : "Type",
  "Description" : "Description",
  "Identifier" : "Identifier"
}
},
"Installer" : {
  "Action" : "Action",
  "ProductCode" : "ProductCode",
  "UpgradeCode" : "UpgradeCode"
},
"ActiveX" : {
  "Version" : "Version",
  "CLSID" : "CLSID",
  "Codebase" : "Codebase"
},
"GroupId" : "GroupId",
"TenantId" : "TenantId",
"StoreApp" : {
  "Version" : "Version",
  "Publisher" : "Publisher",
```

```
    "Name" : "Name"
  },
  "ServiceControl" : {
    "Service" : {
      "DisplayName" : "DisplayName",
      "Name" : "Name"
    }
  },
  "TrustedApplication" : {
    "Version" : "Version",
    "Name" : "Name"
  },
  "Event" : {
    "Type" : "Type",
    "Action" : "Action"
  },
  "RemotePowerShell" : {
    "Command" : "Command"
  },
  "AdapterVersion" : "AdapterVersion",
  "Session" : {
    "Locale" : "Locale",
    "PowerUser" : true,
    "WindowsSessionId" : "WindowsSessionId",
    "Administrator" : true,
    "Identifier" : "Identifier",
    "UILanguage" : "UILanguage"
  }
},
"data_stream" : {
  "namespace" : "namespace",
  "type" : "type",
  "dataset" : "dataset"
},
"service" : {
  "node" : {
    "role" : "role",
    "name" : "name"
  },
  "environment" : "environment",
  "address" : "address",
  "origin" : {
    "environment" : "environment",
    "address" : "address",
    "name" : "name",
    "id" : "id",
    "state" : "state",
    "type" : "type",
    "ephemeral_id" : "ephemeral_id",
    "version" : "version"
  },
  "name" : "name",
  "id" : "id",
```

```
"state" : "state",
"type" : "type",
"ephemeral_id" : "ephemeral_id",
"version" : "version",
"target" : {
  "environment" : "environment",
  "address" : "address",
  "name" : "name",
  "id" : "id",
  "state" : "state",
  "type" : "type",
  "ephemeral_id" : "ephemeral_id",
  "version" : "version"
}
},
"organization" : {
  "name" : "name",
  "id" : "id"
},
"http" : {
  "request" : {
    "referrer" : "referrer",
    "method" : "method",
    "mime_type" : "mime_type",
    "bytes" : 6,
    "id" : "id",
    "body" : {
      "bytes" : 0,
      "content" : "content"
    }
  },
  "response" : {
    "status_code" : 4,
    "mime_type" : "mime_type",
    "bytes" : 4,
    "body" : {
      "bytes" : 1,
      "content" : "content"
    }
  },
  "version" : "version"
},
"tls" : {
  "cipher" : "cipher",
  "established" : true,
  "server" : {
    "not_after" : "2000-01-23T04:56:07.000+00:00",
    "ja3s" : "ja3s",
    "subject" : "subject",
    "not_before" : "2000-01-23T04:56:07.000+00:00",
    "certificate" : "certificate",
    "issuer" : "issuer",
    "certificate_chain" : [ "certificate_chain", "certificate_chain" ],
```

```
    "hash" : {
      "sha1" : "sha1",
      "sha256" : "sha256",
      "md5" : "md5"
    }
  },
  "curve" : "curve",
  "next_protocol" : "next_protocol",
  "client" : {
    "not_after" : "2000-01-23T04:56:07.000+00:00",
    "server_name" : "server_name",
    "supported_ciphers" : [ "supported_ciphers", "supported_ciphers" ],
    "subject" : "subject",
    "not_before" : "2000-01-23T04:56:07.000+00:00",
    "certificate" : "certificate",
    "ja3" : "ja3",
    "issuer" : "issuer",
    "certificate_chain" : [ "certificate_chain", "certificate_chain" ],
    "hash" : {
      "sha1" : "sha1",
      "sha256" : "sha256",
      "md5" : "md5"
    }
  },
  "resumed" : true,
  "version" : "version",
  "version_protocol" : "version_protocol"
},
"threat" : {
  "indicator" : {
    "first_seen" : "2000-01-23T04:56:07.000+00:00",
    "last_seen" : "2000-01-23T04:56:07.000+00:00",
    "confidence" : "confidence",
    "ip" : "ip",
    "sightings" : 4,
    "description" : "description",
    "type" : "type",
    "url" : {
      "extension" : "extension",
      "original" : "original",
      "scheme" : "scheme",
      "top_level_domain" : "top_level_domain",
      "query" : "query",
      "path" : "path",
      "registered_domain" : "registered_domain",
      "fragment" : "fragment",
      "password" : "password",
      "port" : 0,
      "domain" : "domain",
      "subdomain" : "subdomain",
      "full" : "full",
      "username" : "username"
    }
  }
},
```

```
"scanner_stats" : 2,
"reference" : "reference",
"marking" : {
  "tlp" : "tlp"
},
"port" : 9,
"provider" : "provider",
"modified_at" : "2000-01-23T04:56:07.000+00:00",
"email" : {
  "address" : "address"
}
},
"feed" : {
  "reference" : "reference",
  "name" : "name",
  "description" : "description",
  "dashboard_id" : "dashboard_id"
},
"framework" : "framework",
"software" : {
  "reference" : "reference",
  "name" : "name",
  "alias" : [ "alias", "alias" ],
  "id" : "id",
  "type" : "type",
  "platforms" : [ "platforms", "platforms" ]
},
"technique" : {
  "reference" : [ "reference", "reference" ],
  "name" : [ "name", "name" ],
  "subtechnique" : {
    "reference" : [ "reference", "reference" ],
    "name" : [ "name", "name" ],
    "id" : [ "id", "id" ]
  },
  "id" : [ "id", "id" ]
},
"enrichments" : [ {
  "indicator" : "indicator",
  "matched" : {
    "field" : "field",
    "occurred" : "2000-01-23T04:56:07.000+00:00",
    "atomic" : "atomic",
    "index" : "index",
    "id" : "id",
    "type" : "type"
  }
}, {
  "indicator" : "indicator",
  "matched" : {
    "field" : "field",
    "occurred" : "2000-01-23T04:56:07.000+00:00",
    "atomic" : "atomic",
```

```
    "index" : "index",
    "id" : "id",
    "type" : "type"
  }
} ],
"group" : {
  "reference" : "reference",
  "name" : "name",
  "alias" : [ "alias", "alias" ],
  "id" : "id"
},
"tactic" : {
  "reference" : [ "reference", "reference" ],
  "name" : [ "name", "name" ],
  "id" : [ "id", "id" ]
}
},
"transaction" : {
  "id" : "id"
},
"span" : {
  "id" : "id"
}
} ]
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **EpmEcsEventResponseModel**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

500

Server Error

File

 `get /v1/File/download/GetYamlApiDefinitionFile`

Get the API definition file in YAML format (v1FileDownloadGetYamlApiDefinitionFileGet)

Return type

String

Example data

Content-Type: application/json

```
""
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **String**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

Groups

 `post /v1/Groups/AutoAssignPolicyRevision`

Auto assign policy revision to the group (v1GroupsAutoAssignPolicyRevisionPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [AssignPolicyRevisionToGroupRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **UUID**

404

Not Found **ProblemDetails**

423

Client Error **ProblemDetails**



`get /v1/Groups`

Retrieves the list of Groups with pagination (sorting and filtering) (v1GroupsGet)

Query parameters

Sorts (optional)

Query Parameter —

Pagination.PageSize (optional)

Query Parameter — The number of records per page, for example 1. Shouldn't exceed 200. format: int32

Pagination.PageNumber (optional)

Query Parameter — The page number to retrieve from results, for example 1 format: int32

Filter.Id (optional)

Query Parameter — The Id of the group(Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

Filter.Name (optional)

Query Parameter — The name of the group

Filter.Description (optional)

Query Parameter — The description of the group

Filter.PolicyName (optional)

Query Parameter — The policy name of the group

Filter.PolicyRevisionStatus (optional)

Query Parameter — The policy revision status of the group

Filter.ComputerCount (optional)

Query Parameter — Number of computers in a group format: int32

Filter.ActiveComputers.Value (optional)

Query Parameter — Integer value for the filter, e.g. 100 format: int32

Filter.ActiveComputers.Operator (optional)

Query Parameter —

Filter.Created.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

Filter.Created.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Return type

[GroupListItemModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "policyName" : "policyName",
    "created" : "2000-01-23T04:56:07.000+00:00",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "description" : "description",
    "policyRevisionId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "revision" : 7,
    "computerCount" : 5,
    "activeComputers" : 2,
    "default" : true,
    "policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "name" : "name",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "locked" : true,
    "policyRevisionStatus" : "OnLatestPolicy"
  }, {
    "policyName" : "policyName",
    "created" : "2000-01-23T04:56:07.000+00:00",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "description" : "description",
    "policyRevisionId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "revision" : 7,
    "computerCount" : 5,
    "activeComputers" : 2,
    "default" : true,
    "policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "name" : "name",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
```

```
"locked" : true,  
  "policyRevisionStatus" : "OnLatestPolicy"  
} ],  
"pageSize" : 6,  
"totalRecordCount" : 1  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **GroupListItemModelPagedResponse**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

500

Server Error



`post /v1/Groups/{id}/AssignComputersByCsv`

assigns computers to the group by input of csv file (v1GroupsIdAssignComputersByCsvPost)

Path parameters

id (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- multipart/form-data

Form parameters

csvFile (optional)

Form Parameter — format: binary

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

201

Created **UUID**

404

Not Found **ProblemDetails**

423

Client Error **ProblemDetails**



```
post /v1/Groups/{id}/AssignComputers
```

assigns computers to the group (v1GroupsIdAssignComputersPost)

Path parameters

id (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [AssignComputersToGroupRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

201

Created **UUID**

404

Not Found **ProblemDetails**

423Client Error **ProblemDetails** `post /v1/Groups/{id}/AssignPolicyRevision`

Assigns policy revision to the group (v1GroupsIdAssignPolicyRevisionPost)

Path parameters

id (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [AssignPolicyRevisionToGroupRequest](#) (optional)**Body Parameter** —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`

- text/json

Responses

200

Success **UUID**

404

Not Found **ProblemDetails**

423

Client Error **ProblemDetails**



patch /v1/Groups/{id}/ClearPolicy

Clears policy from group (v1GroupsIdClearPolicyPatch)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

204

No Content **UUID**

404

Not Found **ProblemDetails**

423

Client Error **ProblemDetails**



```
delete /v1/Groups/{id}
```

Deletes group (v1GroupsIdDelete)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

204

No Content **UUID**

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



```
get /v1/Groups/{id}
```

Retrieves a detail of the group (v1GroupsIdGet)

Path parameters

id (required)

Path Parameter — format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success

401

Unauthorized **ProblemDetails**

404Not Found **ProblemDetails****patch /v1/Groups/{id}/MarkAsDefault**

Marks group as default (v1GroupsIdMarkAsDefaultPatch)

Path parameters

id (required)

Path Parameter — format: uuid**Return type**

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses**204**No Content **UUID****404**Not Found **ProblemDetails****423**Client Error **ProblemDetails**

`post /v1/Groups`

Creates Group (v1GroupsPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [CreateGroupRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: `application/json`

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

201

Created **UUID**

409

Conflict **ProblemDetails**

 `put /v1/Groups`

Modifies Group (v1GroupsPut)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ModifyGroupRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

204

No Content **UUID**

404

Not Found **ProblemDetails**

409Conflict **ProblemDetails****423**Client Error **ProblemDetails****post /v1/Groups/UnassignComputers**

Unassigns computers from the groups (v1GroupsUnassignComputersPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request bodybody [UnassignComputersToGroupRequest](#) (optional)**Body Parameter** —**Return type**

array[UUID]

Example data

Content-Type: application/json

```
[ "046b6c7f-0b8a-43b9-b35d-6489e6daee91", "046b6c7f-0b8a-43b9-b35d-6489e6daee91" ]
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

202

Accepted

204

No Content

404

Not Found **ProblemDetails**

423

Client Error **ProblemDetails**

Policies



`get /v1/Policies`

Retrieve list of Policies with pagination (sorting and filtering) (v1PoliciesGet)

Query parameters

Sorts (optional)

Query Parameter —

Pagination.PageSize (optional)

Query Parameter — The number of records per page, for example 1. Shouldn't exceed 200. format: int32

Pagination.PageNumber (optional)

Query Parameter — The page number to retrieve from results, for example 1 format: int32

Filter.Name (optional)

Query Parameter — The Name of the Policy, e.g. - Policy1

Filter.Size (optional)

Query Parameter — The Size of the Policy in Kb, e.g. 225 format: int32

Filter.Revision (optional)

Query Parameter — The number of revisions for the Policy, e.g. 5 format: int32

Filter.TotalAssignedRevisions (optional)

Query Parameter — The total number of Groups with the Policy assigned (any Revision), e.g. 10 format: int32

Filter.Created.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

Filter.Created.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.DraftUser (optional)

Query Parameter — The 'Locked By' user, i.e. the user that created the last draft which has locked the Policy, e.g. jbloggs@email.com

Return type

[PolicyListItemModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "latestAssignedRevisions" : 3,
    "created" : "2000-01-23T04:56:07.000+00:00",
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "description" : "description",
    "hasOpenDraft" : true,
    "periodLocked" : "periodLocked",
    "revision" : 2,
    "totalAssignedRevisions" : 9,
    "totalRevisions" : 7,
    "openDraftId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "checkedOutDate" : "2000-01-23T04:56:07.000+00:00",
    "isAssignedToGroup" : true,
    "size" : 5,
    "draftUserId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "name" : "name",
    "lastModifiedUserId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "lastModifiedUser" : "lastModifiedUser",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "lastModified" : "2000-01-23T04:56:07.000+00:00",
    "draftUser" : "draftUser",
    "locked" : true,
    "lastPolicyToGroupAssignment" : "2000-01-23T04:56:07.000+00:00"
  }, {
```

```
"latestAssignedRevisions" : 3,
"created" : "2000-01-23T04:56:07.000+00:00",
"errorInfo" : {
  "userAccountName" : "userAccountName",
  "parentTaskName" : "parentTaskName",
  "initiated" : "2000-01-23T04:56:07.000+00:00",
  "errorCode" : 0,
  "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
},
"description" : "description",
"hasOpenDraft" : true,
"periodLocked" : "periodLocked",
"revision" : 2,
"totalAssignedRevisions" : 9,
"totalRevisions" : 7,
"openDraftId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"checkedOutDate" : "2000-01-23T04:56:07.000+00:00",
"isAssignedToGroup" : true,
"size" : 5,
"draftUserId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"name" : "name",
"lastModifiedUserId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"lastModifiedUser" : "lastModifiedUser",
"id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"lastModified" : "2000-01-23T04:56:07.000+00:00",
"draftUser" : "draftUser",
"locked" : true,
"lastPolicyToGroupAssignment" : "2000-01-23T04:56:07.000+00:00"
} ],
"pageSize" : 6,
"totalRecordCount" : 1
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **PolicyListItemModelPagedResponse**

400

Bad Request **ProblemDetails**

401Unauthorized **ProblemDetails****500**

Server Error

**get /v1/Policies/{id}/AssignedGroups**

Retrieves list of Groups that are assigned to Policy (v1PoliciesIdAssignedGroupsGet)

Path parameters

id (required)

Path Parameter — format: uuid**Return type**array[[PolicyGroupsListItemModel](#)]**Example data**

Content-Type: application/json

```
[ {
  "isDefault" : true,
  "policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "name" : "name",
  "description" : "description",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "policyRevisionId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
}, {
  "isDefault" : true,
  "policyId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "name" : "name",
  "description" : "description",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "policyRevisionId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
} ]
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**



```
get /v1/Policies/{id}/Content
```

Downloads Latest Policy Revision (v1PoliciesIdContentGet)

Path parameters

id (required)

Path Parameter — format: uuid

Produces


This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

404

Not Found **ProblemDetails**

 `delete /v1/Policies/{id}`

Deletes policy (v1PoliciesIdDelete)

Path parameters

id (required)

Path Parameter — format: uuid

Query parameters

forceDelete (optional)

Query Parameter —

Return type

UUID

Example data

Content-Type: application/json

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

201

Created **UUID**

404

Not Found **ProblemDetails**

409Conflict **ProblemDetails****423**Client Error **ProblemDetails****patch /v1/Policies/{id}/DiscardDraft**

Reverts and discards policy changes (v1PoliciesIdDiscardDraftPatch)

Path parameters

id (required)

Path Parameter — Policy identifier format: uuid**Produces**

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses**204**

No Content

404Not Found **ProblemDetails****409**Conflict **ProblemDetails****423**Client Error **ProblemDetails**

 `get /v1/Policies/{id}`

Retrieves a detail of the policy (v1PoliciesIdGet)

Path parameters

id (required)

Path Parameter — format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

 `put /v1/Policies/{id}`

Request to update policy properties (v1PoliciesIdPut)

Path parameters

id (required)

Path Parameter — PolicyId format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request body

body [ModifyPolicyRequest](#) (optional)

Body Parameter — policy properties

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

204

No Content

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



```
get /v1/Policies/{id}/Revisions
```

Retrieves list of policy revisions (v1PoliciesIdRevisionsGet)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

array[[PolicyRevisionModel](#)]

Example data

Content-Type: application/json

```
[ {
  "size" : 6,
  "created" : "2000-01-23T04:56:07.000+00:00",
  "isAssignedGroup" : true,
  "comment" : "comment",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "user" : "user",
  "revision" : 0
}, {
  "size" : 6,
  "created" : "2000-01-23T04:56:07.000+00:00",
  "isAssignedGroup" : true,
  "comment" : "comment",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "user" : "user",
  "revision" : 0
} ]
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

 `get /v1/Policies/PolicyRevision/{policyRevisionId}/Content`

Downloads Policy Revision (v1PoliciesPolicyRevisionPolicyRevisionIdContentGet)

Path parameters

policyRevisionId (required)

Path Parameter — format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

404

Not Found **ProblemDetails**

Roles

 `get /v1/Roles`

Retrieve list of Roles (v1RolesGet)

Return type

array[[RoleListItemModel](#)]

Example data

Content-Type: application/json

```
[ {  
  "name" : "name",  
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
```



```
"allowPermissions" : [ {
  "resource" : "resource",
  "action" : "action"
}, {
  "resource" : "resource",
  "action" : "action"
} ],
"denyPermissions" : [ null, null ]
}, {
  "name" : "name",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "allowPermissions" : [ {
    "resource" : "resource",
    "action" : "action"
  }, {
    "resource" : "resource",
    "action" : "action"
  } ],
  "denyPermissions" : [ null, null ]
} ]
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

500

Server Error

 `get /v1/Roles/{id}`

Retrieve role details (v1RolesIdGet)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

[RoleModel](#)

Example data

Content-Type: application/json

```
{
  "name" : "name",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "allowPermissions" : [ {
    "resource" : "resource",
    "action" : "action"
  }, {
    "resource" : "resource",
    "action" : "action"
  } ],
  "denyPermissions" : [ null, null ]
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **RoleModel**

400Bad Request **ProblemDetails****401**Unauthorized **ProblemDetails****500**

Server Error

ScimResourceTypes

 `get /scim/v2/ResourceTypes`

gets types of resources available (scimV2ResourceTypesGet)

Query parameters

api-version (optional)

Query Parameter —

Return type

[ScimResourceResponseScimListResponse](#)

Example data

Content-Type: application/json

```
{
  "totalResults" : 0,
  "startIndex" : 6,
  "itemsPerPage" : 1,
  "schemas" : [ "schemas", "schemas" ],
  "Resources" : [ {
    "schema" : "schema",
    "endpoint" : "endpoint",
    "meta" : {
      "resourceType" : "resourceType"
    }
  },
  "schemas" : [ "schemas", "schemas" ],
  "name" : "name",
```

```

        "description" : "description"
    }, {
        "schema" : "schema",
        "endpoint" : "endpoint",
        "meta" : {
            "resourceType" : "resourceType"
        },
        "schemas" : [ "schemas", "schemas" ],
        "name" : "name",
        "description" : "description"
    } ]
}
    
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success **ScimResourceResponseScimListResponse**



get /scim/v2/ResourceTypes/User

gets types of resources available (scimV2ResourceTypesUserGet)

Query parameters

api-version (optional)

Query Parameter —

Return type

[ScimResourceResponse](#)

Example data

Content-Type: application/json

```
{
  "schema" : "schema",
  "endpoint" : "endpoint",
  "meta" : {
    "resourceType" : "resourceType"
  },
  "schemas" : [ "schemas", "schemas" ],
  "name" : "name",
  "description" : "description"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success **ScimResourceResponse**

ScimSchemas



`get /scim/v2/Schemas`

Get the Schema supported by the SCIM Api (scimV2SchemasGet)

Query parameters

api-version (optional)

Query Parameter —

Return type

[ScimSchemaResponseScimListResponse](#)

Example data

Content-Type: application/json

```
{
  "totalResults" : 0,
  "startIndex" : 6,
  "itemsPerPage" : 1,
  "schemas" : [ "schemas", "schemas" ],
  "Resources" : [ {
    "meta" : {
      "resourceType" : "resourceType"
    },
    "schemas" : [ "schemas", "schemas" ],
    "name" : "name",
    "description" : "description",
    "attributes" : [ {
      "uniqueness" : "uniqueness",
      "name" : "name",
      "description" : "description",
      "mutability" : "mutability",
      "type" : "type",
      "caseExact" : true,
      "multiValued" : true,
      "returned" : "returned",
      "required" : true,
      "subAttributes" : [ {
        "uniqueness" : "uniqueness",
        "name" : "name",
        "description" : "description",
        "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
        "mutability" : "mutability",
        "type" : "type",
        "caseExact" : true,
        "multiValued" : true,
        "returned" : "returned",
        "required" : true
      }, {
        "uniqueness" : "uniqueness",
        "name" : "name",
        "description" : "description",
        "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
        "mutability" : "mutability",
        "type" : "type",
        "caseExact" : true,
        "multiValued" : true,
        "returned" : "returned",
        "required" : true
      } ]
    } ]
  }, {
    "uniqueness" : "uniqueness",
    "name" : "name",
    "description" : "description",
    "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
    "mutability" : "mutability",
    "type" : "type",
    "caseExact" : true,
    "multiValued" : true,
    "returned" : "returned",
    "required" : true
  } ]
}
```

```
"mutability" : "mutability",
"type" : "type",
"caseExact" : true,
"multiValued" : true,
"returned" : "returned",
"required" : true,
"subAttributes" : [ {
  "uniqueness" : "uniqueness",
  "name" : "name",
  "description" : "description",
  "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
  "mutability" : "mutability",
  "type" : "type",
  "caseExact" : true,
  "multiValued" : true,
  "returned" : "returned",
  "required" : true
}, {
  "uniqueness" : "uniqueness",
  "name" : "name",
  "description" : "description",
  "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
  "mutability" : "mutability",
  "type" : "type",
  "caseExact" : true,
  "multiValued" : true,
  "returned" : "returned",
  "required" : true
} ]
} ],
"id" : "id"
}, {
  "meta" : {
    "resourceType" : "resourceType"
  },
  "schemas" : [ "schemas", "schemas" ],
  "name" : "name",
  "description" : "description",
  "attributes" : [ {
    "uniqueness" : "uniqueness",
    "name" : "name",
    "description" : "description",
    "mutability" : "mutability",
    "type" : "type",
    "caseExact" : true,
    "multiValued" : true,
    "returned" : "returned",
    "required" : true,
    "subAttributes" : [ {
      "uniqueness" : "uniqueness",
      "name" : "name",
      "description" : "description",
      "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
```

```
    "mutability" : "mutability",
    "type" : "type",
    "caseExact" : true,
    "multiValued" : true,
    "returned" : "returned",
    "required" : true
  }, {
    "uniqueness" : "uniqueness",
    "name" : "name",
    "description" : "description",
    "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
    "mutability" : "mutability",
    "type" : "type",
    "caseExact" : true,
    "multiValued" : true,
    "returned" : "returned",
    "required" : true
  } ]
}, {
  "uniqueness" : "uniqueness",
  "name" : "name",
  "description" : "description",
  "mutability" : "mutability",
  "type" : "type",
  "caseExact" : true,
  "multiValued" : true,
  "returned" : "returned",
  "required" : true,
  "subAttributes" : [ {
    "uniqueness" : "uniqueness",
    "name" : "name",
    "description" : "description",
    "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
    "mutability" : "mutability",
    "type" : "type",
    "caseExact" : true,
    "multiValued" : true,
    "returned" : "returned",
    "required" : true
  }, {
    "uniqueness" : "uniqueness",
    "name" : "name",
    "description" : "description",
    "canonicalValues" : [ "canonicalValues", "canonicalValues" ],
    "mutability" : "mutability",
    "type" : "type",
    "caseExact" : true,
    "multiValued" : true,
    "returned" : "returned",
    "required" : true
  } ]
} ],
"id" : "id"
```



```
} ]  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200

Success **ScimSchemaResponseScimListResponse**

ScimServiceProviderConfig



```
get /scim/v2/ServiceProviderConfig
```

gets the Json structure available (scimV2ServiceProviderConfigGet)

Query parameters

api-version (optional)

Query Parameter —

Return type

[ScimServiceProviderConfigResponse](#)

Example data

Content-Type: application/json

```
{  
  "patch" : {  
    "supported" : true  
  },  
}
```

```

"authenticationSchemes" : {
  "name" : "name",
  "description" : "description",
  "type" : "type",
  "primary" : true
},
"meta" : {
  "resourceType" : "resourceType"
},
"schemas" : [ "schemas", "schemas" ],
"bulk" : {
  "maxPayloadSize" : 6,
  "maxOperations" : 0,
  "supported" : true
}
}
    
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **ScimServiceProviderConfigResponse**

ScimUsers



`get /scim/v2/Users`

(scimV2UsersGet)

Query parameters

filter (optional)

Query Parameter —

startIndex (optional)

Query Parameter — format: int32

count (optional)

Query Parameter — format: int32

api-version (optional)

Query Parameter —

Return type

[ScimUserModelScimListResponse](#)

Example data

Content-Type: application/json

```
{
  "totalResults" : 0,
  "startIndex" : 6,
  "itemsPerPage" : 1,
  "schemas" : [ "schemas", "schemas" ],
  "Resources" : [ {
    "entitlements" : [ null, null ],
    "displayName" : "displayName",
    "timezone" : "timezone",
    "roles" : [ {
      "value" : "value",
      "primary" : true
    }, {
      "value" : "value",
      "primary" : true
    } ],
    "externalId" : "externalId",
    "groups" : [ "", "" ],
    "active" : true,
    "userName" : "userName",
    "locale" : "locale",
    "emails" : [ {
      "type" : "type",
      "value" : "value",
      "primary" : true
    }, {
      "type" : "type",
      "value" : "value",
      "primary" : true
    } ],
    "password" : "password",
    "dateTimeFormat" : "dateTimeFormat",
    "meta" : {
      "created" : "2000-01-23T04:56:07.000+00:00",
      "resourceType" : "resourceType"
    },
    "schemas" : [ "schemas", "schemas" ],
```

```
    "name" : {
      "givenName" : "givenName",
      "familyName" : "familyName",
      "middleName" : "middleName"
    },
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
  }, {
    "entitlements" : [ null, null ],
    "displayName" : "displayName",
    "timezone" : "timezone",
    "roles" : [ {
      "value" : "value",
      "primary" : true
    }, {
      "value" : "value",
      "primary" : true
    } ],
    "externalId" : "externalId",
    "groups" : [ "", "" ],
    "active" : true,
    "userName" : "userName",
    "locale" : "locale",
    "emails" : [ {
      "type" : "type",
      "value" : "value",
      "primary" : true
    }, {
      "type" : "type",
      "value" : "value",
      "primary" : true
    } ],
    "password" : "password",
    "dateTimeFormat" : "dateTimeFormat",
    "meta" : {
      "created" : "2000-01-23T04:56:07.000+00:00",
      "resourceType" : "resourceType"
    },
    "schemas" : [ "schemas", "schemas" ],
    "name" : {
      "givenName" : "givenName",
      "familyName" : "familyName",
      "middleName" : "middleName"
    },
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
  } ]
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**

- text/json

Responses

200

Success **ScimUserModelScimListResponse**



`post /scim/v2/Users`

(scimV2UsersPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request body

body [ScimUserModel](#) (optional)

Body Parameter —

Query parameters

api-version (optional)

Query Parameter —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

201

Created

404Not Found **ProblemDetails****409**Conflict **ProblemDetails** `get /scim/v2/Users/{userID}`

(scimV2UsersUserIDGet)

Path parameters

userID (required)

Path Parameter — format: uuid**Query parameters**

api-version (optional)

Query Parameter —**Return type**[ScimUserModel](#)**Example data**

Content-Type: application/json

```
{
  "entitlements" : [ null, null ],
  "displayName" : "displayName",
  "timezone" : "timezone",
  "roles" : [ {
    "value" : "value",
    "primary" : true
  }, {
    "value" : "value",
    "primary" : true
  } ],
  "externalId" : "externalId",
  "groups" : [ "", "" ],
  "active" : true,
```

```
"userName" : "userName",
"locale" : "locale",
"emails" : [ {
  "type" : "type",
  "value" : "value",
  "primary" : true
}, {
  "type" : "type",
  "value" : "value",
  "primary" : true
} ],
"password" : "password",
"dateTimeFormat" : "dateTimeFormat",
"meta" : {
  "created" : "2000-01-23T04:56:07.000+00:00",
  "resourceType" : "resourceType"
},
"schemas" : [ "schemas", "schemas" ],
"name" : {
  "givenName" : "givenName",
  "familyName" : "familyName",
  "middleName" : "middleName"
},
"id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **ScimUserModel**

404

Not Found **ProblemDetails**



patch /scim/v2/Users/{userID}

Patch operation (scimV2UsersUserIDPatch)

Path parameters

userID (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- **application/json**
- **text/json**
- **application/*+json**

Request body

body [ScimUserPatchRequest](#) (optional)

Body Parameter —

Query parameters

api-version (optional)

Query Parameter —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success

404

Not Found **ProblemDetails**

423

Client Error **ProblemDetails**

 `put /scim/v2/Users/{userID}`

Modify a user (scimV2UsersUserIDPut)

Path parameters

userID (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json
- text/json
- application/*+json

Request body

body [ScimUserModel](#) (optional)

Body Parameter —

Query parameters

api-version (optional)

Query Parameter —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

200


Success

404

Not Found **ProblemDetails**

409Conflict **ProblemDetails****423**Client Error **ProblemDetails**

Tasks

 `get /v1/Tasks/{id}`

Retrieves a detail of the Task (v1TaskIdGet)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

[TaskDetailModel](#)

Example data

Content-Type: application/json

```
{
  "initiated" : "2000-01-23T04:56:07.000+00:00",
  "messageParameters" : [ {
    "key" : "messageParameters"
  }, {
    "key" : "messageParameters"
  } ],
  "stateName" : "stateName",
  "tenantId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "name" : "name",
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "state" : 0,
  "completed" : "2000-01-23T04:56:07.000+00:00",
  "completedWithErrors" : true,
  "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "user" : "user"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

200

Success **TaskDetailModel**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

Users



`get /v1/Users`

Retrieves the list of Users with pagination (sorting and filtering) (`v1UsersGet`)

Query parameters

Sorts (optional)

Query Parameter —

`Pagination.PageSize` (optional)

Query Parameter — The number of records per page, for example 1. Shouldn't exceed 200. format: int32

`Pagination.PageNumber` (optional)

Query Parameter — The page number to retrieve from results, for example 1 format: int32

`Filter.EmailAddress` (optional)

Query Parameter — Email

Filter.RoleId (optional)

Query Parameter — Role identifier format: uuid

Filter.LastSignedIn.Dates (optional)

Query Parameter — Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00 format: date-time

Filter.LastSignedIn.SelectionMode (optional)

Query Parameter — The selection mode of date criteria e.g single, multiple, range

Filter.Disabled (optional)

Query Parameter — Is user disabled

Filter.Language (optional)

Query Parameter — Language

Return type

[UserListItemModelPagedResponse](#)

Example data

Content-Type: application/json

```
{
  "pageCount" : 5,
  "pageNumber" : 0,
  "data" : [ {
    "accountName" : "accountName",
    "created" : "2000-01-23T04:56:07.000+00:00",
    "roles" : [ {
      "resourceId" : "resourceId",
      "name" : "name",
      "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "resourceType" : "resourceType"
    }, {
      "resourceId" : "resourceId",
      "name" : "name",
      "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
      "resourceType" : "resourceType"
    } ],
    "errorInfo" : {
      "userAccountName" : "userAccountName",
      "parentTaskName" : "parentTaskName",
      "initiated" : "2000-01-23T04:56:07.000+00:00",
      "errorCode" : 0,
      "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
    },
    "language" : "language",
    "emailAddress" : "emailAddress",
    "olsonTimeZoneId" : "olsonTimeZoneId",
    "roleName" : "roleName",
```

```
"disabled" : true,
"id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"locked" : true,
"dateTimeDisplayFormat" : "dateTimeDisplayFormat",
"lastSignedIn" : "2000-01-23T04:56:07.000+00:00"
}, {
  "accountName" : "accountName",
  "created" : "2000-01-23T04:56:07.000+00:00",
  "roles" : [ {
    "resourceId" : "resourceId",
    "name" : "name",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "resourceType" : "resourceType"
  }, {
    "resourceId" : "resourceId",
    "name" : "name",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "resourceType" : "resourceType"
  } ],
  "errorInfo" : {
    "userAccountName" : "userAccountName",
    "parentTaskName" : "parentTaskName",
    "initiated" : "2000-01-23T04:56:07.000+00:00",
    "errorCode" : 0,
    "userId" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91"
  },
  "language" : "language",
  "emailAddress" : "emailAddress",
  "olsonTimeZoneId" : "olsonTimeZoneId",
  "roleName" : "roleName",
  "disabled" : true,
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "locked" : true,
  "dateTimeDisplayFormat" : "dateTimeDisplayFormat",
  "lastSignedIn" : "2000-01-23T04:56:07.000+00:00"
} ],
"pageSize" : 6,
"totalRecordCount" : 1
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **UserListItemModelPagedResponse**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

500

Server Error



`post /v1/Users/{id}/AssignRole`

Assign Role to User (v1UsersIdAssignRolePost)

Path parameters

id (required)

Path Parameter — UserId format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [AssignUserToRoleRequest](#) (optional)

Body Parameter — Role assignment request containing Role identifier

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

204

No Content

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**



`patch /v1/Users/{id}/Disable`

Disables User (v1UsersIdDisablePatch)

Path parameters

id (required)

Path Parameter — UserId format: uuid

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses

204

No Content

404Not Found **ProblemDetails****423**Client Error **ProblemDetails**`patch /v1/Users/{id}/Enable`

Enables User (v1UsersIdEnablePatch)

Path parameters

id (required)

Path Parameter — format: uuid**Produces**


This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses**204**

No Content

401Unauthorized **ProblemDetails****404**Not Found **ProblemDetails****423**Client Error **ProblemDetails**

 `get /v1/Users/{id}`

Retrieves a detail of the User (v1UsersIdGet)

Path parameters

id (required)

Path Parameter — format: uuid

Return type

[UserDetailModel](#)

Example data

Content-Type: application/json

```
{
  "emailAddress" : "emailAddress",
  "accountName" : "accountName",
  "created" : "2000-01-23T04:56:07.000+00:00",
  "olsonTimeZoneId" : "olsonTimeZoneId",
  "roles" : [ {
    "resourceId" : "resourceId",
    "name" : "name",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "allowPermissions" : [ {
      "resource" : "resource",
      "action" : "action"
    }, {
      "resource" : "resource",
      "action" : "action"
    } ],
    "denyPermissions" : [ null, null ],
    "resourceType" : "resourceType"
  }, {
    "resourceId" : "resourceId",
    "name" : "name",
    "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "allowPermissions" : [ {
      "resource" : "resource",
      "action" : "action"
    }, {
      "resource" : "resource",
      "action" : "action"
    } ],
    "denyPermissions" : [ null, null ],
    "resourceType" : "resourceType"
  } ]
}
```

```
} ],
  "isFirstSignIn" : true,
  "disabled" : true,
  "language" : "language",
  "allowInvites" : true,
  "id" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
  "dateTimeDisplayFormat" : "dateTimeDisplayFormat",
  "lastSignedIn" : "2000-01-23T04:56:07.000+00:00"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- **text/plain**
- **application/json**
- **text/json**

Responses

200

Success **UserDetailModel**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**



put /v1/Users/{id}/ModifyUserPreferences

Modifies User Preferences (v1UsersIdModifyUserPreferencesPut)

Path parameters

id (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ModifyUserPreferencesRequest](#) (optional)

Body Parameter —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

204

No Content

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

409

Conflict **ProblemDetails**

423

Client Error **ProblemDetails**

 `put /v1/Users/{id}`

Modifies User (v1UsersIdPut)

Path parameters

id (required)

Path Parameter — format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [ModifyUserRequest](#) (optional)

Body Parameter —

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

204

No Content

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

404

Not Found **ProblemDetails**

409Conflict **ProblemDetails****423**Client Error **ProblemDetails** `patch /v1/Users/{id}/ResendInvite`

Resends invitation email to User (v1UsersIdResendInvitePatch)

Path parameters

id (required)

Path Parameter — format: uuid**Produces**

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/plain
- application/json
- text/json

Responses**204**

No Content

401Unauthorized **ProblemDetails****404**Not Found **ProblemDetails** `post /v1/Users`

Creates User (v1UsersPost)

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`
- `text/json`
- `application/*+json`

Request body

body [CreateUserRequest](#) (optional)

Body Parameter —

Return type

UUID

Example data

Content-Type: `application/json`

```
"046b6c7f-0b8a-43b9-b35d-6489e6daee91"
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `text/plain`
- `application/json`
- `text/json`

Responses

201

Created **UUID**

400

Bad Request **ProblemDetails**

401

Unauthorized **ProblemDetails**

409Conflict **ProblemDetails**

Models

[[Jump to Methods](#)]

Table of Contents

1. [AcceptedDomainDetailModel](#)
2. [AcceptedDomainListItemModel](#)
3. [Activex](#)
4. [ActivityAuditDetailModel](#)
5. [ActivityAuditDetailModelPagedResponse](#)
6. [ActivityAuditListItemModel](#)
7. [ActivityAuditListItemModelPagedResponse](#)
8. [ActivityAuditRoleNameModel](#)
9. [ActivityAuditRoleResourceModel](#)
10. [Agent](#)
11. [AgentBuild](#)
12. [AgentHostType](#)
13. [ApiClientDataAuditingDetailModel](#)
14. [Application](#)
15. [Applicationgroup](#)
16. [As](#)
17. [AsOrganization](#)
18. [AssignComputersToGroupRequest](#)
19. [AssignPolicyRevisionToGroupRequest](#)
20. [AssignUserToRoleRequest](#)
21. [Attribute](#)
22. [Authentication](#)
23. [Authorization](#)
24. [AuthorizationRequestAuditDetailModel](#)
25. [AuthorizationRequestAuditDetailModelPagedResponse](#)
26. [AuthorizationRequestAuditListItemModel](#)
27. [AuthorizationRequestAuditListItemModelPagedResponse](#)
28. [Authorizationrequest](#)
29. [Authorizinguser](#)
30. [Bundle](#)
31. [CertificateInformationModel](#)
32. [ChangedBy](#)
33. [Client](#)
34. [ClientNat](#)

35. [Cloud](#)
36. [CloudAccount](#)
37. [CloudInstance](#)
38. [CloudMachine](#)
39. [CloudOrigin](#)
40. [CloudProject](#)
41. [CloudService](#)
42. [CloudTarget](#)
43. [CodeSignature](#)
44. [Com](#)
45. [ComputerDataAuditingDetailModel](#)
46. [ComputerDetailModel](#)
47. [ComputerFilterModel](#)
48. [ComputerListItemModel](#)
49. [ComputerListItemModelPagedResponse](#)
50. [ComputerLogModel](#)
51. [ComputerRenewCertificateRequest](#)
52. [ComputerRetrieveLogsRequest](#)
53. [ComputerRetrieveStatusInfoRequest](#)
54. [ComputersAuthoriseRequest](#)
55. [ComputersDeactivateRequest](#)
56. [ComputersRejectRequest](#)
57. [ComputersRemoveRequest](#)
58. [Configuration](#)
59. [Container](#)
60. [ContainerCpu](#)
61. [ContainerDisk](#)
62. [ContainerDiskRead](#)
63. [ContainerDiskWrite](#)
64. [ContainerImage](#)
65. [ContainerImageHash](#)
66. [ContainerMemory](#)
67. [ContainerNetwork](#)
68. [ContainerNetworkEgress](#)
69. [ContainerNetworkIngress](#)
70. [Content](#)
71. [Contentgroup](#)
72. [CountRange](#)
73. [CreateAcceptedDomainRequest](#)
74. [CreateGroupRequest](#)

75. [CreateUserRequest](#)
76. [DataStream](#)
77. [DateFilterModel](#)
78. [DateSelectionMode](#)
79. [Destination](#)
80. [DestinationNat](#)
81. [DII](#)
82. [Dns](#)
83. [DnsQuestion](#)
84. [Ecs](#)
85. [Elf](#)
86. [ElfHeader](#)
87. [ElfSections](#)
88. [ElfSegments](#)
89. [Email](#)
90. [EmailAttachments](#)
91. [EmailAttachmentsFile](#)
92. [EmailBcc](#)
93. [EmailCc](#)
94. [EmailFrom](#)
95. [EmailReplyTo](#)
96. [EmailSender](#)
97. [EmailTo](#)
98. [EndpointInformationModel](#)
99. [EpmEcsEvent](#)
100. [EpmEcsEventResponseModel](#)
101. [EpmEcsEventSpan](#)
102. [EpmEcsEventTrace](#)
103. [EpmEcsEventTransaction](#)
104. [Epmwinmac](#)
105. [Error](#)
106. [Event](#)
107. [Faas](#)
108. [FaasTrigger](#)
109. [File](#)
110. [Geo](#)
111. [GeoPoint](#)
112. [Gpo](#)
113. [Group](#)
114. [GroupDataAuditingDetailModel](#)

- 115. [GroupListItemModel](#)
- 116. [GroupListItemModelPagedResponse](#)
- 117. [Hash](#)
- 118. [Host](#)
- 119. [HostBoot](#)
- 120. [HostCpu](#)
- 121. [HostDisk](#)
- 122. [HostDiskRead](#)
- 123. [HostDiskWrite](#)
- 124. [HostNetwork](#)
- 125. [HostNetworkEgress](#)
- 126. [HostNetworkIngress](#)
- 127. [Http](#)
- 128. [HttpRequest](#)
- 129. [HttpRequestBody](#)
- 130. [HttpResponse](#)
- 131. [HttpResponseBody](#)
- 132. [InstallationKeyDataAuditingDetailModel](#)
- 133. [Installer](#)
- 134. [ListItemErrorInfoModel](#)
- 135. [Log](#)
- 136. [LogFile](#)
- 137. [LogOrigin](#)
- 138. [LogOriginFile](#)
- 139. [Message](#)
- 140. [ModifyAcceptedDomainRequest](#)
- 141. [ModifyGroupRequest](#)
- 142. [ModifyPolicyRequest](#)
- 143. [ModifyUserPreferencesRequest](#)
- 144. [ModifyUserRequest](#)
- 145. [Network](#)
- 146. [OS](#)
- 147. [Observer](#)
- 148. [OperationValue](#)
- 149. [Operator](#)
- 150. [Orchestrator](#)
- 151. [OrchestratorCluster](#)
- 152. [OrchestratorResource](#)
- 153. [OrchestratorResourceParent](#)
- 154. [Organization](#)

- 155. [Os](#)
- 156. [Owner](#)
- 157. [Package](#)
- 158. [Pe](#)
- 159. [PolicyDataAuditingDetailModel](#)
- 160. [PolicyGroupsListItemModel](#)
- 161. [PolicyListItemModel](#)
- 162. [PolicyListItemModelPagedResponse](#)
- 163. [PolicyRevisionDataAuditingDetailModel](#)
- 164. [PolicyRevisionModel](#)
- 165. [PolicyRevisionState](#)
- 166. [Privilegedgroup](#)
- 167. [ProblemDetails](#)
- 168. [Process](#)
- 169. [ProcessEntryLeader](#)
- 170. [ProcessEntryMeta](#)
- 171. [ProcessGroupLeader](#)
- 172. [ProcessParent](#)
- 173. [ProcessPrevious](#)
- 174. [ProcessSessionLeader](#)
- 175. [ProcessThread](#)
- 176. [Registry](#)
- 177. [RegistryData](#)
- 178. [Related](#)
- 179. [Remotepowershell](#)
- 180. [RoleElement](#)
- 181. [RoleItemModel](#)
- 182. [RoleListItemModel](#)
- 183. [RoleModel](#)
- 184. [RolePermissionModel](#)
- 185. [Rule](#)
- 186. [Rulescript](#)
- 187. [RulescriptOutcome](#)
- 188. [SCIMEmail](#)
- 189. [SCIMUserName](#)
- 190. [ScimAuthenticationSchemes](#)
- 191. [ScimBulk](#)
- 192. [ScimOperation](#)
- 193. [ScimResourceMeta](#)
- 194. [ScimResourceResponse](#)

- 195. [ScimResourceResponseScimListResponse](#)
- 196. [ScimSchemaResponse](#)
- 197. [ScimSchemaResponseScimListResponse](#)
- 198. [ScimServiceProviderConfigResponse](#)
- 199. [ScimSupported](#)
- 200. [ScimUserMetaModel](#)
- 201. [ScimUserModel](#)
- 202. [ScimUserModelScimListResponse](#)
- 203. [ScimUserPatchRequest](#)
- 204. [Server](#)
- 205. [ServerNat](#)
- 206. [Service](#)
- 207. [ServiceNode](#)
- 208. [ServiceOrigin](#)
- 209. [ServiceTarget](#)
- 210. [Servicecontrol](#)
- 211. [ServicecontrolService](#)
- 212. [Session](#)
- 213. [SettingDataAuditingDetailModel](#)
- 214. [SortDirection](#)
- 215. [SortModel](#)
- 216. [Source](#)
- 217. [SourceNat](#)
- 218. [Storeapp](#)
- 219. [SubAttribute](#)
- 220. [TaskDetailModel](#)
- 221. [Threat](#)
- 222. [ThreatEnrichments](#)
- 223. [ThreatEnrichmentsMatched](#)
- 224. [ThreatFeed](#)
- 225. [ThreatGroup](#)
- 226. [ThreatIndicator](#)
- 227. [ThreatIndicatorEmail](#)
- 228. [ThreatIndicatorMarking](#)
- 229. [ThreatSoftware](#)
- 230. [ThreatTactic](#)
- 231. [ThreatTechnique](#)
- 232. [ThreatTechniqueSubtechnique](#)
- 233. [Tls](#)
- 234. [TlsClient](#)

- 235. [TlsClientHash](#)
- 236. [TlsServer](#)
- 237. [TlsServerHash](#)
- 238. [Token](#)
- 239. [Trustedapplication](#)
- 240. [UnassignComputersToGroupRequest](#)
- 241. [Url](#)
- 242. [User](#)
- 243. [UserAgent](#)
- 244. [UserAgentDevice](#)
- 245. [UserChanges](#)
- 246. [UserDataAuditing](#)
- 247. [UserDetailModel](#)
- 248. [UserEffective](#)
- 249. [UserListItemModel](#)
- 250. [UserListItemModelPagedResponse](#)
- 251. [UserRoleResourceItemModel](#)
- 252. [UserTarget](#)
- 253. [Vlan](#)
- 254. [Vulnerability](#)
- 255. [VulnerabilityScanner](#)
- 256. [VulnerabilityScore](#)
- 257. [Workstyle](#)
- 258. [X509](#)
- 259. [X509Issuer](#)
- 260. [X509Subject](#)
- 261. [_event](#)
- 262. [_rule](#)
- 263. [id_AssignComputersByCsv_body](#)



AcceptedDomainDetailModel

id (optional)

UUID Accepted Domain Id format: uuid

domain (optional)

String Accepted Domain name

created (optional)

Date Created date format: date-time



AcceptedDomainListItemModel

Model of Accepted Domain list item

id (optional)

UUID The Id (Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

locked (optional)

Boolean

errorInfo (optional)

ListItemErrorInfoModel

domain (optional)

String Accepted Domain name

created (optional)

Date Created date format: date-time



Activex

Codebase (optional)

String

CLSID (optional)

String

Version (optional)

String



ActivityAuditDetailModel

Activity audit detail model

id (optional)

Long Id format: int64

details (optional)

String Details

userId (optional)

UUID User id format: uuid

user (optional)

String user name

entity (optional)

String entity
auditType (optional)
String audit type
created (optional)
Date created format: date-time
changedBy (optional)
ChangedBy
apiClientDataAuditing (optional)
ApiClientDataAuditingDetailModel
computerDataAuditing (optional)
ComputerDataAuditingDetailModel
groupDataAuditing (optional)
GroupDataAuditingDetailModel
installationKeyDataAuditing (optional)
InstallationKeyDataAuditingDetailModel
policyDataAuditing (optional)
PolicyDataAuditingDetailModel
policyRevisionDataAuditing (optional)
PolicyRevisionDataAuditingDetailModel
settingsDataAuditing (optional)
SettingDataAuditingDetailModel
userDataAuditing (optional)
UserDataAuditing



ActivityAuditDetailModelPagedResponse

pageNumber (optional)
Integer format: int32
pageSize (optional)
Integer format: int32
totalRecordCount (optional)
Integer format: int32
pageCount (optional)
Integer format: int32
data (optional)
array[ActivityAuditDetailModel]



ActivityAuditListItemModel

Model of Activity Audit list item

id (optional)

Long Activity Audit identifier format: int64

locked (optional)

Boolean

errorInfo (optional)

ListItemErrorInfoModel

details (optional)

String Activity Audit Details

user (optional)

String Initiated User email or API Client identifier

created (optional)

Date Created date format: date-time

entity (optional)

String Name of Activity Audit entity

auditType (optional)

String Audit Type Name

changedBy (optional)

ChangedBy



ActivityAuditListItemModelPagedResponse

pageNumber (optional)

Integer format: int32

pageSize (optional)

Integer format: int32

totalRecordCount (optional)

Integer format: int32

pageCount (optional)

Integer format: int32

data (optional)

array[ActivityAuditListItemModel]



ActivityAuditRoleNameModel

activity audit role name mapping model

roleId (optional)

UUID role id format: uuid

roleName (optional)

String role name



ActivityAuditRoleResourceModel

Role Resource Model for activity audits

resourceType (optional)

String Type of resource

resourceId (optional)

UUID Id of the resource format: uuid

resourceName (optional)

String Resource name

newRoles (optional)

array[ActivityAuditRoleNameModel] List of new roles

oldRoles (optional)

array[ActivityAuditRoleNameModel] List of oldRoles



Agent

version (optional)

String

build (optional)

AgentBuild

name (optional)

String

type (optional)

String

id (optional)

String

ephemeral_id (optional)

String

AgentBuild

original (optional)

String

AgentHostType

enum

String

- Undefined
- MicrosoftWindows
- AppleMacOS
- Linux

ApiClientDataAuditingDetailModel

newName (optional)

String

oldName (optional)

String

newDescription (optional)

String

oldDescription (optional)

String

secretUpdated (optional)

Boolean

deleted (optional)

Boolean

 **Application**

Type (optional)

String

Description (optional)

String

Identifier (optional)

String

 **Applicationgroup**

Name (optional)

String

Description (optional)

String

Identifier (optional)

String

 **As**

number (optional)

Long format: int64

organization (optional)

AsOrganization

 **AsOrganization**

name (optional)

String



AssignComputersToGroupRequest

computerIds (optional)

array[UUID] computer ids which will be assigned to the group format: uuid

excludedComputerIds (optional)

array[UUID] computer ids which will not be assigned to group format: uuid

filter (optional)

ComputerFilterModel

allComputers (optional)

Boolean assigns all computers to the group



AssignPolicyRevisionToGroupRequest

policyRevisionId (optional)

UUID format: uuid



AssignUserToRoleRequest

Model for assigning role to user

roleId

UUID Role identifier format: uuid



Attribute

attributes of schemas

name (optional)

String name of attribute

description (optional)

String description of attribute

type (optional)

String type of attribute

caseExact (optional)

Boolean Flag for whether or not the attribute's casing should be exact

multiValued (optional)
Boolean Flag for whether or not the attribute has multi values
mutability (optional)
String Mutability of the attribute
required (optional)
Boolean Flag for whether or not the attribute is required
returned (optional)
String how the attribute is returned
uniqueness (optional)
String Is the value unique
subAttributes (optional)
array[SubAttribute] List of subattributes



Authentication

User (optional)

String



Authorization

ChallengeCode (optional)

String

ResponseStatus (optional)

String



AuthorizationRequestAuditDetailModel

id (optional)

Long format: int64

ticketId (optional)

String

productName (optional)

String

user (optional)

String

computerName (optional)

String

reason (optional)

String

decisionPerformedByUser (optional)

String

timeOfRequest (optional)

Date format: date-time

decisionTime (optional)

Date format: date-time

decision (optional)

String

startTime (optional)

Date format: date-time

duration (optional)

String**AuthorizationRequestAuditDetailModelPagedResponse**

pageNumber (optional)

Integer format: int32

pageSize (optional)

Integer format: int32

totalRecordCount (optional)

Integer format: int32

pageCount (optional)

Integer format: int32

data (optional)

array[AuthorizationRequestAuditDetailModel]

**AuthorizationRequestAuditListItemModel**

id (optional)

Long format: int64

ticketId (optional)

String

productName (optional)

String

user (optional)

String

computerName (optional)

String

reason (optional)

String

decisionPerformedByUser (optional)

String

timeOfRequest (optional)

Date format: date-time

decisionTime (optional)

Date format: date-time

decision (optional)

String

duration (optional)

String

startTime (optional)

Date format: date-time**AuthorizationRequestAuditListItemModelPagedResponse**

pageNumber (optional)

Integer format: int32

pageSize (optional)

Integer format: int32

totalRecordCount (optional)

Integer format: int32

pageCount (optional)

Integer format: int32

data (optional)

array[**AuthorizationRequestAuditListItemModel**]



Authorizationrequest

ControlAuthorization (optional)

Boolean

AuthRequestURI (optional)

String



Authorizinguser

Identifier (optional)

String

Name (optional)

String

DomainIdentifier (optional)

String

DomainNetBIOSName (optional)

String

DomainName (optional)

String

CredentialSource (optional)

String



Bundle

Name (optional)

String

Type (optional)

String

Creator (optional)

String

InfoDescription (optional)

String

Version (optional)

String

DownloadSource (optional)

String

Uri (optional)

String**CertificateInformationModel**

validFrom (optional)

Date format: date-time

validTo (optional)

Date format: date-time

lastIssued (optional)

Date format: date-time**ChangedBy**

enum

String

- API
- Portal

**Client**

address (optional)

String

ip (optional)

String

port (optional)

Long format: int64

mac (optional)

String

domain (optional)

String

registered_domain (optional)

String

top_level_domain (optional)

String

subdomain (optional)

String

bytes (optional)

Long format: int64

packets (optional)

Long format: int64

nat (optional)

ClientNat

as (optional)

As

geo (optional)

Geo

user (optional)

User**ClientNat**

ip (optional)

String

port (optional)

Long format: int64**Cloud**

provider (optional)

String

availability_zone (optional)

String

region (optional)

String

instance (optional)

CloudInstance

machine (optional)

CloudMachine

account (optional)

CloudAccount

service (optional)

CloudService

project (optional)

CloudProject

origin (optional)

CloudOrigin

target (optional)

CloudTarget**CloudAccount**

id (optional)

String

name (optional)

String**CloudInstance**

id (optional)

String

name (optional)

String**CloudMachine**

type (optional)

String



CloudOrigin

provider (optional)

String

availability_zone (optional)

String

region (optional)

String

instance (optional)

CloudInstance

machine (optional)

CloudMachine

account (optional)

CloudAccount

service (optional)

CloudService

project (optional)

CloudProject



CloudProject

id (optional)

String

name (optional)

String



CloudService

name (optional)

String



CloudTarget

provider (optional)

String

availability_zone (optional)

String

region (optional)

String

instance (optional)

CloudInstance

machine (optional)

CloudMachine

account (optional)

CloudAccount

service (optional)

CloudService

project (optional)

CloudProject



CodeSignature

exists (optional)

Boolean

subject_name (optional)

String

valid (optional)

Boolean

trusted (optional)

Boolean

status (optional)

String

team_id (optional)

String

signing_id (optional)

String

digest_algorithm (optional)

String

timestamp (optional)

Date format: date-time



AppID (optional)

String

CLSID (optional)

String

DisplayName (optional)

String



ComputerDataAuditingDetailModel

updatedPoliciesOn (optional)

map[String, String]

deactivatedAgents (optional)

map[String, String]

newDeletedAgents (optional)

array[String]



ComputerDetailModel

id (optional)

UUID format: uuid

hostType (optional)

String

created (optional)

Date format: date-time

adapterVersion (optional)

String

agentVersion (optional)

String

authorisationState (optional)

String

authorised (optional)

Date format: date-time

connected (optional)

Boolean

lastConnected (optional)

Date format: date-time

deactivated (optional)

Boolean

autoDeactivated (optional)

Boolean

pendingDeactivation (optional)

Boolean

deactivatedOn (optional)

Date format: date-time

groupId (optional)

UUID format: uuid

groupName (optional)

String

policyId (optional)

UUID format: uuid

policyName (optional)

String

policyRevision (optional)

Integer format: int32

policyRevisionStatus (optional)

String

endpointInformation (optional)

EndpointInformationModel

certificateInformation (optional)

CertificateInformationModel

hostPolicyId (optional)

UUID format: uuid

hostPolicyName (optional)

String

hostPolicyRevision (optional)

Integer format: int32

hostLastUpdated (optional)

Date format: date-time

agentLogs (optional)

array[ComputerLogModel]

duplicateCount (optional)

Integer format: int32

credentialType (optional)

String**ComputerFilterModel**

Filter Class for Computers

computerId (optional)

UUID The Id of the Computer(Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

host (optional)

String The host name of the Computer, for example - Computer1

hostType (optional)

AgentHostType

agentVersion (optional)

String The agent version of the Computer, example - 5.6.126.0

adapterVersion (optional)

String The adapter version of the Computer, example - 20.5.195.0

authorisationState (optional)

String The state of the Computer, example - Authorised, Pending

lastConnected (optional)

DateFilterModel

policyRevisionStatus (optional)

String Policy Revision Status, example - AwaitingLatestPolicy

policyId (optional)

UUID Policy Id, example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

policyName (optional)

String Policy Name, example - Policy1

groupId (optional)

UUID Group Id, example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

groupName (optional)

String Group Name, example - Group1

os (optional)

OS

domain (optional)

String Domain Name, example - BeyondTrust

created (optional)

DateFilterModel

duplicateCount (optional)

CountRange**ComputerListItemModel**

id (optional)

UUID The Id (Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

locked (optional)

Boolean

errorInfo (optional)

ListItemErrorInfoModel

created (optional)

Date Created Date of the computer, example - 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562 format: date-time

host (optional)

String The host name of the Computer, for example - Computer1

hostType (optional)

AgentHostType

os (optional)

String OS Name, example - Windows

domain (optional)

String Domain Name, example - BeyondTrust

adapterVersion (optional)

String The adapter version of the Computer, example - 20.5.195.0

agentVersion (optional)

String The agent version of the Computer, example - 5.6.126.0

authorisationState (optional)

String The state of the Computer, example - Authorised, Pending

lastConnected (optional)

Date Date when computer is last connected, example - 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562 format: date-time

deactivated (optional)

Boolean if computer is deactivated, example - false

deactivatedOn (optional)

Date Date when computer turned into deactivation state, example - 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562 format: date-time

pendingDeactivation (optional)

Boolean if computer is in PendingDeactivation state, example - false

rejected (optional)

Boolean if computer is deactivated, example - false
duplicate (optional)
Boolean if computer has/is duplicate, example - false
duplicateCount (optional)
Integer Computer duplicate count, Min and Max Ranges, example - 1,2,3 format: int32
policyRevisionId (optional)
UUID format: uuid
policyId (optional)
UUID Policy Id, example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid
policyName (optional)
String Policy Name, example - Policy1
policyRevisionStatus (optional)
String
groupId (optional)
UUID Group Id, example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid
groupName (optional)
String Group Name, example - Group1
credentialType (optional)
String



ComputerListItemModelPagedResponse

pageNumber (optional)
Integer format: int32
pageSize (optional)
Integer format: int32
totalRecordCount (optional)
Integer format: int32
pageCount (optional)
Integer format: int32
data (optional)
array[ComputerListItemModel]



ComputerLogModel

id (optional)

UUID format: uuid
created (optional)
Date format: date-time
returned (optional)
Date format: date-time



ComputerRenewCertificateRequest

computerId (optional)
UUID format: uuid



ComputerRetrieveLogsRequest

computerId (optional)
UUID format: uuid



ComputerRetrieveStatusInfoRequest

computerId (optional)
UUID format: uuid



ComputersAuthoriseRequest

computerIds (optional)
array[UUID] format: uuid
excludedComputerIds (optional)
array[UUID] format: uuid
filter (optional)
ComputerFilterModel
allComputers (optional)
Boolean

groupId (optional)

UUID format: uuid



ComputersDeactivateRequest

computerIds (optional)

array[UUID] format: uuid

excludedComputerIds (optional)

array[UUID] format: uuid

filter (optional)

ComputerFilterModel

allComputers (optional)

Boolean



ComputersRejectRequest

Request to reject Computer(s)

computerIds (optional)

array[UUID] List of Computers identifiers to be rejected format: uuid

excludedComputerIds (optional)

array[UUID] List of Computers identifiers to be excluded from the rejection list format: uuid

filter (optional)

ComputerFilterModel

allComputers (optional)

Boolean Is all Computers matching BT.Common.ManagementApi.Computer.ComputerFilterModel and ExcludedComputerIds should be rejected



ComputersRemoveRequest

Request to remove Computer(s)

computerIds (optional)

array[UUID] List of Computers identifiers to be removed (optional when allComputers is true, otherwise its required) format: uuid

excludedComputerIds (optional)

array[UUID] List of Computers identifiers to be excluded from the deletion list format: uuid

filter (optional)

ComputerFilterModel

allComputers (optional)

Boolean Is all Computers matching BT.Common.ManagementApi.Computer.ComputerFilterModel and ExcludedComputerIds should be removed

**Configuration**

Identifier (optional)

String

RevisionNumber (optional)

String

Source (optional)

String

Name (optional)

String

Path (optional)

String

LoadAuditMode (optional)

array[String]

SigningEnforcement (optional)

String

Application (optional)

Application

ApplicationGroup (optional)

Applicationgroup

Content (optional)

Content

ContentGroup (optional)

Contentgroup

GPO (optional)

Gpo

Message (optional)

Message

Rule (optional)

Rule

RuleScript (optional)

Rulescript

Token (optional)

Token

Workstyle (optional)

Workstyle



Container

cpu (optional)

ContainerCpu

disk (optional)

ContainerDisk

id (optional)

String

image (optional)

ContainerImage

labels (optional)

String

memory (optional)

ContainerMemory

name (optional)

String

network (optional)

ContainerNetwork

runtime (optional)

String



ContainerCpu

usage (optional)

Double format: double



ContainerDisk

read (optional)

ContainerDiskRead

write (optional)

ContainerDiskWrite**ContainerDiskRead**

bytes (optional)

Long format: int64**ContainerDiskWrite**

bytes (optional)

Long format: int64**ContainerImage**

name (optional)

String

tag (optional)

array[String]

hash (optional)

ContainerImageHash**ContainerImageHash**

all (optional)

array[String]



ContainerMemory

usage (optional)

Double format: double



ContainerNetwork

ingress (optional)

ContainerNetworkIngress

egress (optional)

ContainerNetworkEgress



ContainerNetworkEgress

bytes (optional)

Long format: int64



ContainerNetworkIngress

bytes (optional)

Long format: int64



Content

Type (optional)

String

Description (optional)

String

Identifier (optional)

String



Contentgroup

Name (optional)

String

Description (optional)

String

Identifier (optional)

String



CountRange

Range Class to specify Min and Max Values

min (optional)

Integer Min Value of CountRange, example - 1,2,3 format: int32

max (optional)

Integer Max Value of CountRange, example - 1,2,3 format: int32



CreateAcceptedDomainRequest

Create Accepted Domain Model

domainName (optional)

String Accepted Domain Name



CreateGroupRequest

name (optional)

String name of the group, for example - Alianse Group

description (optional)

String description of the group, for example - Alianse Group Description

isDefault (optional)

Boolean



CreateUserRequest

CreateUserRequest

emailAddress (optional)

String EmailAddress

olsonTimeZoneld (optional)

String OlsonTimeZoneld

dateTimeDisplayFormat (optional)

String DateTimeDisplayFormat

roleld (optional)

UUID Roleld format: uuid

language (optional)

String Language

enabled (optional)

Boolean Enabled



DataStream

type (optional)

String

dataset (optional)

String

namespace (optional)

String



DateFilterModel

DateFilter to specify Dates to be filtered

dates (optional)

array[Date] Valid date formats for filter - 2020-12-24, 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24

19:09:47.6816562 +00:00 format: date-time

selectionMode (optional)

DateSelectionMode



DateSelectionMode

Date Selection Mode for filter

enum

String

- Single
- Multiple
- Range



Destination

address (optional)

String

ip (optional)

String

port (optional)

Long format: int64

mac (optional)

String

domain (optional)

String

registered_domain (optional)

String

top_level_domain (optional)

String

subdomain (optional)

String

bytes (optional)

Long format: int64

packets (optional)

Long format: int64

nat (optional)

DestinationNat

as (optional)

As

geo (optional)

Geo

user (optional)

User



DestinationNat

ip (optional)

String

port (optional)

Long format: int64



D11

name (optional)

String

path (optional)

String

hash (optional)

Hash

pe (optional)

Pe

code_signature (optional)

CodeSignature



Dns

type (optional)

String

id (optional)

String

op_code (optional)

String

header_flags (optional)

array[String]

response_code (optional)

String

question (optional)

DnsQuestion

answers (optional)

String

resolved_ip (optional)

array[String]

**DnsQuestion**

name (optional)

String

type (optional)

String

class (optional)

String

registered_domain (optional)

String

top_level_domain (optional)

String

subdomain (optional)

String**Ecs**

version (optional)

String**Elf**

creation_date (optional)

Date format: date-time

architecture (optional)

String

byte_order (optional)
String
cpu_type (optional)
String
header (optional)
ElfHeader
sections (optional)
array[ElfSections]
exports (optional)
map[String, String]
imports (optional)
map[String, String]
shared_libraries (optional)
array[String]
telfhash (optional)
String
segments (optional)
array[ElfSegments]



ElfHeader

class (optional)
String
data (optional)
String
os_abi (optional)
String
type (optional)
String
version (optional)
String
abi_version (optional)
String
entrypoint (optional)
Long format: int64
object_version (optional)
String



ElfSections

flags (optional)

String

name (optional)

String

physical_offset (optional)

String

type (optional)

String

physical_size (optional)

Long format: int64

virtual_address (optional)

Long format: int64

virtual_size (optional)

Long format: int64

entropy (optional)

Long format: int64

chi2 (optional)

Long format: int64



ElfSegments

type (optional)

String

sections (optional)

String



Email

attachments (optional)

array[EmailAttachments]

bcc (optional)

EmailBcc

cc (optional)

EmailCc

content_type (optional)

String

delivery_timestamp (optional)

Date format: date-time

direction (optional)

String

from (optional)

EmailFrom

local_id (optional)

String

message_id (optional)

String

origination_timestamp (optional)

Date format: date-time

reply_to (optional)

EmailReplyTo

sender (optional)

EmailSender

subject (optional)

String

to (optional)

EmailTo

x_mailer (optional)

String**EmailAttachments**

file (optional)

EmailAttachmentsFile**EmailAttachmentsFile**

extension (optional)

String

mime_type (optional)

String

name (optional)

String

size (optional)

Long format: int64

hash (optional)

Hash**EmailBcc**

address (optional)

array[String]**EmailCc**

address (optional)

array[String]**EmailFrom**

address (optional)

array[String]**EmailReplyTo**

address (optional)

array[String]

**EmailSender**

address (optional)

String**EmailTo**

address (optional)

array[String]**EndpointInformationModel**

macAddress (optional)

String

osArchitecture (optional)

String

osCaption (optional)

String

osCodeSet (optional)

String

osComputerDescription (optional)

String

osCountryCode (optional)

String

osInstallDate (optional)

Date format: date-time

osManufacturer (optional)

String

osOrganization (optional)

String

osSerialNumber (optional)

String

osSystemDirectory (optional)

String

osSystemDrive (optional)

String

osVersion (optional)

String

osVersionString (optional)

String

processorCaption (optional)

String

processorDescription (optional)

String

processorManufacturer (optional)

String

processorName (optional)

String

systemDnsHostName (optional)

String

systemDomain (optional)

String

systemManufacturer (optional)

String

systemModel (optional)

String

systemName (optional)

String

systemPrimaryOwnerName (optional)

String

systemSystemType (optional)

String

systemWorkgroup (optional)

String**EpmEcsEvent**

agent (optional)

Agent

@timestamp (optional)

Date format: date-time

tags (optional)

array[String]

labels (optional)

String

message (optional)

String

client (optional)

Client

cloud (optional)

Cloud

container (optional)

Container

data_stream (optional)

DataStream

destination (optional)

Destination

dll (optional)

Dll

dns (optional)

Dns

ecs (optional)

Ecs

email (optional)

Email

error (optional)

Error

event (optional)

_event

faas (optional)

Faas

file (optional)

File

group (optional)

Group

host (optional)

Host

http (optional)

Http

log (optional)

Log

network (optional)

Network

observer (optional)

Observer

orchestrator (optional)

Orchestrator

organization (optional)

Organization

package (optional)

Package

process (optional)

Process

registry (optional)

Registry

related (optional)

Related

rule (optional)

_rule

server (optional)

Server

service (optional)

Service

source (optional)

Source

threat (optional)

Threat

tls (optional)

Tls

trace (optional)

EpmEcsEventTrace

transaction (optional)

EpmEcsEventTransaction

span (optional)

EpmEcsEventSpan

url (optional)

Url

user (optional)

User

user_agent (optional)

UserAgent

vulnerability (optional)

Vulnerability

EPMWinMac (optional)

Epmwinmac



EpmEcsEventResponseModel

This class holds Epm Ecs Event response

totalRecordsReturned (optional)

Long Total records returned by query format: int64

events (optional)

array[EpmEcsEvent] List of events returned by query



EpmEcsEventSpan

id (optional)

String



EpmEcsEventTrace

id (optional)

String



EpmEcsEventTransaction

id (optional)

String



Epmwinmac

SchemaVersion (optional)

String

GroupId (optional)
String

TenantId (optional)
String

AdapterVersion (optional)
String

ActiveX (optional)
Activex

AuthorizationRequest (optional)
Authorizationrequest

AuthorizingUser (optional)
Authorizinguser

COM (optional)
Com

Configuration (optional)
Configuration

Event (optional)
Event

Installer (optional)
Installer

PrivilegedGroup (optional)
Privilegedgroup

RemotePowerShell (optional)
Remotepowershell

ServiceControl (optional)
Servicecontrol

Session (optional)
Session

StoreApp (optional)
Storeapp

TrustedApplication (optional)
Trustedapplication



id (optional)
String

message (optional)

String
code (optional)
String
type (optional)
String
stack_trace (optional)
String

Event

Type (optional)
String
Action (optional)
String

Faas

name (optional)
String
id (optional)
String
version (optional)
String
coldstart (optional)
Boolean
execution (optional)
String
trigger (optional)
FaaSTrigger

FaaSTrigger

type (optional)
String

request_id (optional)

String



name (optional)

String

attributes (optional)

array[String]

directory (optional)

String

drive_letter (optional)

String

path (optional)

String

target_path (optional)

String

extension (optional)

String

type (optional)

String

device (optional)

String

inode (optional)

String

uid (optional)

String

owner (optional)

String

gid (optional)

String

group (optional)

String

mode (optional)

String

size (optional)

Long format: int64

mtime (optional)

Date format: date-time
ctime (optional)

Date format: date-time
created (optional)

Date format: date-time
accessed (optional)

Date format: date-time
mime_type (optional)

String
fork_name (optional)

String
DriveType (optional)

String
SourceUrl (optional)

String
ZoneTag (optional)

String
ProductVersion (optional)

String
Description (optional)

String
Version (optional)

String
hash (optional)

Hash
pe (optional)

Pe
x509 (optional)

X509
Bundle (optional)

Bundle
Owner (optional)

Owner
code_signature (optional)

CodeSignature
elf (optional)

Elf

 **Geo**

location (optional)

GeoPoint

continent_code (optional)

String

continent_name (optional)

String

country_name (optional)

String

region_name (optional)

String

city_name (optional)

String

country_iso_code (optional)

String

postal_code (optional)

String

region_iso_code (optional)

String

timezone (optional)

String

name (optional)

String

TimezoneOffset (optional)

Long format: int64

 **GeoPoint**

lon (optional)

Double format: double

lat (optional)

Double format: double



Version (optional)

String

DisplayName (optional)

String

ActiveDirectoryPath (optional)

String

LinkInformation (optional)

String



id (optional)

String

name (optional)

String

domain (optional)

String



newName (optional)

String

oldName (optional)

String

newDescription (optional)

String

oldDescription (optional)

String

newsDefault (optional)

Boolean

oldsDefault (optional)

Boolean

addPolicyRevisions (optional)

map[String, String]
removePolicyRevisions (optional)
map[String, String]
newAgents (optional)
map[String, String]
removeAgents (optional)
map[String, String]



GroupListItemModel

locked (optional)

Boolean

errorInfo (optional)

ListItemErrorInfoModel

id (optional)

UUID The Id of the group(Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

name (optional)

String The name of the group

description (optional)

String The description of the group

computerCount (optional)

Integer The Computer count of the group format: int32

activeComputers (optional)

Integer Active Computers in the Group format: int32

created (optional)

Date The created date of resource e.g 2020-12-24 19:09:47, 2020-12-24 19:09:47.6816562, 2020-12-24 19:09:47.6816562 +00:00

format: date-time

policyRevisionId (optional)

UUID format: uuid

policyId (optional)

UUID format: uuid

policyRevisionStatus (optional)

PolicyRevisionState

policyName (optional)

String

revision (optional)

Integer format: int32

default (optional)

Boolean



GroupListItemModelPagedResponse

pageNumber (optional)

Integer format: int32

pageSize (optional)

Integer format: int32

totalRecordCount (optional)

Integer format: int32

pageCount (optional)

Integer format: int32

data (optional)

array[GroupListItemModel]



Hash

md5 (optional)

String

sha1 (optional)

String

sha256 (optional)

String

sha384 (optional)

String

sha512 (optional)

String

ssdeep (optional)

String

t1sh (optional)

String

 **Host**

hostname (optional)

String

name (optional)

String

id (optional)

String

ip (optional)

array[String]

mac (optional)

array[String]

type (optional)

String

uptime (optional)

Long format: int64

architecture (optional)

String

domain (optional)

String

cpu (optional)

HostCpu

disk (optional)

HostDisk

network (optional)

HostNetwork

boot (optional)

HostBoot

pid_ns_ino (optional)

String

DomainIdentifier (optional)

String

NetBIOSName (optional)

String

DomainNetBIOSName (optional)

String

ChassisType (optional)

String

ClientName (optional)

String

DefaultLocale (optional)

String

DefaultUILanguage (optional)

String

geo (optional)

Geo

os (optional)

Os**HostBoot**

id (optional)

String**HostCpu**

usage (optional)

Double format: double**HostDisk**

read (optional)

HostDiskRead

write (optional)

HostDiskWrite**HostDiskRead**

bytes (optional)

Long format: int64

**HostDiskWrite**

bytes (optional)

Long format: int64**HostNetwork**

ingress (optional)

HostNetworkIngress

egress (optional)

HostNetworkEgress**HostNetworkEgress**

bytes (optional)

Long format: int64

packets (optional)

Long format: int64**HostNetworkIngress**

bytes (optional)

Long format: int64

packets (optional)

Long format: int64**Http**

request (optional)

HttpRequest

response (optional)

HttpResponse

version (optional)

String



HttpRequest

id (optional)

String

method (optional)

String

mime_type (optional)

String

body (optional)

HttpRequestBody

referrer (optional)

String

bytes (optional)

Long format: int64



HttpRequestBody

content (optional)

String

bytes (optional)

Long format: int64



HttpResponse

status_code (optional)

Long format: int64

mime_type (optional)

String

body (optional)

HttpResponseBody

bytes (optional)

Long format: int64**HttpResponseBody**

content (optional)

String

bytes (optional)

Long format: int64**InstallationKeyDataAuditingDetailModel**

oldLabel (optional)

String

newLabel (optional)

String

newDisabled (optional)

Boolean

oldDisabled (optional)

Boolean

deleted (optional)

Boolean**Installer**

ProductCode (optional)

String

UpgradeCode (optional)

String

Action (optional)

String

**ListItemErrorInfoModel**

parentTaskName (optional)

String

errorCode (optional)

Integer format: int32

userId (optional)

UUID format: uuid

userAccountName (optional)

String

initiated (optional)

Date format: date-time

**Log**

level (optional)

String

file (optional)

LogFile

logger (optional)

String

origin (optional)

LogOrigin

syslog (optional)

String

**LogFile**

path (optional)

String


 **LogOrigin**

file (optional)

LogOriginFile

function (optional)

String

 **LogOriginFile**

name (optional)

String

line (optional)

Long format: int64

 **Message**

Type (optional)

String

Name (optional)

String

Description (optional)

String

UserReason (optional)

String

Identifier (optional)

String

AuthMethods (optional)

array[String]

Authorization (optional)

Authorization

Authentication (optional)

Authentication



ModifyAcceptedDomainRequest

domain (optional)

String



ModifyGroupRequest

id (optional)

UUID id of the group, for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

name (optional)

String name of the group, for example - Alianse Group

description (optional)

String description of the group, for example - Alianse Group desc



ModifyPolicyRequest

name (optional)

String

description (optional)

String



ModifyUserPreferencesRequest

olsonTimeZoneld (optional)

String

dateTimeDisplayFormat (optional)

String

preferredLanguage (optional)

String



ModifyUserRequest

emailAddress (optional)

String

olsonTimeZoneld (optional)

String

dateTimeDisplayFormat (optional)

String

language (optional)

String



Network

name (optional)

String

type (optional)

String

iana_number (optional)

String

transport (optional)

String

application (optional)

String

protocol (optional)

String

direction (optional)

String

forwarded_ip (optional)

String

community_id (optional)

String

bytes (optional)

Long format: int64

packets (optional)

Long format: int64

inner (optional)

String

vlan (optional)

Vlan



OS Enumeration for Computer Filter

enum

String

- Windows
- Mac



mac (optional)

array[String]

ip (optional)

array[String]

hostname (optional)

String

name (optional)

String

product (optional)

String

vendor (optional)

String

version (optional)

String

serial_number (optional)

String

type (optional)

String

ingress (optional)

String

egress (optional)

String

geo (optional)

Geo

os (optional)

Os**OperationValue**

Storing the values of the scim operation
value (optional)

String Generic string value location if no specific field is specified.

valueBoolean (optional)

Boolean Generic boolean value if no specific field is specified.

active (optional)

Boolean Active value of a user

timezone (optional)

String Timezone value of a user

locale (optional)

String Locale/language value of a user

email (optional)

String Email of a user

role (optional)

String Role of a user

**Operator**

enum

String

- EqualTo
- LessThan
- GreaterThan
- LessThanOrEqualTo
- GreaterThanOrEqualTo



Orchestrator

cluster (optional)

OrchestratorCluster

type (optional)

String

organization (optional)

String

namespace (optional)

String

resource (optional)

OrchestratorResource

api_version (optional)

String



OrchestratorCluster

name (optional)

String

id (optional)

String

url (optional)

String

version (optional)

String



OrchestratorResource

name (optional)

String

type (optional)

String

parent (optional)

OrchestratorResourceParent

ip (optional)

array[String]

id (optional)

String



OrchestratorResourceParent

type (optional)

String



Organization

name (optional)

String

id (optional)

String



Os

type (optional)

String

platform (optional)

String

name (optional)

String

full (optional)

String

family (optional)

String

version (optional)

String

kernel (optional)

String

ProductType (optional)

String

 **Owner**

Identifier (optional)

String

Name (optional)

String

DomainIdentifier (optional)

String

DomainName (optional)

String

DomainNetBIOSName (optional)

String

 **Package**

name (optional)

String

version (optional)

String

build_version (optional)

String

description (optional)

String

size (optional)

Long format: int64

installed (optional)

Date format: date-time

path (optional)

String

architecture (optional)

String

checksum (optional)

String

install_scope (optional)

String

license (optional)

String

reference (optional)

String

type (optional)

String



Pe

original_file_name (optional)

String

file_version (optional)

String

description (optional)

String

product (optional)

String

company (optional)

String

imphash (optional)

String

architecture (optional)

String

pehash (optional)

String



PolicyDataAudtingDetailModel

newName (optional)

String

oldName (optional)

String

newDescription (optional)

String

oldDescription (optional)

String



PolicyGroupsListItemModel

id (optional)

UUID format: uuid

name (optional)

String

description (optional)

String

policyRevisionId (optional)

UUID format: uuid

policyId (optional)

UUID format: uuid

isDefault (optional)

Boolean



PolicyListItemModel

id (optional)

UUID The Id (Guid format), for example - 59A00329-87AC-49EC-BC2C-9B9E26F05185 format: uuid

locked (optional)

Boolean

errorInfo (optional)

ListItemErrorInfoModel

name (optional)

String

size (optional)

Integer format: int32

revision (optional)

Integer format: int32

totalRevisions (optional)

Integer format: int32

totalAssignedRevisions (optional)

Integer format: int32

latestAssignedRevisions (optional)

Integer format: int32

created (optional)

Date format: date-time

lastModified (optional)
Date format: date-time
lastModifiedUserId (optional)
UUID format: uuid
lastModifiedUser (optional)
String
hasOpenDraft (optional)
Boolean
openDraftId (optional)
UUID format: uuid
isAssignedToGroup (optional)
Boolean
draftUserId (optional)
UUID format: uuid
draftUser (optional)
String
lastPolicyToGroupAssignment (optional)
Date format: date-time
checkedOutDate (optional)
Date format: date-time
description (optional)
String
periodLocked (optional)
String



PolicyListItemModelPagedResponse

pageNumber (optional)
Integer format: int32
pageSize (optional)
Integer format: int32
totalRecordCount (optional)
Integer format: int32
pageCount (optional)
Integer format: int32
data (optional)
array[PolicyListItemModel]



PolicyRevisionDataAuditingDetailModel

newGroups (optional)

map[String, String]



PolicyRevisionModel

id (optional)

UUID format: uuid

created (optional)

Date format: date-time

revision (optional)

Integer format: int32

size (optional)

Integer format: int32

comment (optional)

String

user (optional)

String

isAssignedGroup (optional)

Boolean



PolicyRevisionState

enum

String

- OnLatestPolicy
- OnAnEarlierPolicy
- NoPolicy
- AwaitingLatestPolicy
- AwaitingAnEarlierPolicy



Privilegedgroup

Name (optional)

String

RID (optional)

String

Access (optional)

String



ProblemDetails

type

String

title

String

status

integer(\$int32)

detail

String

instance

String



Process

pid (optional)

Long format: int64

entity_id (optional)

String

name (optional)

String

pgid (optional)

Long format: int64

command_line (optional)

String

args (optional)

array[String]

args_count (optional)

Long format: int64

executable (optional)

String

title (optional)

String

thread (optional)

ProcessThread

start (optional)

Date format: date-time

uptime (optional)

Long format: int64

working_directory (optional)

String

exit_code (optional)

Long format: int64

end (optional)

Date format: date-time

interactive (optional)

Boolean

same_as_process (optional)

Boolean

env_vars (optional)

String

entry_meta (optional)

ProcessEntryMeta

tty (optional)

String

ElevationRequired (optional)

Boolean

group (optional)

Group

real_group (optional)

Group

saved_group (optional)

Group

supplemental_groups (optional)

Group

hash (optional)

Hash

pe (optional)

Pe

code_signature (optional)

CodeSignature

elf (optional)

Elf

HostedFile (optional)

File

user (optional)

User

saved_user (optional)

User

real_user (optional)

User

parent (optional)

ProcessParent

entry_leader (optional)

ProcessEntryLeader

session_leader (optional)

ProcessSessionLeader

group_leader (optional)

ProcessGroupLeader

previous (optional)

ProcessPrevious**ProcessEntryLeader**

pid (optional)

Long format: int64

entity_id (optional)

String

name (optional)

String

pgid (optional)

Long format: int64

command_line (optional)

String

args (optional)
array[String]
args_count (optional)
Long format: int64
executable (optional)
String
title (optional)
String
thread (optional)
ProcessThread
start (optional)
Date format: date-time
uptime (optional)
Long format: int64
working_directory (optional)
String
exit_code (optional)
Long format: int64
end (optional)
Date format: date-time
interactive (optional)
Boolean
same_as_process (optional)
Boolean
env_vars (optional)
String
entry_meta (optional)
ProcessEntryMeta
tty (optional)
String
ElevationRequired (optional)
Boolean
group (optional)
Group
real_group (optional)
Group
saved_group (optional)
Group
supplemental_groups (optional)
Group

hash (optional)
Hash
pe (optional)
Pe
code_signature (optional)
CodeSignature
elf (optional)
Elf
HostedFile (optional)
File
user (optional)
User
saved_user (optional)
User
real_user (optional)
User
parent (optional)
ProcessParent



ProcessEntryMeta

type (optional)
String
source (optional)
Source



ProcessGroupLeader

pid (optional)
Long format: int64
entity_id (optional)
String
name (optional)
String
pgid (optional)
Long format: int64

command_line (optional)

String

args (optional)

array[String]

args_count (optional)

Long format: int64

executable (optional)

String

title (optional)

String

thread (optional)

ProcessThread

start (optional)

Date format: date-time

uptime (optional)

Long format: int64

working_directory (optional)

String

exit_code (optional)

Long format: int64

end (optional)

Date format: date-time

interactive (optional)

Boolean

same_as_process (optional)

Boolean

env_vars (optional)

String

entry_meta (optional)

ProcessEntryMeta

tty (optional)

String

ElevationRequired (optional)

Boolean

group (optional)

Group

real_group (optional)

Group

saved_group (optional)

Group

supplemental_groups (optional)

Group

hash (optional)

Hash

pe (optional)

Pe

code_signature (optional)

CodeSignature

elf (optional)

Elf

HostedFile (optional)

File

user (optional)

User

saved_user (optional)

User

real_user (optional)

User



ProcessParent

pid (optional)

Long format: int64

entity_id (optional)

String

name (optional)

String

pgid (optional)

Long format: int64

command_line (optional)

String

args (optional)

array[String]

args_count (optional)

Long format: int64

executable (optional)

String

title (optional)

String

thread (optional)

ProcessThread

start (optional)

Date format: date-time

uptime (optional)

Long format: int64

working_directory (optional)

String

exit_code (optional)

Long format: int64

end (optional)

Date format: date-time

interactive (optional)

Boolean

same_as_process (optional)

Boolean

env_vars (optional)

String

entry_meta (optional)

ProcessEntryMeta

tty (optional)

String

ElevationRequired (optional)

Boolean

group (optional)

Group

real_group (optional)

Group

saved_group (optional)

Group

supplemental_groups (optional)

Group

hash (optional)

Hash

pe (optional)

Pe

code_signature (optional)

CodeSignature

elf (optional)

Elf

HostedFile (optional)

File

user (optional)

User

saved_user (optional)

User

real_user (optional)

User

group_leader (optional)

ProcessGroupLeader**ProcessPrevious**

pid (optional)

Long format: int64

entity_id (optional)

String

name (optional)

String

pgid (optional)

Long format: int64

command_line (optional)

String

args (optional)

array[String]

args_count (optional)

Long format: int64

executable (optional)

String

title (optional)

String

thread (optional)

ProcessThread

start (optional)

Date format: date-time

uptime (optional)

Long format: int64

working_directory (optional)

String

exit_code (optional)

Long format: int64

end (optional)

Date format: date-time

interactive (optional)

Boolean

same_as_process (optional)

Boolean

env_vars (optional)

String

entry_meta (optional)

ProcessEntryMeta

tty (optional)

String

ElevationRequired (optional)

Boolean

group (optional)

Group

real_group (optional)

Group

saved_group (optional)

Group

supplemental_groups (optional)

Group

hash (optional)

Hash

pe (optional)

Pe

code_signature (optional)

CodeSignature

elf (optional)

Elf

HostedFile (optional)

File

user (optional)

User

saved_user (optional)

User

real_user (optional)

User



ProcessSessionLeader

pid (optional)

Long format: int64

entity_id (optional)

String

name (optional)

String

pgid (optional)

Long format: int64

command_line (optional)

String

args (optional)

array[String]

args_count (optional)

Long format: int64

executable (optional)

String

title (optional)

String

thread (optional)

ProcessThread

start (optional)

Date format: date-time

uptime (optional)

Long format: int64

working_directory (optional)

String

exit_code (optional)

Long format: int64

end (optional)

Date format: date-time

interactive (optional)

Boolean

same_as_process (optional)

Boolean

env_vars (optional)

String

entry_meta (optional)

ProcessEntryMeta

tty (optional)

String

ElevationRequired (optional)

Boolean

group (optional)

Group

real_group (optional)

Group

saved_group (optional)

Group

supplemental_groups (optional)

Group

hash (optional)

Hash

pe (optional)

Pe

code_signature (optional)

CodeSignature

elf (optional)

Elf

HostedFile (optional)

File

user (optional)

User

saved_user (optional)

User

real_user (optional)

User

parent (optional)

ProcessParent



ProcessThread

id (optional)

Long format: int64

name (optional)

String



Registry

hive (optional)

String

key (optional)

String

value (optional)

String

path (optional)

String

data (optional)

RegistryData



RegistryData

type (optional)

String

strings (optional)

array[String]

bytes (optional)

String



Related

ip (optional)

array[String]
user (optional)
array[String]
hash (optional)
array[String]
hosts (optional)
array[String]



Remotepowershell

Command (optional)

String



RoleElement

role object

primary (optional)

Boolean booleana flag for whether or not this is the primary role

value (optional)

String User role value



RoleItemModel

Model of role list item

id (optional)

UUID Identifier format: uuid

name (optional)

String Name

resourceId (optional)

String Resource Id

resourceType (optional)

String Resource Type



RoleListItemModel

id (optional)

UUID format: uuid

name (optional)

String

allowPermissions (optional)

array[RolePermissionModel]

denyPermissions (optional)

array[RolePermissionModel] deprecated. rbac only support allow permissions



RoleModel

id (optional)

UUID format: uuid

name (optional)

String

allowPermissions (optional)

array[RolePermissionModel]

denyPermissions (optional)

array[RolePermissionModel] deprecated. rbac only support allow permissions



RolePermissionModel

resource (optional)

String

action (optional)

String



Rule

Identifier (optional)

String

OnDemand (optional)

Boolean

Action (optional)

String**Rulescript**

FileName (optional)

String

Publisher (optional)

String

Outcome (optional)

RulescriptOutcome**RulescriptOutcome**

Version (optional)

String

Name (optional)

String

RuleAffected (optional)

Boolean

Result (optional)

String

Output (optional)

String**SCIMEmail**

primary (optional)

Boolean

value (optional)

String

type (optional)

String



SCIMUserName

givenName (optional)

String

familyName (optional)

String

middleName (optional)

String



ScimAuthenticationSchemes

authentication schemes for scim
name (optional)

String name of authentication

description (optional)

String description of authentication

type (optional)

String type of authentication

primary (optional)

Boolean flag for whether or not the authentication scheme is the primary



ScimBulk

flag to see if scim bulk operations is supported

maxOperations (optional)

Integer max operations format: int32

maxPayloadSize (optional)

Integer max payload size format: int32

supported (optional)

Boolean flag for bulk operations



ScimOperation

SCIM Operations going to be performed on a user
op (optional)

String Operation to be performed on a user. add or replace
path (optional)

String Which field the operation should affect. optional
value (optional)

array[OperationValue] Values of the fields going that are going to be changed



ScimResourceMeta

resource type meta data
resourceType (optional)

String resource type meta data



ScimResourceResponse

Json structure for resource type response
schemas (optional)

array[String] schema

name (optional)

String name of resource type

description (optional)

String description of resource type

endpoint (optional)

String endpoint

schema (optional)

String schema

meta (optional)

ScimResourceMeta



ScimResourceResponseScimListResponse

schemas (optional)
array[String]
totalResults (optional)
Integer format: int32
startIndex (optional)
Integer format: int32
itemsPerPage (optional)
Integer format: int32
Resources (optional)
array[ScimResourceResponse]



ScimSchemaResponse

Structure of the schema response
schemas (optional)
array[String] schema
id (optional)
String id of schema
name (optional)
String name of schema
description (optional)
String description of schema
attributes (optional)
array[Attribute] available attributes
meta (optional)
ScimResourceMeta



ScimSchemaResponseScimListResponse

schemas (optional)
array[String]
totalResults (optional)
Integer format: int32

startIndex (optional)
Integer format: int32
itemsPerPage (optional)
Integer format: int32
Resources (optional)
array[ScimSchemaResponse]



ScimServiceProviderConfigResponse

schemas (optional)
array[String] service provider config schema
patch (optional)
ScimSupported
bulk (optional)
ScimBulk
filter (optional)
ScimSupported
changePassword (optional)
ScimSupported
sort (optional)
ScimSupported
etag (optional)
ScimSupported
authenticationSchemes (optional)
ScimAuthenticationSchemes
meta (optional)
ScimResourceMeta



ScimSupported

Flag to see if scim feature if supported
supported (optional)
Boolean flag to see if scim feature is supported



ScimUserMetaModel

resourceType (optional)

String

created (optional)

Date format: date-time



ScimUserModel

schemas (optional)

array[String]

id (optional)

UUID format: uuid

userName (optional)

String

name (optional)

SCIMUserName

emails (optional)

array[SCIMEmail]

displayName (optional)

String

locale (optional)

String

timezone (optional)

String

externalId (optional)

String

dateTimeFormat (optional)

String

groups (optional)

array[null]

password (optional)

String

active (optional)

Boolean boolean flag of whether or not a user is active

roles (optional)

array[RoleElement] A complex role object for scim

entitlements (optional)
array[RoleElement] A complex role object for scim
meta (optional)
ScimUserMetaModel



ScimUserModelScimListResponse

schemas (optional)
array[String]
totalResults (optional)
Integer format: int32
startIndex (optional)
Integer format: int32
itemsPerPage (optional)
Integer format: int32
Resources (optional)
array[ScimUserModel]



ScimUserPatchRequest

Patch request used to update a user through SCIM
schemas (optional)
array[String] Schema of the request, should be urn:ietf:params:scim:api:messages:2.0:PatchOp
operations (optional)
array[ScimOperation] SCIM Operations going to be performed on a user



Server

address (optional)
String
ip (optional)
String
port (optional)
Long format: int64

mac (optional)
String
domain (optional)
String
registered_domain (optional)
String
top_level_domain (optional)
String
subdomain (optional)
String
bytes (optional)
Long format: int64
packets (optional)
Long format: int64
nat (optional)
ServerNat
as (optional)
As
geo (optional)
Geo
user (optional)
User



ServerNat

ip (optional)
String
port (optional)
Long format: int64



Service

environment (optional)
String
id (optional)
String

name (optional)
String
node (optional)
ServiceNode
type (optional)
String
state (optional)
String
version (optional)
String
ephemeral_id (optional)
String
address (optional)
String
origin (optional)
ServiceOrigin
target (optional)
ServiceTarget



ServiceNode

name (optional)
String
role (optional)
String



ServiceOrigin

environment (optional)
String
id (optional)
String
name (optional)
String
node (optional)
ServiceNode

type (optional)

String

state (optional)

String

version (optional)

String

ephemeral_id (optional)

String

address (optional)

String



ServiceTarget

environment (optional)

String

id (optional)

String

name (optional)

String

node (optional)

ServiceNode

type (optional)

String

state (optional)

String

version (optional)

String

ephemeral_id (optional)

String

address (optional)

String



Servicecontrol

Service (optional)

ServicecontrolService



ServicecontrolService

DisplayName (optional)

String

Name (optional)

String



Session

Administrator (optional)

Boolean

Locale (optional)

String

Identifier (optional)

String

PowerUser (optional)

Boolean

WindowsSessionId (optional)

String

UILanguage (optional)

String



SettingDataAuditingDetailModel

addDomain (optional)

String

removeDomain (optional)

String

modifyDomainOldValue (optional)

String

modifyDomainNewValue (optional)

String



SortDirection



SortModel

by (optional)

String The property on which to sort e.g. name

order (optional)

SortDirection



Source

address (optional)

String

ip (optional)

String

port (optional)

Long format: int64

mac (optional)

String

domain (optional)

String

registered_domain (optional)

String

top_level_domain (optional)

String

subdomain (optional)

String

bytes (optional)

Long format: int64

packets (optional)

Long format: int64

nat (optional)

SourceNat

as (optional)

As

geo (optional)

Geo

user (optional)

User**SourceNat**

ip (optional)

String

port (optional)

Long format: int64**Storeapp**

Name (optional)

String

Publisher (optional)

String

Version (optional)

String**SubAttribute**

Schema for subattributes

name (optional)

String name of attribute

description (optional)

String description of attribute

type (optional)

String type of attribute

canonicalValues (optional)

array[String] list of canonical values

caseExact (optional)

Boolean Flag for whether or not the attribute's casing should be exact

multiValued (optional)

Boolean Flag for whether or not the attribute has multi values

mutability (optional)

String Mutability of the attribute

required (optional)

Boolean Flag for whether or not the attribute is required

returned (optional)

String how the attribute is returned

uniqueness (optional)

String Is the value unique



TaskDetailModel

id (optional)

UUID format: uuid

tenantId (optional)

UUID format: uuid

name (optional)

String

state (optional)

Integer format: int32

stateName (optional)

String

initiated (optional)

Date format: date-time

completed (optional)

Date format: date-time

userId (optional)

UUID format: uuid

user (optional)

String

completedWithErrors (optional)

Boolean

messageParameters (optional)

array[map[String, String]]

 **Threat**

enrichments (optional)
array[ThreatEnrichments]
feed (optional)
ThreatFeed
framework (optional)
String
group (optional)
ThreatGroup
indicator (optional)
ThreatIndicator
software (optional)
ThreatSoftware
tactic (optional)
ThreatTactic
technique (optional)
ThreatTechnique

 **ThreatEnrichments**

indicator (optional)
String
matched (optional)
ThreatEnrichmentsMatched

 **ThreatEnrichmentsMatched**

atomic (optional)
String
field (optional)
String
id (optional)
String
index (optional)

String

occurred (optional)

Date format: date-time

type (optional)

String**ThreatFeed**

dashboard_id (optional)

String

name (optional)

String

description (optional)

String

reference (optional)

String**ThreatGroup**

alias (optional)

array[String]

id (optional)

String

name (optional)

String

reference (optional)

String**ThreatIndicator**

first_seen (optional)

Date format: date-time

last_seen (optional)

Date format: date-time

modified_at (optional)

Date format: date-time

sightings (optional)

Long format: int64

type (optional)

String

description (optional)

String

scanner_stats (optional)

Long format: int64

confidence (optional)

String

ip (optional)

String

port (optional)

Long format: int64

email (optional)

ThreatIndicatorEmail

marking (optional)

ThreatIndicatorMarking

reference (optional)

String

provider (optional)

String

x509 (optional)

X509

as (optional)

As

file (optional)

File

geo (optional)

Geo

registry (optional)

Registry

url (optional)

Url

**ThreatIndicatorEmail**

address (optional)

String**ThreatIndicatorMarking**

tlp (optional)

String**ThreatSoftware**

id (optional)

String

name (optional)

String

alias (optional)

array[String]

platforms (optional)

array[String]

reference (optional)

String

type (optional)

String**ThreatTactic**

id (optional)

array[String]

name (optional)

array[String]

reference (optional)

array[String]



ThreatTechnique

id (optional)

array[String]

name (optional)

array[String]

reference (optional)

array[String]

subtechnique (optional)

ThreatTechniqueSubtechnique



ThreatTechniqueSubtechnique

id (optional)

array[String]

name (optional)

array[String]

reference (optional)

array[String]



Tls

version (optional)

String

version_protocol (optional)

String

cipher (optional)

String

curve (optional)

String

resumed (optional)

Boolean

established (optional)

Boolean

next_protocol (optional)

String

client (optional)

TlsClient

server (optional)

TlsServer



TlsClient

ja3 (optional)

String

server_name (optional)

String

supported_ciphers (optional)

array[String]

subject (optional)

String

issuer (optional)

String

not_before (optional)

Date format: date-time

not_after (optional)

Date format: date-time

certificate_chain (optional)

array[String]

certificate (optional)

String

hash (optional)

TlsClientHash

x509 (optional)

X509



TlsClientHash

md5 (optional)

String

sha1 (optional)

String

sha256 (optional)

String



TlsServer

ja3s (optional)

String

subject (optional)

String

issuer (optional)

String

not_before (optional)

Date format: date-time

not_after (optional)

Date format: date-time

certificate_chain (optional)

array[String]

certificate (optional)

String

hash (optional)

TlsServerHash

x509 (optional)

X509



TlsServerHash

md5 (optional)

String

sha1 (optional)

String

sha256 (optional)

String**Token**

Name (optional)

String

Description (optional)

String

Identifier (optional)

String**Trustedapplication**

Name (optional)

String

Version (optional)

String**UnassignComputersToGroupRequest**

allComputers (optional)

Boolean

filter (optional)

ComputerFilterModel

excludedComputerIds (optional)

array[UUID] format: uuid

selectionComputerIds (optional)

array[UUID] selection computers ids will work when "allComputers" : false format: uuid

 **Url**

original (optional)

String

full (optional)

String

scheme (optional)

String

domain (optional)

String

registered_domain (optional)

String

top_level_domain (optional)

String

subdomain (optional)

String

port (optional)

Long format: int64

path (optional)

String

query (optional)

String

extension (optional)

String

fragment (optional)

String

username (optional)

String

password (optional)

String

 **User**

id (optional)

String

name (optional)

String

full_name (optional)

String

email (optional)

String

hash (optional)

String

domain (optional)

String

roles (optional)

array[String]

DomainIdentifier (optional)

String

DomainNetBIOSName (optional)

String

DefaultLocale (optional)

String

DefaultTimezoneOffset (optional)

Long format: int64

DefaultUILanguage (optional)

String

LocalIdentifier (optional)

Long format: int64

group (optional)

Group

target (optional)

UserTarget

effective (optional)

UserEffective

changes (optional)

UserChanges



UserAgent

original (optional)

String

name (optional)

String

version (optional)

String

device (optional)

UserAgentDevice

os (optional)

Os**UserAgentDevice**

name (optional)

String**UserChanges**

id (optional)

String

name (optional)

String

full_name (optional)

String

email (optional)

String

hash (optional)

String

domain (optional)

String

roles (optional)

array[String]

DomainIdentifier (optional)

String

DomainNetBIOSName (optional)

String

DefaultLocale (optional)

String

DefaultTimezoneOffset (optional)

Long format: int64

DefaultUILanguage (optional)

String

LocalIdentifier (optional)

Long format: int64

group (optional)

Group**UserDataAuditing**

Activity Audit User Data

newEmailAddress (optional)

String New Email Address

oldEmailAddress (optional)

String Old Email Address

newOlsonTimeZoneld (optional)

String New Timezone

oldOlsonTimeZoneld (optional)

String Old Timezone

newDateTimeDisplayFormat (optional)

String New Datetime Display Format

oldDateTimeDisplayFormat (optional)

String Old Datetime Display Format

newPreferredLanguage (optional)

String New Preferred Language

oldPreferredLanguage (optional)

String Old Preferred Language

newDisabled (optional)

Boolean New Disabled

oldDisabled (optional)

Boolean Old Disabled

newUserType (optional)

String new user type

oldUserType (optional)

String old user type

roles (optional)

array[ActivityAuditRoleResourceModel] Role audit data



UserDetailModel

id (optional)

UUID format: uuid

accountName (optional)

String

emailAddress (optional)

String

created (optional)

Date format: date-time

isFirstSignIn (optional)

Boolean

lastSignedIn (optional)

Date format: date-time

disabled (optional)

Boolean

roles (optional)

array[UserRoleResourceItemModel]

olsonTimeZoneId (optional)

String

dateTimeDisplayFormat (optional)

String

language (optional)

String

allowInvites (optional)

Boolean



UserEffective

id (optional)

String

name (optional)

String

full_name (optional)

String

email (optional)

String

hash (optional)
String
domain (optional)
String
roles (optional)
array[String]
DomainIdentifier (optional)
String
DomainNetBIOSName (optional)
String
DefaultLocale (optional)
String
DefaultTimezoneOffset (optional)
Long format: int64
DefaultUILanguage (optional)
String
LocalIdentifier (optional)
Long format: int64
group (optional)
Group



UserListItemModel

Model of user list item
locked (optional)
Boolean
errorInfo (optional)
ListItemErrorInfoModel
id (optional)
UUID User identifier format: uuid
accountName (optional)
String Account name
emailAddress (optional)
String Email
created (optional)
Date Creation date format: date-time
lastSignedIn (optional)
Date Last logged in date format: date-time

disabled (optional)
Boolean Is user disabled
roles (optional)
array[RoleItemModel] List of user roles
roleName (optional)
String Role name
olsonTimeZoneld (optional)
String Time zone
dateTimeDisplayFormat (optional)
String Date and time display format
language (optional)
String Preferred language



UserListItemModelPagedResponse

pageNumber (optional)
Integer format: int32
pageSize (optional)
Integer format: int32
totalRecordCount (optional)
Integer format: int32
pageCount (optional)
Integer format: int32
data (optional)
array[UserListItemModel]



UserRoleResourceItemModel

id (optional)
UUID format: uuid
name (optional)
String
allowPermissions (optional)
array[RolePermissionModel]
denyPermissions (optional)
array[RolePermissionModel] deprecated. rbac only support allow permissions

resourceId (optional)

String

resourceType (optional)

String



UserTarget

id (optional)

String

name (optional)

String

full_name (optional)

String

email (optional)

String

hash (optional)

String

domain (optional)

String

roles (optional)

array[String]

DomainIdentifier (optional)

String

DomainNetBIOSName (optional)

String

DefaultLocale (optional)

String

DefaultTimezoneOffset (optional)

Long format: int64

DefaultUILanguage (optional)

String

LocalIdentifier (optional)

Long format: int64

group (optional)

Group

 **Vlan**

id (optional)

String

name (optional)

String

 **Vulnerability**

classification (optional)

String

enumeration (optional)

String

reference (optional)

String

score (optional)

VulnerabilityScore

category (optional)

array[String]

description (optional)

String

id (optional)

String

scanner (optional)

VulnerabilityScanner

severity (optional)

String

report_id (optional)

String

 **VulnerabilityScanner**

vendor (optional)

String

 **VulnerabilityScore**

base (optional)

Double format: double

temporal (optional)

Double format: double

environmental (optional)

Double format: double

version (optional)

String

 **Workstyle**

Name (optional)

String

Description (optional)

String

Identifier (optional)

String

 **X509**

version_number (optional)

String

serial_number (optional)

String

issuer (optional)

X509Issuer

signature_algorithm (optional)

String

not_before (optional)

Date format: date-time

not_after (optional)

Date format: date-time

subject (optional)

X509Subject

public_key_algorithm (optional)

String

public_key_size (optional)

Long format: int64

public_key_exponent (optional)

Long format: int64

public_key_curve (optional)

String

alternative_names (optional)

array[String]**X509Issuer**

distinguished_name (optional)

String

common_name (optional)

array[String]

organizational_unit (optional)

array[String]

organization (optional)

array[String]

locality (optional)

array[String]

state_or_province (optional)

array[String]

country (optional)

array[String]**X509Subject**

distinguished_name (optional)

String

common_name (optional)

array[String]

organizational_unit (optional)

array[String]
organization (optional)
array[String]
locality (optional)
array[String]
state_or_province (optional)
array[String]
country (optional)
array[String]



id (optional)
String
code (optional)
String
kind (optional)
String
category (optional)
array[String]
action (optional)
String
outcome (optional)
String
type (optional)
array[String]
module (optional)
String
dataset (optional)
String
provider (optional)
String
severity (optional)
Long format: int64
original (optional)
String
hash (optional)
String

duration (optional)
Long format: int64
sequence (optional)
Long format: int64
timezone (optional)
String
created (optional)
Date format: date-time
start (optional)
Date format: date-time
end (optional)
Date format: date-time
risk_score (optional)
Double format: double
risk_score_norm (optional)
Double format: double
ingested (optional)
Date format: date-time
reference (optional)
String
url (optional)
String
reason (optional)
String
agent_id_status (optional)
String



id (optional)
String
uuid (optional)
String
version (optional)
String
name (optional)
String
description (optional)

String

category (optional)

String

ruleset (optional)

String

reference (optional)

String

author (optional)

array[String]

license (optional)

String**id_AssignComputersByCsv_body**

csvFile (optional)

byte[] format: binary